# Analysis and Design of a Novel Active Soft Switched Phase-Shifted Full Bridge Converter

Naga Brahmendra Yadav Gorla, Dr. Lakshmi Narasamma N

Abstract—This paper proposes an active soft-switching circuit for bridge converters aiming to improve the power conversion efficiency. The proposed circuit achieves loss-less switching for both main and auxiliary switches without increasing the main switch current/voltage rating. A winding coupled to the primary of power transformer ensures ZCS for the auxiliary switches during their turn-off. A 350 W, 100 kHz phase shifted full bridge (PSFB) converter is built to validate the analysis and design. Theoretical loss calculations for proposed circuit is presented. The proposed circuit is compared with passive soft switched PSFB in terms of efficiency and loss in duty cycle.

Keywords—Active soft switching, passive soft switching, ZVS, ZCS, PSFB.

# I. INTRODUCTION

**P**HASE shifted full bridge (PSFB) DC-DC converter is extensively used in applications such as automobile inverters, telecom power supplies, un-interrupted power supplies, stand-alone/grid connected inverters fed from renewable energy sources. The phase shift introduced between two legs creates additional freewheeling intervals in the primary side. Output voltage is a function of the phase shift. This topology uses transformer's leakage inductance and intrinsic capacitance of switching devices to achieve ZVS for the active switches [1]- [4]. Analysis of lagging, leading leg transitions and ZVS range calculations has been reported in [1], [5] respectively. In these topologies, energy stored in the leakage inductor may not be sufficient to achieve ZVS for the lagging leg under high input voltage and/or light load conditions.

PSFB with passive soft switching circuits for wide ZVS ranges has been presented in [6]- [10]. In these topologies, the additional series inductance in the primary of transformer adversely effects the performance of the converter causing the loss in duty cycle and severe voltage ringing across the devices in the secondary side [11].

All the active soft switched PSFB converters have auxiliary circuit added in parallel to the full bridge, which ensures soft switching for main switches. The active soft switching circuits for PSFB has been reported in [8]- [16]. The limitations in these topologies are narrow ZVS range of load, loss in duty cycle, the voltage stress across the devices in the secondary side, circulating loss in the primary side circuit etc.

A new active soft switching circuit for bridge converters is proposed in this paper which addresses some of the problems mentioned above. PSFB topology is chosen to validate the analysis. Proposed circuit is connected in parallel to the

Naga Brahmendra Yadav Gorla and Dr.Lakshmi Narasamma N are with the Department of Electrical Engineering, Indian Institute of Technology Madras, Chennai 600036, India. email:gorla.indra@gmail.com lagging leg as shown in Fig. 1 to achieve ZVS for switches in lagging leg. Novelty of the circuit lies in achieving zero voltage switching for main switches in lagging leg, zero current switching for active switches in auxiliary circuit.

This paper is organized as follows: Steady state analysis with necessary mathematical expressions and waveforms of the proposed circuit is discussed in section II. Design strategy and experimental results of the proposed converter are covered in section III and IV respectively. Theoretical loss calculations and loss in duty cycle are presented in sections V and VI respectively. Section VII presents the conclusion and references.

#### II. STEADY STATE ANALYSIS



Fig. 1. Proposed active soft switched full bridge DC-DC converter with Auxiliary circuit.

Steady state analysis of proposed PSFB is presented in this section. Analysis of converter is divided into twelve intervals. In the following analysis, voltage drops across the devices are neglected. The output filter inductor is large enough to assume constant load current. Turns ratio between the primary of power transformer and coupled winding  $(L_T)$  is chosen as  $k_T$ . Switching sequence and switching transients are shown in Fig. 3. Magnified portion of the image selected by the rectangle box in Fig. 3 is depicted in Fig. 4.  $\theta$  is the phase shift introduced between lagging and leading legs of PSFB. The auxiliary switches are gated prior to the corresponding main switches in order to ensure their ZVS.

**Interval 0** ( $t < t_0$ ): Prior to  $t_0$ , anti parallel diode  $D_{B1}$  and  $S_2$  are in conduction. Gating  $S_1$  at  $t=t_0$  ensures ZVS to the main switch  $S_1$ .  $L_m$  is magnetizing inductance of transformer.

$$C_1 = C_2 = C_3 = C_4 = C; C_{4r} = C_{1r} = C_r$$
$$v_{C1}(t_0) = v_{C2}(t_0) = 0; v_{C3}(t_0) = v_{C4}(t_0) = V_{dc}; i'(t_0) = nI$$

**Interval 1** ( $t_0 < t < t_1$ ): This is positive power transfer interval wherein, main switches  $S_1$ ,  $S_2$ , output rectifier diodes  $D_1$ ,  $D_2$  are in conduction carrying full load current. Fig. 2(a) illustrates circuit conditions during interval 1.

Manuscript received December 15, 2012; revised December 25, 2012.

Voltage across the primary  $(v_{ab})$  and reflected load current (i') during this interval are given as,

$$L_m \frac{di_m(t-t_0)}{dt} = v_{ab}(t-t_0) = V_{dc}$$
$$i_p(t-t_0) = i'(t-t_0) + i_m(t-t_0) = nI + i_m(t-t_0)$$

At  $t = t_1$ , gating to main switch  $S_2$  is removed.

**Interval 2**  $(t_1 < t < t_2)$ : When gating to  $S_2$  falls below the threshold level, primary current  $(i_p)$  which was initially flowing through  $S_2$ , will now flows through the capacitor  $C_2$ .  $C_2$  across the switch  $S_2$  is chosen such that turn-off of  $S_2$  is a loss less transition. Rectifier diodes  $D_1$  and  $D_2$  continues to conduct since voltage across the primary of transformer is positive. Magnetizing current is assumed to be at  $i_m^*$ . Fig 2(b) explains circuit conditions during interval 2.

$$\frac{dv_{C3}(t-t_1)}{dt} = \frac{i_p(t-t_1)}{2C}$$

$$V_{dc} - L_m \frac{di_p(t-t_1)}{dt} - v_{C2}(t-t_1) = 0,$$
where  $i_p(t-t_1) = i'(t-t_1) + i_m(t-t_1) = nI + i_m^*$ 

At the end of interval 2,  $S_3$  is turned on with a delay  $t_d$  as shown in Fig. 3. The design should ensures that  $C_3$  discharge completely and  $D_{B3}$  begins to conduct within the time delay.

**Interval 3**  $(t_2 < t < t_3)$ : This is freewheeling interval wherein, main switch  $S_1$  and diode  $D_{B3}$  are in conduction as shown in Fig 2(c). Voltage across the primary of the transformer is zero, all the output rectifier diodes are in conduction sharing full load current equally. This makes the reflected load current in the primary of the transformer zero. Magnetizing current  $(i_m^*)$  freewheels in the transformer primary during this interval.

$$L_m \frac{di_m(t-t_2)}{dt} = 0; i_m(t-t_2) = i_m^*$$
$$i_p(t-t_2) = i'(t-t_2) + i_m(t-t_2) = i_m^*$$
$$i_{D1}(t-t_2) = i_{D3}(t-t_2) = \frac{I}{2}$$

Interval 3 ends at  $t = t_3$ , when gating to  $S_1$  is removed.

**Interval 4**  $(t_3 < t < t_4)$ : This is the interval during which auxiliary circuit becomes active. Main switch  $S_1$  is turned off and auxiliary switch  $S_{4a}$  is gated at  $t = t_3$ . Fig. 2(d) describes circuit conditions during interval 4. Voltage across the resonant inductor  $(v_{Lr})$  is  $V_{dc}$  during this interval. Current through resonant inductor raises linearly as,

$$i_{Lr}(t) = \frac{V_{dc}}{L_r}(t - t_3)$$
$$i'(t - t_3) = n(i_{D1}(t - t_3) - i_{D3}(t - t_3))$$

At the end of this interval i.e., at  $t = t_4$  auxiliary inductor current reaches load current,  $D_3$  and  $D_4$  starts conducting full load current.

$$T_1 = \frac{L_r n I}{V_{dc}}, where \ T_1 = (t_4 - t_3)$$
 (1)

**Interval 5**  $(t_4 < t < t_5)$ : Resonant elements  $L_r$  and  $C_{4r}$  resonates during this interval. Fig 2(e) shows the circuit



Fig. 3. Key waveforms for proposed Active Soft Switched PSFB DC-DC converter  $% \left( {{{\rm{DC}}} \right)_{\rm{T}}} \right)$ 



Fig. 4. Auxiliary interval waveforms

condition during this interval. Resonant inductor current  $(i_{Lr})$ 

# International Journal of Electrical, Electronic and Communication Sciences ISSN: 2517-9438 Vol:7, No:1, 2013



(a) Interval 1:  $(t_0 < t < t_1)$  Positive power transfer interval.



(c) Interval 3:  $(t_2 < t < t_3)$  Freewheeling interval



(e) Interval 5:  $(t_4 < t < t_5)$  Main switch  $S_4$  auxiliary interval 2.

Fig. 2. Proposed active soft switched converter circuit conditions for intervals 1-6.

and resonant capacitor voltage  $(v_{Cr})$  are given as,

$$i_{Lr}(t - t_4) = nI + V_{dc} \sqrt{\frac{C_r}{L_r}} sin(w(t - t_4)) \quad (2)$$
$$v_{C4r}(t - t_4) = V_{dc} cos(w(t - t_4)), where \ w = \frac{1}{\sqrt{L_r C_r}}$$

At the end of this interval, at  $t = t_5$ 

$$V_{dc}cos(w(t_5 - t_4)) = \frac{-V_{dc}}{k_T}$$
  
$$T_2 = (t_5 - t_4) = \frac{1}{w}\cos^{-1}(\frac{-1}{k_T})$$
(3)

At the end of this interval, voltage across resonant capacitor reaches  $\frac{-V_{dc}}{k_T}$ . This forward biases the anti parallel diode  $D_{B4}$  across the main switch  $S_4$  as shown in Fig. 4.

**Interval 6** ( $t_5 < t < t_6$ ): Fig 2(f) shows the circuit condition during interval 6. Voltage across the Resonant capacitor is  $\frac{-V_{dc}}{k_T}$  which resets the resonant inductor current to zero as,

$$i_{Lr}(t) = i_{Lr}(t_5) - \frac{V_{dc}}{k_T L_r}(t - t_5)$$
$$= (nI + V_{dc}\sqrt{\frac{C_{r4}}{L_r}}(\frac{\sqrt{k_T^2 - 1}}{k_T})) - \frac{V_{dc}}{k_T L_r}(t - t_5)$$

At the end of this interval, at  $t = t_6$ 

$$T_3 = \frac{nIk_T L_r}{V_{dc}} + w_r \sqrt{k_T^2 - 1}; \quad where, T_3 = (t_6 - t_5) \quad (4)$$

Turning off  $S_{4a}$  after  $i_{Lr}(t)$  becoming zero ensures ZCS during turn-off for the auxiliary switch. Gating  $S_4$  after  $t = t_5$  ensures ZVS during turn-on.



(b) Interval 2:  $(t_1 < t < t_2)$  Transition from positive power to freewheeling.



(d) Interval 4:  $(t_3 < t < t_4)$  Main switch  $S_4$  auxiliary interval 1.



(f) Interval 6:  $(t_5 < t < t_6)$  Main switch  $S_4$  auxiliary interval 3.

**Interval 7** ( $t_6 < t < t_7$ ): Main switches  $S_3$ ,  $S_4$  output rectifier diodes  $D_3$ ,  $D_4$  are in conduction during this interval.

$$L_m \frac{di_m(t-t_6)}{dt} = v_{ab}(t-t_6) = -V_{dc}$$
$$i_p(t-t_6) = i'(t-t_6) + i_m(t-t_6); i'(t-t_6) = -nI$$

Analysis of interval 8 to 12 is similar to that of intervals 1 to 7.

### III. DESIGN STRATEGY

Design guidelines for proposed PSFB DC-DC converter is presented in this section.

#### A. Filter components design

- 1) The process of selecting filter inductor  $(L_f)$ , filter capacitor  $(C_f)$  is same as the traditional PWM bridge converters.
- In the proposed topology, voltage and current rating of the active and passive devices are same as the conventional PWM bridge converter.

#### B. Auxiliary circuit components design

The auxiliary circuit components design include design of resonant inductor and capacitor.

1) Ratio between resonant frequency  $f_r$  and switching frequency  $f_s$  is so chosen that losses due to resonant circuit should be low.

$$f_r = k * f_s = \frac{1}{2\Pi\sqrt{L_r C_r}} \tag{5}$$

2) Interval 5 in steady stare analysis describes the resonant intervals. During these intervals, auxiliary inductor  $L_r$  resonates with auxiliary capacitor  $C_r$ . The peak resonant inductor current  $(i_{PLr})$  is given as,

$$i_{PLr} = nI + V_{dc} \sqrt{\frac{C_r}{L_r}} \tag{6}$$

- 3) The rate of rise of current in the auxiliary circuit during the interval 5 depends on  $L_r$ .
  - a) Larger value of  $L_r$  increases the length of the interval  $T_1$  as well as  $T_2$ . Effective duty cycle also gets reduced because of Larger  $T_1$ .
  - b) Smaller value of  $L_r$  increases the peak of auxiliary inductor current which intern increases the conduction losses.

#### C. Choice of coupled inductor turns

Turns ratio between primary of power transformer and coupled inductor  $(k_T)$  decides the resonant period  $T_2$  as well as reseting period for auxiliary inductor current  $T_3$ .

a) For a given  $k_T$ , resonant period  $T_2$  is given by equation 3 and auxiliary current resetting period is given by equation 4.

Specifications of proposed active soft switched PSFB DC-DC converter for 350 W based on the above design strategies are shown in table I. The proposed circuit is compared with traditional passive soft switching circuit reported in [1] in terms of steady state losses and loss in duty cycle in the subsequent sections.

 TABLE I

 Specifications of proposed Active soft switched PSFB DC-DC converter

S.no	description	values
1	Supply voltage	40-57 Volts
2	Output voltage	400 Volts
3	Output power	350 Watts
4	Filter inductance	10 mH
5	Filter capacitance	5.6 µF
6	Resonant inductance	$1 \mu H$
7	Resonant capacitance	15 nF
8	Switching frequency	100 kHz

# IV. RESULTS AND DISCUSSIONS

Table I shows the design specifications used in building laboratory test setup and in simulations. Efficiency of passive soft switched and Proposed active soft switched converter is compared in Table II.

Gating sequence of auxiliary switches and corresponding lagging leg switches are shown in fig. 5. Gating for auxiliary switch  $S_{4a}$ , auxiliary inductor current  $(I_{Lr})$ , gate to source and drain to source voltage of main switch  $S_4$  are shown in fig. 6. It can be observed that, the auxiliary inductor current  $(I_{Lr})$ raises from zero when gating is given to auxiliary switch  $S_{4a}$ . This reduces the turn-on losses in the auxiliary switch. Gating to auxiliary switch  $S_{4a}$  is removed when  $I_{Lr}$  is reseted. This reduces the turn-off losses in  $S_{4a}$ . RMS current through the auxiliary switches  $(I_{Lr})$  is less since it is operated for small durations. Hence conduction losses in the auxiliary switches



Fig. 5. (From top) gating to the switch  $S_1$  (scale=10 V/div), gating to auxiliary switch  $S_{1a}$  (scale=20 V/div), gating to switch  $S_4$  (scale=10 V/div), gating to auxiliary switch  $S_{4a}$  (scale=20 V/div), x-axis scale=2  $\mu$ s/div.



Fig. 6. (From top) gating to the auxiliary switch  $S_{4a}$  (scale=10 V/div), auxiliary inductor current (scale=10 A/div), gating to lagging leg switch  $S_4$  (scale=10 V/div), drain to source voltage of  $S_4$  (scale=50 V/div), x-axis scale=2  $\mu$ /div.



Fig. 7. (From top) gating to the auxiliary switch  $S_{4a}$  (scale=5 V/div), auxiliary inductor current (scale=5 A/div), gating to lagging leg switch  $S_4$  (scale=10 V/div), drain to source voltage of  $S_4$  (scale=50 V/div) at 20% load, x-axis scale=800 ns/div.

are less even though peak current is more than load current. Drain to source voltage for lagging leg switch is zero when it is switched on with auxiliary circuit. This reduces turn-on losses in lagging leg switches (fig. 7, fig 8) contributing an overall improvement in the conversion efficiency as shown in table II.

#### V. LOSS CALCULATIONS

Auxiliary inductor current is approximated as triangular wave for reducing the complexity of analysis. The RMS



Fig. 8. (From top) gating to the auxiliary switch  $S_{4a}$  (scale=10 V/div), auxiliary inductor current (scale=10 A/div), gating to lagging leg switch  $S_4$  (scale=10 V/div), drain to source voltage of  $S_4$  (scale=50 V/div) at 80% load, x-axis scale=800 ns/div.

current through resonant inductor is given as

$$I_{Lr_{rms}} = I_{PLr} \sqrt{\frac{2(T_1 + T_2 + T_3)f_s}{3}}$$
(7)

where  $T_1$ ,  $T_2$ ,  $T_3$  are given by equations 1, 3, 4 respectively. Auxiliary circuit losses include conduction losses in auxiliary switches ( $S_{1a}$ ,  $S_{4a}$ ), and auxiliary diodes ( $D_{1a}$ ,  $D_{4a}$ ). The switching losses in active switches of the auxiliary circuit are zero due to ZCS as stated earlier (fig. 6). Auxiliary circuit loss is approximately 6.75% of passive soft switching losses.



Fig. 9. Theoretical loss calculation of a 350 W proposed active soft switched PSFB and passive soft switched PSFB. The losses are calculated for several items: PL1-auxiliary circuit losses; PL2-main circuit conduction losses; PL3-rectifier diodes conduction losses; PL4-rectifier diode recovery losses at 70% load condition.

Theoretical loss calculations for 350 W proposed active soft switched PSFB and passive soft switched PSFB converter at 70% load conditions are compared in fig. 9. The proposed auxiliary circuit reduces the main switch switching losses, improving the over all conversion efficiency of converter as shown in Table II. Conduction loss in the main switches of proposed active soft switched PSFB is approximately half of passive soft switched PSFB due to the fact that the current during freewheeling intervals is magnetizing current instead of reflected full load current. Output rectifier diode current during freewheeling period is reduced to half of load current in the proposed active soft switched PSFB converter, in turn reduces the rectifier conduction and recovery losses considerably as depicted in fig. 9. There is an over all reduction of 37.3% in losses with proposed active soft switched PSFB at 70 % load condition.

# VI. LOSS IN DUTY CYCLE WITH PROPOSED ACTIVE AND PASSIVE SOFT SWITCHING

# A. Passive soft switching

Loss in duty cycle for passive soft switching case is  $\Delta D_p$  as reported in [1].

$$\Delta D_p = \frac{2n_p(i_1 + i_2)f_s L_s}{V_{dc}}$$
$$\cong \Delta D_p = \frac{4n_p I f_s L_s}{V_{dc}}$$
(8)

Effective duty cycle in passive soft switching PSFB converter  $(D_{effp})$  is

$$D_{effp} = D - \Delta D_p$$

Effective output voltage of the converter in passive soft switching PSFB  $(V_{op})$  is given as

$$V_{op} = V_{dc}n_p D_{effp}$$
  
=  $V_{dc}n_p (D - \frac{4n_p I f_s L_s}{V_{dc}}) = V_{dc}n_p D - 4n_p^2 I f_s L_s$ 

where,  $n_p$  is number of turns of power transformer in passive soft switched PSFB converter.

# B. Proposed Active soft switching

Interval 4 explains the first auxiliary interval in the proposed converter. All the rectifier diodes are in conduction till the auxiliary inductor current reaches reflected load current. This reduces the effective duty of the converter. Loss in the duty corresponds to the period  $T_1$  is  $\Delta D_a$ .

$$\Delta D_a = \frac{2n_a I L_r f_s}{V_{dc}} \tag{9}$$

Effective duty cycle in proposed active soft switching PSFB converter  $(D_{effa})$  is

$$D_{effa} = D - \Delta D_a$$

Effective output voltage of the converter in proposed circuit  $(V_{oa})$  is given as

$$V_{oa} = V_{dc}n_a D_{effa}$$
  
=  $V_{dc}n_a (D - \frac{2n_a I f_s L_r}{V_{dc}}) = V_{dc}n_a D - 4n_a^2 I f_s L_r$ 

where,  $n_a$  is number of turns of power transformer in proposed active soft switched PSFB converter. Loss in duty cycle of the proposed active soft switched PSFB and passive soft switched PSFB for different load conditions is plotted for common specifications given in table I. It can be seen from the fig. 10 that for any given load, output voltage can be realized with minimum duty loss in the proposed active soft switched converter.



Fig. 10. Loss in duty cycle for passive soft switching PSFB and proposed circuit under different load conditions.

TABLE II EFFICIENCIES FOR PASSIVE AND ACTIVE SOFT SWITCHED PSFB DC-DC.

%	Passive Soft	Proposed Active
load	Switched % $\eta$	Soft Switched $\%\eta$
15	79.83	85.10
20	78.19	88.36
30	82.35	92.57
40	81.46	89.75
50	82.5	89.45
60	84.38	89.5
70	84.02	89.56
80	83.99	87.60
90	83.43	87.79
100	83.42	86.95

# VII. CONCLUSION

Ξ

A new active soft switching circuit for bridge converters is proposed in this paper. The novelty of the proposed circuit lies in achieving ZVS during turn-on for main switch and ZCS during turn-on and turn-off for the auxiliary switches. Proposed circuit is compared with conventional passive soft switched PSFB in terms of steady state efficiency and loss in duty cycle. There is an efficiency improvement of about 5% at 70% load condition. Improvement in efficiency is observer from 10% to 100% load conditions.

#### REFERENCES

- Sabate, J.A.; Vlatkovic, V.; Ridley, R.B.; Lee, F.C.; Cho, B.H.; , "Design considerations for high-voltage high-power full-bridge zero-voltageswitched PWM converter," *Applied Power Electronics Conference and Exposition*, 1990. APEC '90, Conference Proceedings 1990., Fifth Annual , vol., no., pp.275-284, 11-16 March 1990.
- [2] Mweene, L.H.; Wright, C.A.; Schlecht, M.F.; , "A 1 kW 500 kHz frontend converter for a distributed power supply system," *Power Electronics, IEEE Transactions on*, vol.6, no.3, pp.398-407, Jul 1991.
- [3] Song-Yi Lin; Chern-Lin Chen; , "Analysis and design for RCD clamped snubber used in output rectifier of phase-shift full-bridge ZVS converters," *Industrial Electronics, IEEE Transactions on*, vol.45, no.2, pp.358-359, Apr 1998.
- [4] Moschopoulos, G.; Jain, P.; , "ZVS PWM full-bridge converters with dual auxiliary circuits," *Telecommunications Energy Conference*, 2000. INTELEC. Twenty-second International , vol., no., pp.574-581, 2000.
- [5] Chao Yan; Hongyang Wu; Jianhong Zeng; Ying Jianping; Jingtao Tan; , "A precise ZVS range calculation method for full bridge converter,"*Power Electronics Specialist Conference*, 2003. PESC '03. 2003 IEEE 34th Annual , vol.4, no., pp. 1832- 1836 vol.4, 15-19 June 2003.

- [6] Borage, M.; Tiwari, S.; Bhardwaj, S.; Kotaiah, S.; , "A Full-Bridge DCDC Converter With Zero-Voltage-Switching Over the Entire Conversion Range,"*Power Electronics, IEEE Transactions on*, vol.23, no.4, pp.1743-1750, July 2008.
- [7] Chen Zhao; Xinke Wu; Peipei Meng; Zhaoming Qian; , "Optimum Design Consideration and Implementation of a Novel Synchronous Rectified Soft-Switched Phase-Shift Full-Bridge Converter for Low-Output-Voltage High-Output-Current Applications," *Power Electronics, IEEE Transactions on*, vol.24, no.2, pp.388-397, Feb. 2009.
- [8] Moschopoulos, G.; Jain, P.; , "ZVS PWM full-bridge converters with dual auxiliary circuits," *Telecommunications Energy Conference*, 2000. INTELEC. Twenty-second International , vol., no., pp.574-581, 2000.
- [9] Cho, J.G.; Sabate, J.A.; Lee, F.C.; , "Novel full bridge zero-voltagetransition PWM DC/DC converter for high power applications," *Applied Power Electronics Conference and Exposition*, 1994. APEC '94. Conference Proceedings 1994., Ninth Annual , vol., no., pp.143-149 vol.1, 13-17 Feb 1994.
- [10] Moschopoulos, G.; Jain, P.; , "A PWM full-bridge converter with load independent soft-switching capability," *Applied Power Electronics Conference and Exposition*, 2000. APEC 2000. Fifteenth Annual IEEE , vol.1, no., pp.79-85 vol.1, 2000.
- [11] Ordonez, M.; Quaicoe, J.E.; , "Soft-Switching Techniques for Efficiency Gains in Full-Bridge Fuel Cell Power Conversion," *Power Electronics*, *IEEE Transactions on*, vol.26, no.2, pp.482-492, Feb. 2011.
- [12] Mason, A.J.; Tschirhart, D.J.; Jain, P.K.; , "New ZVS Phase Shift Modulated Full-Bridge Converter Topologies With Adaptive Energy Storage for SOFC Application," *Power Electronics, IEEE Transactions on*, vol.23, no.1, pp.332-342, Jan. 2008.
- [13] Lakshminarasamma, N.; Ramanarayanan, V.; , "A Family of Auxiliary Switch ZVS-PWM DCDC Converters With Coupled Inductor," *Power Electronics, IEEE Transactions on*, vol.22, no.5, pp.2008-2017, Sept. 2007.
- [14] Lakshminarasamma, N.; Ramanarayanan, V.; , "A Family of Auxiliary Switch ZVS-PWM DC-DC Converters with Coupled Inductor," *IEEE Industrial Electronics*, IECON 2006 - 32nd Annual Conference on , vol., no., pp.2660-2665, 6-10 Nov. 2006.
- [15] Brahmendra, B.N.; Lakshminarasamma, N.; , "Novel soft transition pushpull converter: Analysis, modeling, design and implementation," *IECON 2011 - 37th Annual Conference on IEEE Industrial Electronics Society* , vol., no., pp.1486-1491, 7-10 Nov. 2011.
- [16] Lakshminarasamma N, V Ramanarayanan, A new family of soft transition converters: Design example and dynamic model. *Proceedings of* the National Power Electronics Conference.



Naga Brahmendra Yadav Gorla received the B.Tech degree in Electrical and Electronics Engineering from Acharya nagarjuna university, India in 2010. He is currently working towards MS (Research) in Power Electronics at Indian Institute of Technology Madras, Chennai, India. His areas of interest include DC-DC conversion, inverters, parasitic effects at higher switching frequencies etc. e-mail: gorla.indra@gmail.com



**Dr. Lakshmi Narasamma N** obtained her Ph.D. degree in Electrical Engineering from the Indian Institute of Science and joined the faculty of Electrical Engineering at the Indian Institute of Technology, Madras as an Assistant Professor in the year 2009. She has coauthored four journal papers in peerreviewed journals, including the IEEE Transactions on Power Electronics and several premier conferences. Her research interests are in the areas of Power Electronics and drives.

e-mail: lakshmin@ee.iitm.ac.in