Edge Detection in Low Contrast Images

Koushlendra Kumar Singh, Manish Kumar Bajpai, Rajesh K. Pandey

Abstract—The edges of low contrast images are not clearly distinguishable to human eye. It is difficult to find the edges and boundaries in it. The present work encompasses a new approach for low contrast images. The Chebyshev polynomial based fractional order filter has been used for filtering operation on an image. The preprocessing has been performed by this filter on the input image. Laplacian of Gaussian method has been applied on preprocessed image for edge detection. The algorithm has been tested on two test images.

Keywords—Chebyshev polynomials, Fractional order differentiator, Laplacian of Gaussian (LoG) method, Low contrast image.

I. INTRODUCTION

ONTRAST is the difference in luminance that makes an object distinguishable to human eyes. It is determined by the difference in luminance reflected from two adjacent surfaces [1]. The edges of low contrast images are not clearly distinguishable to human eye. It is difficult to find the edges and boundaries in it. It has been found that the traditional edge detection algorithms are not well suited for these types of images. Edge detection is a common approach for detecting the discontinuities in gray scale value of images. Different approaches have been developed for detection of edges in literature. The popular edge detection methods like Roberts, Sobel, Prewitt operation, Finite impulse response filters, Deriche filter, First order derivative of Gaussian function etc. [2]-[5]. The filter based methods also draw attention of researchers for edge detection, corners detection and their shape detection etc. Major filter based methods are Low pass and High pass filtering approach, Gabour filter, Kirsh operators, Median filtering etc. [6]-[13]. The major challenge in the edge detection algorithms is that they are image dependent. Their performance depends on the quality and type of images.

The Canny edge detection approach is an optimal edge detection algorithm which is based on derivative of Gaussion function [8]. The Laplacian of Gaussian edge detections methods also based on the 2^{nd} order derivative of pixel intensity value of images. The Laplacian has been calculated using standard convolution methods. John et al. has proposed

Koushlendra K. Singh is with the Indian Institute of Technology, Design Manufacturing, Jabalpur, M.P.-482005 India (corresponding author; e-mail: kks04540@gmail.com).

Manish Kumar Bajpai, is with Indian Institute of Information Technology, Design Manufacturing, Jabalpur, M.P.-482005 India (e-mail: mkbajpai@iiitdmj.ac.in).

Rajesh K. Pandey is with the Department of Mathematical Sciences, Indian Institute of Technology (BHU), Varanasi, U.P. 221005 India (e-mail: rkpandey.mat@iitbhu.ac.in). a nonlinear strategy for edge detection with optimal isotropy [12].

Koushlenda et al. have been proposed an algorithm for design of filter that is based on Chebyshev polynomial approximation of fractional order differentiator [14].

The present work encompasses design and development of an algorithm which uses prepressed image in Laplacian of Gaussian (LoG) algorithm. Fractional order differentiator has been used to perform the preprocessing.

The structure of this paper is as follows: Section II discussed design of filter. Section III describes the proposed algorithm for edge detection. Section IV describes the results and conclusion.

II. DESIGN OF FILTER

The detailed algorithm for design of fractional order differentiator is present in literature [14]. We are reproducing it here for better understanding.

Consider two higher order differentiable functions in \square as Y(t) and $\tilde{Y}(t)$ which are observed function and original function respectively. The observed function can be written as

$$Y(t) = \tilde{Y}(t) + \xi(t) \tag{1}$$

here $\xi(t)$ is error. The present work encompasses smoothing of observed function by the use of n^{th} order derivative, L point filtering window and *n*-degree polynomial approximation.

Any function Y(t) can be obtained by polynomial expansion expressed as: [15]

$$Y(t) = \sum_{k=0}^{n} c_k T_k(t)$$
 (2)

t = 1, 2, 3..., L is the position of the t^{th} point in the filtering window and c_k is the k^{th} coefficient of polynomial function.

Least-square method is used for the estimate the coefficients c_k . Equation (2) can be expanded in the form:

$$T_{0}(1)c_{0} + T_{1}(1)c_{1} + T_{2}(1)c_{2} + \dots + T_{n}(1)c_{n} = y_{1}$$

$$T_{0}(2)c_{0} + T_{1}(2)c_{1} + T_{2}(2)c_{2} + \dots + T_{n}(2)c_{n} = y_{2}$$

$$T_{0}(3)c_{0} + T_{1}(3)c_{1} + T_{2}(3)c_{2} + \dots + T_{n}(3)c_{n} = y_{3}$$

$$\dots \dots \dots \dots$$

$$T_{0}(L)c_{0} + T_{1}(L)c_{1} + T_{2}(L)c_{2} + \dots + T_{n}(L)c_{n} = y_{L}$$
(3)

here $Y = [y_1, y_2, ..., y_L]^T$ denotes the measured function points in the filtering window. *T* is a matrix of order $L \times (n+1)$ and can be defined as

$$T = \begin{bmatrix} T_0(1) & T_1(1) & T_2(1) \cdots & T_n(1) \\ T_0(2) & T_1(2) & T_2(2) \cdots & T_n(2) \\ \vdots & \vdots & \vdots & \vdots \\ T_0(L) & T_1(L) & T_2(L) \cdots & T_n(L) \end{bmatrix}$$
(4)

The elements of matrix T are calculated by using Chebyshev polynomial [18]

$$T_{n+1}(t) = 2tT_n(t) - T_{n-1}(t)$$
(5)

here $T_0(t) = 1$, $T_1(t) = t$.

The vectors C storing the coefficients of the polynomial are obtained by:

$$C = (T^T T)^{-1} T^T Y ag{6}$$

Equations (5) and (6) are used to solve (3). It will result

$$\hat{Y} = TC = T(T^T T)^{-1} T^T Y = WY$$
(7)

here *W* denotes window's coefficient matrix. Smoothing can be performed by use of different window coefficient matrix.

Riemann-Liouville fractional order derivative can be expressed as:

$${}_{0}D_{x}^{\alpha}Y(t) = \frac{1}{\Gamma(l-\alpha)} \frac{d^{l}}{dt^{l}} \int_{0}^{x} (t-x)^{l-\alpha-1} f(x) dx$$
(8)

here $0 \le l-1 < \alpha < l$, and $\Gamma(l-\alpha)$ is the Gamma function of $(l-\alpha)$. α is the positive order of differentiation and its value lies between l-1 to l [19].

The fractional order differentiator, corresponding to window coefficient matrix W, can be obtained by (8). Different properties of fractional order differentiation are applied on (7) and we will get

$$\hat{Y}_{t}^{\alpha} = T_{t}^{\alpha} C = W_{t}^{\alpha} Y = c (T^{T} T)^{-1} T^{T} Y$$
(9)

It is generalized form of (7). Here \hat{y}_t^{α} denotes the α^{th} derivative of the t^{th} point in the filtering window, W_t^{α} denotes the α^{th} derivative coefficient vector of the t^{th} point in the filtering window.

Quadrature mirror filter (*QMF*) concept is used for design the high pass filter with newly designed digital fractional order differentiator [16], [17]. The low pass and high pass filters are used here $_{G_0(n)}$ and $_{h_0(n)}$ respectively. The high pass filter $_{h_0(n)}$ is a mirror image of low pass filter $_{G_0(n)}$ and can be expressed as

$$h_0(n) = (-1)^n G_0(n) \tag{10}$$

Full algorithm for the design of filter is described in algorithm 1.

Algorithm I

The algorithm can be expressed as follow
Algorithm (L, n, α ,)
Input: L, n, α
<i>L</i> : Length of differentiator
<i>n</i> : Order of polynomial
α : Order of derivative
T : Matrix
<i>a</i> : Constant
W: Window matrix
Γ : Gamma function
Output: W, h ₀
begin
for $i \leftarrow 1$ to L
for $j \leftarrow 0$ to n
Calculate matrix T_{ij} .
$T_{ij}(i) = 2iT_j(i) - T_{j-1}(i)$
(Here $T_0(i) = 1, T_1(i) = i$)
end for
end for
for $i \leftarrow 1$ to L
for $j \leftarrow 0$ to α
Calculate $a = \left[\frac{\Gamma(n+1)}{\Gamma(n+1-\alpha)}i^{n-\alpha}\right]$
$W_i^{(\alpha)} = a(T^T T)^T T^T$
$G_0(i) \leftarrow W_i^{(\alpha)}$
$h_0(i) = (-1)^L G_0(i)$
end
end
ena

III. ALGORITHM FOR EDGE DETECTION OF LOW CONTRAST IMAGES

The preprocessing has been performed on the input image before applying the Laplacian of Gaussian method for edge detection. Normalization operation has been performed on the input image (I). The normalized image, (I_n), has been processed by newly designed low pass and high pass filters. The output of low pass filtering operation (I_{nl}) has been relaxed with the relaxation coefficient. The relaxation coefficient varies from 0 to 2. The output image of high pass filtering operation, I_{nh} and image I_{nl} has been multiplied. The output image of this operation is input image for Laplacian of Gaussian method (LoG). The Laplacian of Gaussian algorithm has been performed on I_1 . The algorithm has been described in algorithm II. Fig. 1 has described the flow chart of proposed algorithm.

Algorithm II

Proposed algorithm is as follow

Algorithm $(I_E, I, h_0, G_0, \lambda)$

Input: I, h_0, G_0, λ

- I : Input Image
- h_0 : High pass filter
- G_0 : Low pass filter
- $\boldsymbol{\lambda}$: Relaxation coefficient

 I_n : Normalized image

 I_{nl} : Filtered image with low pass filter

I_{nh} : Filtered image with high pass filter

I₁: Intermediate Image

I': Pre-processed Image

LoG (): Standard Laplacian of Gaussian edge detection algorithm *Normalization ():* Normalization of image

Output: I_E

 $\begin{array}{l} \textit{begin} \\ I_n = \textit{Normalization} (I) \\ I_{nh} = h_0(I_n) \\ I_{nl} = G_0(I_n) \\ I_{lr} = \lambda I_{nl} \\ I_1 = I_{lr} \times I_{nh} \\ I_E = \textit{LoG} (I_1) \\ \textit{end} \end{array}$

IV. EXPERIMENTS

The proposed algorithm has been validated with the two low contrast images shown in Fig. 2. Images have low contrast properties as well as smooth properties. Test images are available in the open domain [20].

V.RESULTS

The proposed algorithm has been tested on two test images We have taken $\alpha = 0.5$ and order of polynomial n = 2. Four different lengths of filters i.e. L = 3, 4, 5, 7 have been taken for validation of our proposed algorithm. The effect of length of filters has been also analyzed. The high pass filter coefficients are calculated from (10). These calculated filters have been used for intermediate stage of preprocessing. We have taken the value of relaxation coefficient, $\lambda = 0.1$ corresponding to every filter.

Figs. 3 (a)-(d) show the test results obtained from proposed algorithm for test case 1 (a) for filter size 3, 4, 5 and 7 respectively. Result obtained by proposed algorithm for test case 1 (b) has been shown in Fig. 4. Figs. 4 (a)-(d) have been reported for filter size 3, 4, 5 and 7 respectively. Figs. 5 (a) and (b) show the result obtained by Laplacian of Gaussian (LoG) for test case 1 (a) and test case 1 (b). Results clearly show that the proposed algorithm has been performed better than the Laplacian of Gaussian algorithm. It is difficult to

predict in edges in Fig. 5. Figs. 3 and 4 are more clear visibility. It has been also reported from results that for lower order filter, results are not clearer.



Fig. 1 Flow chart of proposed algorithm



Fig. 2 (a) Test Case I (b) Test case II

International Journal of Information, Control and Computer Sciences ISSN: 2517-9942 Vol:9, No:1, 2015



Fig. 3 Edge of proposed image of test case 1 for L = 3, 4, 5 and 7



Fig. 4 Edge of proposed image of test case 2 for L = 3, 4, 5 and 7

International Journal of Information, Control and Computer Sciences ISSN: 2517-9942 Vol:9, No:1, 2015



Fig. 5 Edge of image using LoG for test case 1 and 2

VI. CONCLUSION

The major part of algorithm has preprocessing of input image. The preprocessing has been performed by newly designed Chebysheby polynomial based fractional order filter. The Laplacian of Gaussian method has not giving better results in case of low contrast images. Visible results clearly shows that algorithm perform better for higher order of filter.

REFERENCES

- R. C. Gonzalez, Richard E. Woods, Digital Image Processing, Third [1] Edition, Pearson Education, New Delhi, 2009,
- [2] A. Rosenfeld and M. Thurston, "Edge and curve detection for visual scene analysis" IEEE Trans. Cornput., vol. C-20, pp. 562-569, 1971.
- D. Man, Vision. San Francisco, CA: Freeman, 1982.D. Marrand E. Hildreth, "Theory of edge detection," Proc. Roy. Soc. London, vol. B207, pp. 187-217, 1980. [4]
- A. P. Witkin, "Scale-space filtering" in Proc. IJCAI-8, 1983 [5]
- A. L. Yuille and T. Poggio, "Scaling theorems for zero-crossings" IEEE [6]
- Trans. Patfern Anal. Machine Intell., vol. PAMI-8, pp. 15-25, 1986. J.M.S. Prewitt, "Object Enhancement and Extraction" Picture [7] Processing and Psychopictorics, B. Lipkin and A. Rosenfeld, eds., pp.
- 75-149. New York: Academic, 1970. [8] J. Canny, "A Computational Approach to Edge Detection" IEEE Trans. Pattern Analysis and Machine Intelligence, Vol. 8 (6), pp. 679- 698, Nov. 1986.
- R. Deriche. "Fast algorithms for low-level vision", IEEE Trans, PAMI, [9] Vol. 12 no A pp. 78-87, 1990.
- [10] J. Shen and S. Castan, "An Optimal Linear Operator for Step Edge Detection" Computer Vision Graphics Image Processing, vol. 54 no. 2, pp. 112-13, Mar. 1992.
- [11] S. Lanser and W. Eckstein, "Eine Modification des Deriche-Verfahrens zur Kantendetektion", In B. Radig, ed., Mustererkennung 1991, vol. 290 of Informatik Fachberichte, DAGM Symposium, Munchen, Springer, Berlin, 1991, pp. 151-158
- [12] B. Jahne, H. Scharr, and S. Korgel, "Principles of filter design", In B. Jahne, H. HauEecker, and P. GeiEJer, eds., Computer Vision and Applications, vol 2, Signal Processing and Pattern Recognition, chapter 6, Academic Press, San Diego. pp 125-151, 1999.
- [13] R.P. Johnson, Contrast based edge detection, Pattern Recognition Vol. 23, pp. 311-318, 1990.

- [14] Koushlendra K. Singh, Manish K. Bajpai, Rajesh K. Pandey "A Novel Approach for Enhancement of Geometric and Contrast Resolution Properties of Low Contrast Images" IIITDMJ/CSE/2014/PGR0108, 2014
- [15] D. Chen, Y. Q. Chen, "Digital Fractional Order Savitzky-Golay Differentiator" IEEE trans. on Circuit and System-II: Express Briefs Vol. 58 pp. 758-762, Nov. 2011.
- [16] S. Guillon, P. Baylon, M. Najim, N. Keskes, Adaptive nonlinear filters for 2-D and 3-D image enhancement, Signal Processing, Vol. 67, pp. 237-254 1998
- S. K. Mitra, Digital Signal Processing: A computer based approach, [17] McGraw-Hill India edition, 2004.
- [18] T. J. Rivlin, The chebyshev polynomials, John Wiley & Sons press, 1974
- I. Podulubny, Fractional Differential Equation, Mathematics in Science [19] & Engineering, 198, Academic Press: California, USA.
- [20] http://photojournal.jpl.nasa.gov/catalog/PIA10300.

Koushlendra K Singh is research scholar in Department of Computer Science & Engineering at Indian Institute of Information Technology Design Manufacturing Jabalpur (III Jabalpur), Jabalpur, India. He received his master degree from Indian Institute of Information Technology Design Manufacturing Jabalpur (III Jabalpur), Jabalpur, India. His area of research is image processing, wavelets, filter design and integral transform.

Manish K Bajpai is currently working as Assistant Professor in Department of Computer Science & Engineering at Indian Institute of Information Technology Design Manufacturing Jabalpur (III Jabalpur), Jabalpur, India. He received his Doctoral degree from Indian Institute of Technology Kanpur, India in 2013. He is currently working in areas of high performance computing, image reconstruction, image processing and climate change.

Rajesh K. Pandey is currently working as Assistant Professor in Department of Mathematical Sciences, Indian Institute of Technology (BHU) Varanasi, India. He received his doctoral degree from Indian Institute of Technology (BHU) in 2009. His works in the field of integral transform, wavelets, signal processing, image processing. He has published more 30 papers in international journals. He is also the recipient of Indo Us fellowship.