

Selection of Material for Gear Used in Fuel Pump Using Graph Theory and Matrix Approach

Sahil, Rajeev Saha, Sanjeev Kumar

Abstract—Material selection is one of the key issues for the production of reliable and quality products in industries. A number of materials are available for a single product due to which material selection become a difficult task. The aim of this paper is to select appropriate material for gear used in fuel pump by using Graph Theory and Matrix Approach (GTMA). GTMA is a logical and systematic approach that can be used to model and analyze various engineering systems. In present work, four alternative material and their seven attributes are used to identify the best material for given product.

Keywords—Material, GTMA, MADM, digraph, decision making.

I. INTRODUCTION

MATERIAL selection is one of the key issues for the production of good products in industries. Materials and design are two very important subjects in their own right and their integration is critical to the development of successful new engineering products [1]. Numbers of material are available for a single product each having its own advantage and disadvantage. Availability of large number of materials makes the selection process a difficult task. During the selection of material, a number of attributes have to be taken into consideration. An attribute is factor which affects the material selection for a given problem. These attributes are: mechanical properties, electrical properties, magnetic properties, physical properties, chemical properties, manufacturing properties material cost, product shape, material impact on environment, performance characteristics, etc.

The selection of good and reliable material for any problem from given alternative materials and their attributes is a multiple attribute decision-making (MADM) problem.

During the past few decades various methods have been proposed to rank alternatives. Rao [2] have worked on selection of material for cryogenic storage tank for transportation of liquid nitrogen from the alternative material. He applied various MADM approaches such as SAW, WPM, graph Theory etc. Liao [3] presented a fuzzy multi criteria decision-making method for material selection. Giachetti [4] described a prototype material and manufacturing process selection system that integrates a formal multiple attribute decision model with a relational database. Rayg [5] used various MADM methods for selection of tool insert for finishing operation. Framework to represent and deal with the relationships between design

variables of both materials parameters and system-level parameters was proposed by Raj [6]. Patel [7] used decision-making method to select robot in different industrial environments considering both qualitative and quantitative attributes. Nikam [8] used SAW and WPM for selection of cutting tool insert in turning operation.

GTMA is a logical and systematic approach that can be used to model and analyze various engineering systems. GTMA method has been employed for material selection [9] and selection of industrial robots [10]. Graph Theory and Matrix Approach (GTMA) helps in identifying different attributes of material and offer a better visual appraisal of the attributes and their interrelations [11]. GTMA has been employed in different fields by different authors:

- Evaluation of cutting fluids [13]
- Flexible manufacturing systems [14]
- Performance evaluation of technical institutions [15]
- Machinability evaluation of work materials [16]
- For contractor ranking [17]
- Quantification of risk mitigation environment of supply chains [18]
- Selection of locations of collection centers [19]
- Modeling and analysis of FMS performance variables [20]
- Disposition decisions in reverse logistics [21]
- Assignment of weightage to machining characteristics to improve overall performance [22]
- Selection of a power plant [23]
- Failure mode and effect analysis [24]
- Selection of cutting parameters in side milling operation [25]
- Barriers to green supply chain management in Indian mining industries [27]
- Disposition decisions in reverse logistics [28]
- Manufacturing system's effectiveness measurement [29]
- To optimize single-product flow-line configurations of RMS [30]
- Analyzing and modeling the performance index of ultrasonic vibration assisted EDM [31]
- Structural modeling and analysis of water resources development and management system [32]
- Evaluation of gas turbine power plant efficiency [33]

Influence of materials (characterized by a bending fatigue strength) of the safety factor for the bending transmission in

Sahil is a student of M. Tech in YMCA University of Science and Technology, Faridabad, India. (corresponding author; phone: 09671571034; email: sahilguptakyt@gmail.com)

Dr. Rajeev Saha and Dr. Sanjeev Kumar are working as faculty member in the Dept. of Mechanical Engg., YMCA University of Science and Technology, Faridabad, India (e-mail: rajeevsaha@gmail.com, getsan25@rediffmail.com).

gear was shown by [26].

II. METHODOLOGY

GTMA is a logical and systematic approach. Digraph had proved very useful in modeling and analyzing the various types of problems. If these digraph become complex then these digraph are analyzed with the help of Matrix method using a computer program. GTMA helps in identifying attributes, and offer a better visual appraisal of the attributes and their interrelations (Rao, 2007).

A. Material Selection Attributes Digraph

The material selection attributes and their interrelationships are graphically represented by a material selection attributes digraph. Fig. 1 illustrates the material selection attributes digraph for the material selection problem. The material selection attributes are surface hardness(SH), Core hardness (CH), oxidation(O), magnetic flux(MF), case depth at pitch circle diameter(PCD), case depth at root(R), Millipore test value(M). The digraph consists of seven nodes representing the seven attributes SH, CH, O, MF, PCD, R and M respectively. Directed edges are drawn from one node to another and represent the inter-relationship among the attributes




Fig. 1 Material Selection Attribute Digraph

The material selection attributes digraph enables a quick visual appraisal of the material selection attributes and their inter-relationships

B. Application of GTMA

Current problem is related with selection of a suitable material for a gear used in fuel pump. The material selection problem considers four alternative materials and seven attributes, and the data are given in Table I.

Mat.	SH	CH	O	MF	PCD	R	M
1	61.5	32	.020	2	.83	.70	4.3
2	62	31.3	.0167	2	.62	.52	3.8
3	61	42	.0155	1.5	.65	.50	3.9
4	60	37	.0145	1	.75	.63	4.1

Mat. = Material. SH= Surface Hardness (HRC), CH= Core Hardness (HRC), O= Oxidation (mm), MF= Magnetic flux (Gauss), PCD= case depth at pitch circle diameter (mm), R=case depth at root (mm), M= Millipore test value (mg). Material 1= 16MnCr5, Material 2= SAE-8620, Material 3= 19MnCr5, Material 4= SCM-420HV.

C. Various Steps Used in Methodology

Step 1: In the current work, the attributes considered for material selection are surface hardness(SH), Core hardness(CH), oxidation(O), magnetic flux(MF), case depth at pitch circle diameter(PCD), case depth at root(R), Millipore test value(M). Objective data of attributes is given in Table I and normalized values of these attributes are given in Table II:

TABLE II
NORMALIZED VALUES

Mat.	SH	CH	O	MF	PCD	R	M
1	.992	.762	1	1	1	1	1
2	1	.745	.835	1	.747	.743	.884
3	.984	1	.775	.75	.783	.714	.907
4	.968	.881	.725	.5	.903	.9	.953

D. Permanent Function

A permanent function is a complete representation of the attributes of a problem and contains all possible information of the attributes and their interrelations. The permanent is similar to the determinant of a Matrix except in permanent all the terms are positive, no negative sign appears in the permanent function of a Matrix and hence no information will be lost. The permanent function for 'N' attributes Matrix when expanded, will have (N!) terms which may be arranged in (N+1) groups. The permanent function of Matrix 'R' can be calculated using (1):

$$\begin{aligned}
 \text{per}(R) = & \prod_{i=1}^N G_i \\
 & + \sum_{i=1}^{N-1} \sum_{j=i+1}^N \dots \sum_{N=t+1}^N (g_{ij}g_{ji}) G_k G_l G_m G_n G_o \dots G_t G_N + \\
 & \sum_{i=1}^{N-2} \sum_{j=i+1}^{N-1} \sum_{k=j+1}^N \dots \sum_{N=t+1}^N (g_{ij}g_{jk}g_{ki} + g_{ik}g_{kj}g_{ji}) \\
 & G_k G_l G_m G_n G_o \dots G_t G_N + \left[\sum_{i=1}^{N-3} \sum_{j=i+1}^N \sum_{k=i+1}^{N-1} \sum_{l=i+2}^N \sum_{N=t+1}^N \right. \\
 & (g_{ij}g_{ji})(g_{kl}g_{lk}) G_m G_n G_o \dots G_t G_N + \\
 & \sum_{i=1}^{N-3} \sum_{j=i+1}^{N-1} \sum_{k=i+1}^N \sum_{l=j+1}^N \dots \sum_{N=t+1}^N (g_{ij}g_{jk}g_{kl}g_{li} \\
 & + g_{il}g_{lk}g_{kj}g_{ji}) G_m G_n G_o \dots G_t G_N \left. \right] \\
 & + \left[\sum_{i=1}^{N-2} \sum_{j=i+1}^{N-1} \sum_{k=j+1}^N \sum_{l=1}^{N-1} \sum_{m=l+1}^N \dots \sum_{N=t+1}^N (g_{ij}g_{jk}g_{ki} \right. \\
 & + g_{ik}g_{kj}g_{ji})(g_{lm}g_{ml}) G_n G_o \dots G_t G_N + \\
 & \sum_{i=1}^{N-4} \sum_{j=i+1}^{N-1} \sum_{k=i+1}^N \sum_{l=i+1}^{N-1} \sum_{m=j+1}^N \dots \sum_{N=t+1}^N (g_{ij}g_{jk}g_{kl}g_{lm}g_{mi} \\
 & + g_{im}g_{ml}g_{lk}g_{kj}g_{ji}) G_n G_o \dots G_t G_N \left. \right] \\
 & + \left[\sum_{i=1}^{N-3} \sum_{j=i+1}^{N-1} \sum_{k=i+1}^N \sum_{l=j+1}^{N-1} \sum_{m=1}^N \sum_{n=m+1}^N \dots \sum_{N=t+1}^N (g_{ij}g_{jk}g_{kl}g_{li} \right. \\
 & + g_{il}g_{lk}g_{kj}g_{ji})(g_{mn}g_{nm}) G_o \dots G_t G_N \\
 & + \sum_{i=1}^{N-5} \sum_{j=i+1}^{N-1} \sum_{k=j+1}^N \sum_{l=1}^{N-2} \sum_{m=l+1}^{N-1} \sum_{n=m+1}^N \dots \sum_{N=t+1}^N (g_{ij}g_{jk}g_{kl}g_{li}
 \end{aligned}$$

$$\begin{aligned}
& +g_{ik}g_{kj}g_{ji})(g_{lm}g_{mn}g_{nl} + g_{ln}g_{nm}g_{ml})G_o \dots G_t G_N \\
& + \sum_{i=1}^{N-5} \sum_{j=i+1}^N \sum_{k=i+1}^{N-3} \sum_{l=i+2}^N \sum_{m=k+1}^{N-1} \sum_{n=k+2}^N \dots \dots \\
& \dots \sum_{N=t+1}^N (g_{ij}g_{ji})(g_{kl}g_{lk})(g_{mn}g_{nm})G_o \dots G_t G_N \\
& + \sum_{i=1}^{N-5} \sum_{j=i+1}^{N-1} \sum_{k=i+1}^N \sum_{l=i+1}^N \sum_{m=i+1}^N \sum_{n=j+1}^N \dots \\
& \sum_{N=t+1}^N (g_{ij}g_{jk}g_{kl}g_{lm}g_{mn}g_{ni} \\
& + g_{in}g_{nm}g_{ml}g_{lk}g_{kj}g_{ji})G_o \dots G_t G_N
\end{aligned} \quad (1)$$

Relative weight of attributes is assigned using 5- point scale suggested by Chen and Hwang [12]. The relative weight of attributes is given in Table III.

	SH	CH	O	MF	PCD	R	M
SH	-	0.505	0.895	0.895	0.695	0.695	0.895
CH	0.495	-	0.895	0.895	0.695	0.695	0.895
O	0.105	0.105	-	0.505	0.295	0.295	0.695
MF	0.105	0.105	0.495	-	0.295	0.295	0.695
PCD	0.305	0.305	0.705	0.705	-	0.505	0.695
R	0.305	0.305	0.705	0.705	0.495	-	0.695
M	0.105	0.105	0.305	0.305	0.305	0.305	-

Step 2: Material selection attribute digraph shows the relative importance of each attribute upon each other. Relative weight Matrix of this digraph is shown in (1). Relative weight Matrix for material 1 is shown in Table IV:

	SH	CH	O	MFT	PCD	R	M
SH	0.992	0.505	0.895	0.895	0.695	0.695	0.895
CH	0.495	0.762	0.895	0.895	0.695	0.695	0.895
O	0.105	0.105	1	0.505	0.295	0.295	0.695
MFT	0.105	0.105	0.495	1	0.295	0.295	0.695
PCD	0.305	0.305	0.705	0.705	1	0.505	0.695
R	0.305	0.305	0.705	0.705	0.495	1	0.695
M	0.105	0.105	0.305	0.305	0.305	0.305	1

Relative weight Matrix for material 2 is shown in Table V:

	SH	CH	O	MF	PCD	R	M
SH	1	0.505	0.895	0.895	0.695	0.695	0.895
CH	0.495	0.745	0.895	0.895	0.695	0.695	0.895
O	0.105	0.105	0.835	0.505	0.295	0.295	0.695
MFT	0.105	0.105	0.495	1	0.295	0.295	0.695
PCD	0.305	0.305	0.705	0.705	0.747	0.505	0.695
ROOT	0.305	0.305	0.705	0.705	0.495	0.743	0.695
M	0.105	0.105	0.305	0.305	0.305	0.305	0.884

Relative weight Matrix for material 3 is shown in Table VI:

	SH	CH	O	MF	PCD	R	M
SH	0.984	0.505	0.895	0.895	0.695	0.695	0.895
CH	0.495	1	0.895	0.895	0.695	0.695	0.895
O	0.105	0.105	0.775	0.505	0.295	0.295	0.695
MF	0.105	0.105	0.495	0.75	0.295	0.295	0.695
PCD	0.305	0.305	0.705	0.705	0.783	0.505	0.695
R	0.305	0.305	0.705	0.705	0.495	0.714	0.695
M	0.105	0.105	0.305	0.305	0.305	0.305	0.907

Relative weight Matrix for material 4 is shown in Table VII:

	SH	CH	O	MF	PCD	R	M
SH	0.968	0.505	0.895	0.895	0.695	0.695	0.895
CH	0.495	0.881	0.895	0.895	0.695	0.695	0.895
O	0.105	0.105	0.725	0.505	0.295	0.295	0.695
MF	0.105	0.105	0.495	0.5	0.295	0.295	0.695
PCD	0.305	0.305	0.705	0.705	0.903	0.505	0.695
R	0.305	0.305	0.705	0.705	0.495	0.9	0.695
M	0.105	0.105	0.305	0.305	0.305	0.305	0.953

The permanent function value of Matrix is calculated with the help of (1). The material selection index value of different material is given below:

Material 1(16MnCr5): 44.1314
 Material 2(SAE-8620): 34.3993
 Material 3(19MnCr5): 34.1925
 Material 4(SCM-420HV): 32.2788

III. CONCLUSION

GTMA suggests the material designated as 1, i.e. 16MnCr5, as the right choice for the given problem of selection of a suitable material for a gear used in fuel pump.

REFERENCES

- [1] K.L. Edwards, Materials influence on design: a decade of development. Mater. Des. 32, 1073–1080 (2011)
- [2] R.V Rao (2006) A material selection model using graph Theory and Matrix approach. Materials Science and Engineering A 431:248–255.
- [3] TW Liao (1996) A fuzzy multi criteria decision-making method for material selection. Journal of Manufacturing Systems 15:1–12.
- [4] RE Giachetti (1998) A decision support system for material and manufacturing process selection. Journal of Intelligent Manufacturing 9:265–276.
- [5] Shivani Raygor and M. S. Take (2015). Selection of work piece combination using MADM methods for CNC turning operation, International Journal of Advanced Engineering Technology.
- [6] R Raj (2000) An interdisciplinary framework for the design and life prediction of engineering systems. Trans ASME, Journal of Engineering Materials Technology 122:348–354.
- [7] R. V. Rao, B. K. Patel and M. Parnichkun (2011), Industrial robot selection using a novel decision-making method considering objective and subjective preferences, Elsevier Robotics and Autonomous Systems.
- [8] K. G. Nikam and S. S. Kadam, "Selection of cutting tool insert in turning of EN8 steel using multiple attribute decision making MADM methods", International Journal of Engineering Sciences & Research Technology (2014).
- [9] R.V Rao. (2006b). A material selection model using graph Theory and Matrix approach. Materials Science and Engineering: A, 431(1), 248-255.
- [10] R.V Rao, & K. K. Padmanabhan, (2006). Selection, identification and

- comparison of industrial robots using digraph and Matrix methods. Robotics and Computer-Integrated Manufacturing, 22(4), 373-383.
- [11] R.V Rao. (2007). Decision making in the manufacturing environment: using graph Theory and fuzzy multiple attribute decision making methods. Springer Science & Business Media.
- [12] SJ Chen, CL Hwan (1992) Fuzzy multiple attribute decision making-methods and applications. Lecture Notes in Economics and Mathematical Systems, Springer, New York
- [13] R.V Rao, & Gandhi, O. P. (2001). Digraph and Matrix method for the selection, identification and comparison of metal-cutting fluids. Proceedings of the Institution of Mechanical Engineers, Part J: Journal of Engineering Tribology, 215(1), 25-33.
- [14] R.V Rao. (2006a). A decision-making framework model for evaluating flexible manufacturing systems using digraph and Matrix methods. The International Journal of Advanced Manufacturing Technology, 30(11-12), 1101-1110.
- [15] R.V Rao. (2000), Graph Theory Matrix Approach for the Performance Evaluation of Technical Institutions, Indian J. Tech. Edu., 23(2), 27-33.
- [16] R. V Rao and O. P. Gandhi (2002), Digraph and Matrix Methods for the Machinability Evaluation of Work Materials, Int. J. Machine Tools and Manufacturing, 42, 321-330.
- [17] Darvish, M., M. Yasaei, and A. Saeedi. (2009). Application of the graph Theory and Matrix methods to contractor ranking. International Journal of Project Management, 27(6), 610-619.
- [18] Faisal, M.N., D. Banwet, and R. Shankar. (2007). Quantification of risk mitigation environment of supply chains using graph Theory and Matrix methods. European Journal of Industrial Engineering, 1(1), 22-39
- [19] Sana Malik, Aradhana Kumari, Saurabh Agrawal (2015), Selection of locations of collection centers for reverse logistics using GTMA, 4th International Conference on Materials Processing and Characterization, sciencedirect, Materials Today: Proceedings 2 (2015) 2538 – 2547.
- [20] Vineet Jain, Tilak Raj (2016), Modeling and analysis of FMS performance variables by ISM, SEM and GTMA approach, International Journal Production Economics 171, 84–96.
- [21] Saurabh Agrawal, Rajesh K. Singh, Qasim Murtaza (2016), Disposition decisions in reverse logistics: Graph theory and matrix approach, Journal of Cleaner Production 137, 93-104.
- [22] K. V Rao, P.B.G.S.N. Murthy, K.P. Vidhu. (2017), Assignment of weightage to machining characteristics to improve overall performance of machining using GTMA and utility concept. CIRP Journal of Manufacturing Science and Technology, <http://dx.doi.org/10.1016/j.cirpj.2016.12.001>
- [23] Yadav, N. & Khan, IA & Grover, S. (2010), "Operational-based economics evaluation and selection of a power plant using graph theoretic approach, world academy of science", Engineering and Technology, vol. 63, p. 426-436
- [24] Gandhi, OP & Agrawal, VP (1992), "FMEA-A digraph and matrix approach", Journal of Reliability Engineering and System Safety, vol. 35, p.47-158
- [25] R.V Rao (2012), A note on "Selection of cutting parameters in side milling operation using graph theory and matrix approach" Int J Adv Manuf Technol (2012) 61:855–858
- [26] S. Medvecká - Beňová, I. Virgala, M. K Elemen, E. Miková (2015), Influence of Material and Gear Parameters on the Safety of Gearing in Metallurgical Industry. ISSN 0543-5846 METABK 54(1) 224-226
- [27] K. Muduli, K.Govindan , A. Barve , Y. Geng, "Barriers to green supply chain management in Indian mining industries: a graph theoretic approach". Journal of Cleaner Production 47 (2013) 335-344
- [28] Saurabh Agrawal, Rajesh K. Singh, Qasim Murtaza, "Disposition decisions in reverse logistics: Graph theory and matrix approach". Journal of Cleaner Production 137 (2016) 93-104
- [29] S. Goyal S. Grover, "Manufacturing system's effectiveness measurement by using combined approach of ANP and GTMA". Int J Syst Assur Eng Manag DOI 10.1007/s13198-012-0129-2
- [30] J.Dou, X.dai, Z. Meng, "Graph theory-based approach to optimize single-product flow-line configurations of RMS". Int J Adv Manuf Technol (2009) 41:916–931 DOI 10.1007/s00170-008-1541-2
- [31] Sanjay Kumar, Sandeep Grover¹, R. S. Walia, "Analyzing and modeling the performance index of ultrasonic vibration assisted EDM using graph theory and matrix approach". Int J Interact Des Manuf DOI 10.1007/s12008-016-0355
- [32] Dwarikanath Ratha, V. P. Agrawal, "Structural Modeling and Analysis of Water Resources Development and Management System: A Graph Theoretic Approach". Water Resour Manage DOI 10.1007/s11269-014-0650.

- [33] Nikhil Dev, Rajesh Kumar Attri, "Evaluation of gas turbine power plant efficiency using graph theoretic approach". Int J Syst Assur Eng Manag DOI 10.1007/s13198-016-0506-3.



Sahil was born on June 11, 1993. He is a student of M.tech in YMCA University of Science & Technology, Faridabad .He completed his B.Tech in Mechanical Engineering in 2015 from Kurukshetra University, Kurukshetra



Rajeev Saha is working as faculty member in Mechanical Department at YMCA University of Science and Technology, Faridabad. He is having around 13 years of experience in industry and 8 years of experience in teaching.



Sanjeev Kumar was born on July 7, 1975. He received the B.E. degree in Mechanical Engineering in 1998, M.Tech. degree in Mech. Engg in 2003 and PhD. in the field of industrial Engg in 2011 from National Institute of technology, Kurukshetra. In 2004 he joined AKGEC Ghaziabad and served there as Head, Professor. In June 2012 he joined YMCA University of Science & Technology, Faridabad Associate Professor in the deptt. of Mechanical Eng. He has published about 60 research papers in the reputed journals and conferences. He has attended about 20 conferences. His fields of expertise are stochastic modeling, TQM, RAM etc. He is the committee member of WASET.

Dr Sanjeev Kumar is life member of Institutions of Engineers (India), Senior member of Indian Institution of Industrial Engineering, IAENG, He is member of editorial board and reviewer committee of various reputed International journals.