Business Intelligence for N=1 Analytics using Hybrid Intelligent System Approach

Rajendra M Sonar

Abstract—The future of business intelligence (BI) is to integrate intelligence into operational systems that works in real-time analyzing small chunks of data based on requirements on continuous basis. This is moving away from traditional approach of doing analysis on ad-hoc basis or sporadically in passive and off-line mode analyzing huge amount data. Various AI techniques such as expert systems, case-based reasoning, neural-networks play important role in building business intelligent systems. Since BI involves various tasks and models various types of problems, hybrid intelligent techniques can be better choice. Intelligent systems accessible through web services make it easier to integrate them into existing operational systems to add intelligence in every business processes. These can be built to be invoked in modular and distributed way to work in real time. Functionality of such systems can be extended to get external inputs compatible with formats like RSS. In this paper, we describe a framework that use effective combinations of these techniques, accessible through web services and work in real-time. We have successfully developed various prototype systems and done few commercial deployments in the area of personalization and recommendation on mobile and websites.

Keywords—Business Intelligence, Customer Relationship Management, Hybrid Intelligent Systems, Personalization and Recommendation (P&R), Recommender Systems.

I. INTRODUCTION

MANY organizations increasingly using BI tools such as data mining to build analytics especially domains like customer relationship management (CRM) to identify, attract, understand, serve and retain the customers [1]-[5]. The new competitive landscape requires continuous analysis of data for insight, only episodic and ad-hoc or periodic will not suffice. Traditional analytics approaches are often asynchronous with business changes. Delays in recognizing, interpreting and acting on trends are critical emerging impediments to competitiveness [6]. Traditional analytics approach based on data mining used in applications like CRM classifies large number of retail customers into few predefined groups like good v/s poor or clusters them into groups by mining huge amount of data [2]. This approach is more of top down and focuses on grouping customers rather than treating them as individuals. However, in worst-case scenario each customer can exhibit a unique pattern based on demographic profile of individual and interactions that individual does with the firm. This means it may not be sufficient to apply the broader group

rules to the customer or try to fit the customer into group. Even a firm is dealing with millions of consumers, the firm must focus on one consumer experience at a time called N=1 [6]. We use the term N=1 analytics to represent analytics that is focused on analyzing one consumer at a time and providing each consumer personalized experiences. N=1 analytics should work in real-time, analysis is done on continuous basis and is integrated into operational systems. The term consumer is used to denote a customer, user etc. [7]



Fig. 1 Possible inputs for N=1 analytics

Products and services or even various offers by the firms are built and configured for a particular kind of target group of consumers. Telecom firms offer various telephone plans keeping in mind various classes of consumers e.g. business class, students etc. or may be based on types of usage patterns e.g. a plan more suitable for more incoming calls rather than outgoing calls. They are not tailor made or dynamically configured to each one's profile, usage pattern and preferences. In order to provide such unique personalized experiences to the consumer, the inputs must come from various sources. Figure 1 shows kind of possible inputs required to offer personalized experiences to consumers. Most of the information like user profiles, user transactions, product and services is already available in the organization in databases generated through operational systems like CRM, ERP (Enterprise Resource Planning), supply-chain management (SCM) etc. Market information is required to understand how consumers in general accept products and services, review and rate them, and what kind of products they are or would be interested in. While offering personalized experiences to individuals, the firm has to follow compliance and policy rules set by the firm, industry and regulatory bodies under which the firm operates e.g. in India, telecom firms are

Rajendra M Sonar is with Indian Institute of Technology Bombay in Shailesh J Mehta School of Management, Powai, Mumbai-400076, India (Phone:+91-22-25767741;fax:+91-22-25722872;e-mail: rm_sonar@iitb.ac.in).

regulated by TRAI (Telecom Regulatory Authority of India) [8] while banking and financial institutions by RBI (Reserve Bank of India) [9].

On the basis of interactions and transactions, if the buying pattern of individuals or risk profiles of individuals can be determined in real-time, it can help firm a) to target the customer with unique, differential and customized product or services offerings, b) to determine which campaign, when and how customer would respond, c) to estimate risk of customer continuous basis and adjust various parameters such as credit limit accordingly, etc. Focusing on analyzing one customer at a time, needs analysis of transactions and information specific to that customer only. This reduces computation overhead and these tasks can be distributed and triggered based on some event or as and when required.



Fig. 2 Traditional approach to business intelligence

Figure 2 shows traditional approach to business intelligence. In this approach, operational systems and business intelligence are treated as separate entities. Analytics team focuses on only analyzing data using various data modeling techniques (like association, classification, clustering etc.) and applicable data mining techniques (such as neural networks, genetic algorithms, etc.) supported BI tools by retrieving data from data marts or data warehouse built for the purpose. Once the results are obtained in the form of rules, equations, decision trees etc. these are either implemented into operational systems or processed separately (like sending emails to target customers who are likely to respond to selected offer). In this kind of approach, the analysis is done more of off-line and ad-hoc or on periodic basis. This approach does not take care of dynamically changing patterns on continuous basis.

There are number of business applications where intelligent systems have been used successfully. Intelligent techniques like expert system (ES), case-based reasoning (CBR), genetic algorithm (GA) and artificial neural network (ANN) can model wide variety of problem types like classification, clustering, optimization and diagnostics [10]. For example, CBR technology can well address technical help-desk, diagnostics, intelligent matching and knowledge-based recommendations applications [11] while expert systems can address applications involving monitoring, automation of expertise and managing complex business rules. Functional areas like analytical CRM require combination of various modeling techniques: association, classification, clustering and prediction to identify, attract, retain and develop customers [2]. Hybrid intelligent systems [12]-[14] that combine and integrate various intelligent techniques at grass root level are well suited to build BI systems requiring such modeling techniques.



Fig. 3 Integrated approach to business intelligence

Web services architecture makes it easier to exchange information in plain text XML (Extensible Markup Language) [15] across diverse plat-forms, technologies and systems in open and standard way. The existence of both synchronous and asynchronous versions of web services enables both realtime and non-real time versions of application integration. Figure 3 shows approach to business intelligence using hybrid intelligent system approach where intelligent systems are loosely (using web services/HTTP: Hypertext Transport Protocol calls) or tightly (using APIs: Application Programming Interface) integrated into operational systems. Once intelligent systems are modeled and configured for specific problem, they are automated to learn on their own continuously based on some event or at specific time intervals based on set criteria. E.g. a) intelligent system modeled to compute associated items to a given item using collaborative filtering technique can be configured to learn new associations whenever user clicks on the item, b) intelligent system modeled to compute personalized items to be shown to the logged in active user can be configured to automatically recompute best personalized items every fifteen minutes fulfilling some criteria like at least one download etc. Such systems can take required information from other websites using RSS: really simple syndication feeds [16] to reflect changes happening in market. Intelligent systems such as knowledge-based recommendation (advisory), can be invoked into operational system to have live interactions with user. One of the advantages of such approach, if intelligent systems are loosely coupled using web services, they can be managed well. They can be distributed running on different machines on network. This can help in better manageability and scalability. In this paper we describe such a framework for business intelligence using integrated approach as shown in figure 3 based on hybrid intelligent systems.

The rest of paper is divided into four sections, section II reviews the base hybrid development framework, in section III

we describe P&R framework to develop P&R systems on top of hybrid framework, section IV describe some case studies and section V concludes the work.

II. REVIEW OF HYBRID DEVELOPMENT FRAMEWORK

Figure 4 shows the components and architecture of hybrid framework [17]. This is an integrated development environment to develop and deploy intelligent systems backed by hybrid of ESs, CBRs and ANNs. It is being commercialized as product called iKen Studio [18] subsequently referred as the hybrid framework. The hybrid framework has all the components required to build intelligent systems backed by rule-based ES, neural network and CBR technology. It supports both structural as well as conversational CBRs [19][20]. Depending upon the broad functionalities, the framework is divided into five layers as shown in figure 4, each layer having components and interfaces specific to functionality of that layer. The components implement core functionality while interfaces provide interactive environment to develop, manage and configure the models. For example, inference engine is implemented as a component: Rule-based ES Engine, while the interface: Rule and UDF Manager provides interactive interface to retrieve, build, modify and store rule-based expert systems and UDFs (User Defined Functions). The framework allows knowledge engineers to add their own functions, called UDFs and invoke them in rule-base. A function implements well defined functionality that do not need complex set of rules but procedural logic. The code of UDF can be easily modified without change in inference engine like expert system rule-base. The details of this framework and its working can be found in [17]. Our purpose in this paper is to discuss how such frameworks can be used to build N=1 analytics that work in real-time and can be integrated into operational systems. Access layer has been added to access various services of the hybrid framework and integrate with other external systems. The services can be accessed through web services, APIs, HTTP calls or embedding interactive sessions inside web applications. The components and interfaces of access layer are connected to other four layers although it is not explicitly shown in figure 4.



Fig. 4 Hybrid intelligent system framework

The hybrid framework works in two modes: *development* and *run-time environment*. The intelligent systems can be developed and tested in development mode and can be deployed and executed through run-time environment. Figure 5 shows a screen shot of development environment. Based on functionality, the development interfaces are grouped. Once intelligent systems are developed and tested, they can be accessed and executed by using various web services, through HTTP calls or by using APIs. The web services supported by the hybrid framework are divided into groups based on functionality of web services.



Figure 6 shows the parti

Fig. 5 Rule manager interface of hybrid framework



the hybrid framework can be accessed using web services. Some of the common web services like starting with $DB_$ help to access data from databases while web services starting with *Session_* help to manage common pool of session data which is shared by multiple intelligent systems.

CBR_Run	ExpertSystem Run
CBR_RunWithData	ExpertSystem RunWithData
CBR_GetMatchingCases	1
CBR_GetSimilarValues	File ReadFromFile
CBR LoadSimilarities	File SaveToFile
CBR SetSimilarities	The_buveToThe
CBR_SetSimilaritiesFromDB	Report ConvertOuervResultInClientForm
	Report GetReport
DB_BeginTransaction	Report GetSQLReport
DB_Commit	
DB_Rollback	Session GetData
DB_ExecuteScript	Session LoadData
DB_GetQueryResult	Session SetVariableValue
DB_InsertData	Session GetVariableValue
DB TransferData	Session ShowReport
DB_UpdateData	Session_bilo wreport
	UDF Execute
Data_TextTransform	UDF ExecuteUsingList
Data XMLTransform	

Fig. 6 Partial list of web services supported by the hybrid framework

We have developed various prototype systems to demonstrate capabilities of the hybrid framework. Some of them are in knowledge-based recommendation systems. Most of them use combination of expert system and case-based reasoning technology. One of the prototype applications is transaction monitoring which is discussed briefly, the purpose is how such applications are built and invoked. This application monitors individual transactions. It has been modeled defining generic transaction characteristics like *transaction Id, amount (cost/value), date, time, merchant name, merchant location (city/area/place), merchant type, mode of payment* and *items purchased*. We derive other attributes from base attributes. E.g. day type: *week-day, weekend, holiday* derived from *date and time*.

The application scans and matches the current transaction with past transactions (of that user) and user's criteria. The user can specify what kind of generic transactions he or she would like to do. Each generic type of transaction becomes a case. E.g. a user may specify preference 'he would normally buy grocery items of amount m, around location l, preferably on evenings on week-ends'. This user preference is stored as a generic transaction. The user can specify multiple generic transactions as criteria. The application uses combination of rules, basic statistics and CBRs. Rules are used to do qualitative analysis as well as quantitative using various functions. These rules also control and call CBRs. Variety of functions are been added to the hybrid framework rule engine like STAT to do basic analysis of transaction of data. It returns statistics of past transactions like average, standard deviation, and maximum amount transacted. Qualitative analysis is done using set of rules. For example, one of the rules is:

IF Transaction.Merchant Type IS Grocery Store

AND Transaction.Merchant Location City IS Mumbai

AND Transaction. Time >= 2300

AND Transaction. Time <=0700

THEN APPEND (ScanReport,"Purchasing at Odd Hours")

Transaction Monitori	1
Transaction ID	
OK Back	
Break Session	
UK Back Break Session	

Transaction Monitoring

Customer ID	2	
Transaction ID	15	
Amount	25000.00	
Date	08/04/2005:14:57:38	
Time	08:35	
Location	D_MART1(Merchant) 74.23% 80%	
Matching with Past Transactions		
Personal Criteria Matching		
Report	Report. Purchasing at Odd Hours Double than max amount Quite more than average amount	

Fig. 7 Execution of intelligent system in interactive mode

st To test the operation using the HTTP POST protocol, click the 'Invoke' but Parameter Value	
o test the operation using the HTTP POST protocol, click the 'Invoke' but Parameter Value	
Talao Talao	:on.
p_GoalVariable: Transaction.Scan	1
p_XmlData: <pre><cose><cd><n>Transaction.ID</n><v>15</v></cd></cose></pre>	/> </td
p_OutputVariableList: [[Transaction.Report,Transaction.Average Matching	g,Tra
Inv	oke

Fig. 8 Execution of intelligent system using web service

Figure 5 shows one of the rules loaded of this application in Rule Manager. Figure 7 shows screen-shots of interactive mode and results of the application. Figure 8 shows explicit execution of the application using web service: ExpertSystem_RunWithData with goal: Transaction.Scan. The outcome of the application is shown in figure 7 has three distinct components: a) how much current transaction is matching with past ones using CBR, b) how much current transaction is matching with user set criteria using CBR, and c) quantitative and qualitative assessment using basic statistics and set of rules. Intelligent systems that monitor transactions as discussed above can be integrated into operational systems such as bank automation systems through web services. This can help banking firms to continuously monitor transactions especially like credit card transactions on continuous basis to reduce possible frauds. These intelligent systems can be triggered and executed based on certain criteria (e.g. it exceeds certain amount) before transaction gets authorized.



Fig. 9 Intelligent systems for 1 to 1 CRM services

Customer Attraction

Automated expert advisory systems (knowledge-based recommendation) help the customer to find out what product fits to his/her profile and requirements in easy way rather than the customer spending time going through lot of products, understanding them, finding out which products suits them etc.

Customer Retention

Personalized campaigns can effectively target the customer for right promotions at the right time and at the right place by approaching the customer using right communication channel. Personalization systems understand the customer's interests, suggest or offer right products with discounts which customer is likely to buy. This can be done on-the-fly to see customer's changing interests. Helpdesks help customers to resolve various issues related to products.

Customer Development

Personalized campaigns and personalization and recommendation systems can effectively up-sell and cross-sell based on customer profile, interactions and transaction history. Intelligent systems can assess risk of the customer on ongoing and adjust various parameters to offer best possible services (e.g. automatically increasing credit limit) or making provision to reduce possible loss (e.g. automatically decreasing credit limit) without affecting customer service

Fig. 10 CRM using intelligent systems

Figure 9 shows list of prototype applications being developed backed by intelligent techniques to have 1-to-1 services from customer's perspective. These kinds of applications can play important role in customer attraction, retention and development. Figure 10 shows in brief how such 1-1 services can be backed by intelligent systems. Once such systems are developed and tested, these systems can distributed, integrated and accessed/invoked in real-time into operational systems.

Figure 11 shows an application developed in banking domain to advise users on mortgage loans based on banking or financial institution selected. It is invoked into financial website by embedding the expert sessions with the user

whenever user clicks on tab conversion.



Fig. 11 Interactions through expert system invoked in web application

BI tools such as data mining tools play major role in building recommender systems. Recommender systems [21] have become wide-spread and many websites have these systems now for better user and consumer personalized experiences and to discover items (products, contents or services) by mining huge transactional data gathered through customer interactions. Firms like *Amazon*, *Netflix* provide unique experiences to their users using recommender systems. Based on understanding and analysis of individual user's browsing and buying patterns, the websites serve the personalized web pages. This helps such firms to attract and retain (customer intimacy: deeper understanding of individual customer preferences) the customers, understand buying patterns and manage resources well.

There are four basic types of recommendation approaches cited in literature [21]-[23] a. *collaborative filtering*: items are recommended based on liking of similar users, b. *content-based filtering*: items are recommended based on user's past

likes and dislikes, c. *demographic filtering*: recommendations based on a demographic profile of the user and, d. *knowledgebased recommendations* (like advisor systems): items are recommended based on deep knowledge about the itemdomain exactly fitting to customer needs, objectives and interests. All these approaches have limitations and strengths which bring in scope for hybrid approach that combine content-based, collaborative, demographic filtering and knowledge-based recommendations [24]. There are many hybrid systems that combine content and collaborative filtering [25], while some systems implement only knowledgebased recommender [26]-[28].



Fig. 12 P&R system Input and Output

III. P&R FRAMEWORK

In this section we describe a P&R framework called Mooga.NET. Throughout the paper we will be referring it as P&R Framework. This framework is developed with specific extensions required for a typical recommender system on top of the hybrid framework. Figure 12 shows set of possible inputs recommender system takes and functionalities it providing using hybrid of various recommendation approaches. Outputs will be displayed in respective widgets on web pages. Some of the widgets will be personalized items. Since P&R framework works on top of hybrid framework it has all advantages of such kind of frameworks [17]. P&R framework uses hybrid of ES and CBR techniques to develop recommender systems that can have all four recommendation approaches implemented. It is domain independent and can work for many types structured items including financial ones.

We describe the working of P&R framework at higher architecture level rather than going into finer details. The purpose of describing this framework is more from utility, usability and ease of model development point of view rather than comparing it with other frameworks, tools and algorithms in recommendation space. We see contributions of the P&R framework from the perspective: a) it uses hybrid AI approach to P&R: combination of deep domain knowledge using ES + machine learning using CBR, b) it is a comprehensive integrated development framework to build, test, deploy, customize and configure recommender systems using hybrid approach quickly, c) it is configured to work in real-time and can be integrated into operational systems using web services or HTTP calls, d) it includes most of the functionalities required for true P&R (collaborative, content-based, demographic as well as knowledge-based).

Some of applications developed using the hybrid framework includes knowledge-based recommender system like for mobile selection [29], car selection [18] and software selection [30]. Most of these applications use combination of ES and CBR technologies. ES technology has been used in host mode and CBR technology in assistant mode. Various parameters of CBR can be controlled and set at run-time. In product recommendation applications, ES assists and guides the user in selecting and specifying right and only relevant inputs based on user's constraints, interests and objectives, while CBR searches and recommends the most matching products based on relevance to user's preferences and constraints [29]. The hybrid framework supports large number of matching functions and various types of features to model problems. Rules/s can be written to cluster the products based on features to recommend the products when a product is selected by the user.

CBR engine of hybrid framework has in-built component to build associations (similarities) between feature values based on transaction history (e.g. past downloads, browse, ratings etc.). This reduces the job of explicitly defining similarities between feature values e.g. if one of the feature in book selection is *author*, similarity between author say x and other authors can be done in two ways a. by considering clickstreams (people who clicked on x also clicked on author y), the strength of association depends upon number instances of clicks and number of users and recentness of clicks b. using some context like category of the book e.g. if the books written by author x are already classified under category say Management/Marketing, then similarities between author xand other authors who write books in *Management/Marketing* category would be set. First approach is like using collaborative filtering on authors while second one is clustering authors based on context of selected author.

Similarities between features values are calculated from result data-set returned in response to database query defined for that purpose. The query can be configured to have the fields (attributes) that represent context while clustering values using *context* or that restrict to build associations amongst values (e.g. associating authors within language of books). In above example, along with category *Management/Marketing*, other attributes like *language of book*, *publisher of book*, *type of book* etc. can be considered if they are present in database. A weight for each type of context (category, language, selected feature, etc.) is set to calculate similarity based on weighted sum method. The weights of features themselves can be store in a database table to do computation at database server. This is illustrated as follow using mathematical form.



Fig. 13 Components and architecture of P&R framework

where W_i is weight given to

database value dv.

context C_i , $C_i f v$ value of ith context for f v and $C_i d v$ is ith context for

If fv is value of feature F then

 $Similar(fv) = \sum_{i=0}^{i=n} W_i * Sim(C_i, fv, C_i, dv)$ Sim(Cfv, Cdv) = I if Cfv = Cdv else 0.

We have tested such associations in Indian movie database (we developed a prototype for one of the movie rental website in India). To associate actors, actresses and directors, context like *movie name*, *genre*, *sub-genre* (like *family/kids*), *tags* given by experts (like *romantic*, *happy*, *relationship*) and *language* (like *Hindi*, *English*, *Gujarati*, etc.) were used. We found interesting clusters (associations) of actors who have acted in many movies of specific genre, sub-genre and language together.

We understood various requirements (including inputs from RSS feeds [17]) of a typical recommender solutions and added extensions (functionalities) to develop recommender systems quickly and integrate them into existing websites/portals. Following four broad requirements are considered to develop the P&R framework. a. It should support almost all kinds of structured items. It should support and extract contents stored in RSS formats b. P&R solution should include all functionalities like user-profiling (based on user's static as well as dynamic derived out of user's transactions), recommendation using hybrid of collaborative, content-based, demographic and knowledge-based approach. Recommendation should not only work for items but also for keywords, tags and selected features c. P&R solutions should be developed quickly, they should be customizable, configurable, and models should be easier to understand. The entire framework should be self-learning dynamic reflecting changing interests of users. d. It should work as a BI layer or added as a feature which can be easily plugged with fewer

modifications in existing systems. Keeping above requirements, hybrid framework is extended to build P&R framework. This P&R framework supports all four recommendation approaches as described in table I and functionality as shown in table II. Functionalities are implemented in modular way using web services that are specific to P&R framework.

TABLE I RECOMMENDATION APPROACHES

Approach	How it is implemented		
Collaborative Filtering	This has been addressed using association algorithm in- built into CBR engine as discussed earlier. This algorithm directly takes dataset (through predefined queries) from database to build associations.		
Content-	Using set of user defined functions and CBR approach.		
based	Functions implement logic to create dynamic user		
Filtering	profiles (reflecting user's changing likes/dislikes: captured <i>feature-wise</i>) based on click-streams and ratings. CBR is used to show most matching items whose features match with individual profiles. It can take into consideration user's preferences set in the form of feature values e.g. if one of the feature is <i>item language</i> then user can set preference for <i>language</i> .		
Demographic	Profiles of most similar users are searched that match		
	demographic profile of selected user using CBR. These		
	profiles are used to show the most matching items.		
Knowledge-	a. Combination of expert system and CBR approach.		
based	Expert system guides the user in selecting relevant		
	inputs based on user's requirement and CBR		
	searches most relevant items matching		
	requirements.		
	b. CBR is used to search most similar items to given		
	item based on feature similarities (e.g. Show Similar/Related kind of functionality)		

A. Major Components and Architecture

As shown in figure 13, there are three distinct entities in overall recommendation solution a. *Client system*, b. P&R

framework, and c. *External systems*. Client system represents website, web application or portal that needs P&R solution. P&R framework consists of all components and interfaces required to build, test, integrate, customize and configure recommendation solutions (as a part of base hybrid framework). External systems are required when specific information about the items is to be retrieved from external websites such as details of features, user ratings and reviews. TABLE II

MAJOR FUNCTIONALITIES OF P&R FRAMEWORK Functionality Major Input Description Items you may User ID List of items that user may like. This like based on discovery is (using combinations of collaborative and content filtering) Your picks User ID List of items based on user likes and dislikes using content-based filtering technique. Top picks Items selected based on popularity or business logic specified by the client organization People also Item ID List of items generated based on collaborative filtering on given item. liked (items) Keyword List of keywords generated based on People also liked collaborative filtering on given (keywords) keyword. Item ID List of items which are logically and Related Items contextually similar to given item using CBR based matching Related List of items which are logically and Keyword Keywords contextually similar to given keyword Help Me User ID Knowledge-based recommendation system to help in selecting the item

Client system is either loosely coupled to P&R framework through web services, HTTP calls or by embedding interactive sessions or tightly connected by API calls. Client CMS (Content Management System) database or web application database (henceforth called *client database*) is accessed in P&R framework in non-intrusive mode. Access to client database is required to synchronize data transfer from client system to P&R framework on periodic basis or based on events.

Since web services are widely used to interconnect different types of systems loosely, we restrict our discussion to only coupling using web services. P&R framework can be coupled to any client system that supports web services.

1) Database Schema

We have modeled P&R framework on three basic types of information entities: *meta-content*, *user* and *transaction*. Database schema and models are divided into two sets a. *generic* and b. *specific to domain*. Domain schema (table III) depends upon type of products supported. The generic schema is designed in such a way that it can support multiple applications in the same database instance. Domain specific schema contains information required for domain modeling e.g. for mobile device item attributes can be *screen size*, *multimedia support*, *internet connectivity options*, *operating system*, etc. Similarly user and transaction specific information can be added.

Generic schema is common to most of the type of items (like RSS formats support multiple types of contents: movies, music, news etc.). In generic schema, we define various generic database tables and customizable views to retrieve datasets required for modeling at development and run-time.

TABLE III INFORMATION ABOUT GENERIC DATABASE SCHEMA

item	what mormation is stored
Meta-content	 Basic attributes (features) of item like <i>title</i>, <i>type</i>, <i>language</i>, <i>format</i>, <i>creation date</i>, <i>publication date</i> etc. each item has unique ID that we maintain same as that of client system follows. <i>Taxonomy</i>, <i>Keywords</i>, <i>Predefined Tags</i> by experts Relationships between items, taxonomy, keywords (with <i>roles</i> and <i>weights</i>) and tags
User	 Static profile: demographic information captured initially through questionnaire or account opening form: it can be personal (like age, gender, area code, education, employed) as well as user's interests. Dynamic profile (based on user's transactions). Dynamic profile is of two types. Global profile and Category-wise profile. Global profile captures and stores what user likes in general. While category-wise profile captures what user likes in a particular category. Each subcategory-wise profile contains what items, keywords, tags, language user chooses or likes along with time abstraction and location specific profile.
Transaction	• User interactions with client system (like click-streams, downloads etc.), interactions can be codified based on evens like click, browse, search, download, rent, reminder, add to favourites, add to wish-list, add rating, add tag etc.

Some of the item features we put under broad feature called *keywords* with role and weight assigned to it e.g. authors in book item will be treated as keywords with role: *author* similarly publisher will be given role: *publisher*. Weight indicates relevance of that keyword in that item, helps in content filtering e.g. if a book is written by two authors, weight (relevance to that book item) of each author name can be equal. Especially in movie databases, the actor names are stored in sequence, with first actor playing major role vis-à-vis the last actor, in such a scenario, first actor has more relevance hence more weight etc.

2) Models and Configurations

Similar to database schema, models are also divided into two types, generic ones and specific to domain. The hybrid framework has various interfaces to manage models and configurations. Following sub-sections describe some of the important models and configurations required for recommendation solution. Knowledge-based recommendation systems are not covered in this paper, it is discussed at length in [29].

a) Domain Vocabulary

Set of all objects (variables, domain values etc.) that are

required to model P&R using ESs and CBRs. The domain vocabulary has variables for meta-contents, users and transactions. The variable names are prefixed appropriately to discriminate logically as shown in figure 14 (most of the figures are screen shots of application EPG: Electronic Programme Guide for TV application, screen-shots are either cropped, extended to proper and readable views).



Fig. 14 Sample generic domain vocabulary

b) Dynamic queries

Dynamic queries are predefined database queries that are used by the framework to retrieve the datasets at run time in various components. This reduces efforts of writing database queries explicitly in rule-base or in functions. These queries are not hard-coded and can be added, modified and removed easily based on modeling requirements. The queries are formulated based on requirements in different components. Figure 15 shows different purposes of dynamic queries and figure 16 shows dynamic query that is used to calculate recommended keywords using collaborative filtering algorithm. Normally queries access data from database views, these views can be easily customized at database side. Figure 17 shows a generic database view called AG_Keyword and its output. This view takes last 90 days transactions and restricts associations of keywords within their roles only. That means relationship between two keywords would be built only if their roles are same. This gives greater degree flexibility in customization and helps in better modeling of filtering at website, e.g. if user clicks on keyword (say author of book), then recommended keywords would show only authors not other keywords like publishers etc. Similarly dynamic queries for collaborative filtering (or content filtering based on context) for items, tags or any other feature can be modeled. Dynamic queries can contain variables whose values are populated at run-time.

Other type of dynamic queries includes predefined queries (accessed by IDs) for defining CBR search space, getting user profiles, item details from database and do on. Figure 18 shows dynamic query used for CBR search whenever items matching with user profile are searched. If a new feature is added in CBR search, corresponding field can be added in this dynamic query. The P&R framework stores static information about items (which is not used for indexing purpose) like language, actors, directors in memory so that they don't have to be fetched from database every time CBR search is made.

We call them *lookup tables*, they are indexed by some *index* key like C_ID_Index in figure 18. Whenever query is executed, based on values of index keys in rows, query results are appended with corresponding static information.

Application	EPG 💙 ? >> <<		
Variable Group	EPG 💌 >> << Show Query Interfaces		
Selected Dynamic	Keywords 💌 >> <<		
Query	Update/Refresh Remove Build Query Test Q		
New Dynamic Query	Add New		
Purpose	CollaborativeFiltering		
Linked/Group/Code Menu	DatabaseMenu DynamicMenu		
Selected Database	CollaborativeFiltering		
Field Name/s	ContentFiltering		
View Name	NextPush		
	Similarities		
Fig. 15	Dynamic query types		
Purpose	CollaborativeFiltering 💌		
Linked/Group/Coo Menu	Je Not Set 💌		
Selected Databas	e EPG 💌 >> <<		
Field Name/s	ID,Keyword,Wt		
View Name	AG_Keyword		
	APP_ID=5 and Wt is not null		

Fig. 16 Sample dynamic query

TOP 100 PERCENT CONVERT(varchar, U_ID) + '' + K_Level AS ID, K_Level AS Role, (1300 - MUNQATEDFF(mixte, D_Date, GETDATE()) / 100.01 / 1300 * SUM(doo.udf_GetWeight(Download_Type, K_Level)), 2) AS Wr, Keyword FROM - doo.Cld?steams (K_Level IN (YY, 'TG', WO', CH') AND (D_Date >= GETDATE() - 90) BY APP ID, LD, Keyword K, Level, Keyword, Keyword (COUNT(*) >= doo.udf_GetGeneralizationFactor(K_Level)))

ID	Role	Wt	APP_ID	Keyword	
39786:TG	TG	0.16	5	Drama	
39786:TG	TG	0.33	5	India on Discovery	
39786:TG	TG	0.18	5	Mythology	
39786:MD	MD	0.24	5	Serious, Involved Viewing	
39927:KY	KY	0.16	5	Hindi	
39927:TG	TG	0.16	5	Hindi	
39927:TG	TG	0.16	5	Mythology	
39928:MD	MD	0.22	5	Family Viewing	
39928:CH	CH	0.55	5	Max	

Fig. 17 Database view linked to dynamic query and output

Select Goal	Variable Group EPG 🔍 >> << Goal/Report Variable iPushGoa				
Interface for:	CBR CBR CBR CBR CBR CBR CANN_TRAINING CANN_TESTING CASE_MANAGEMENT				
System/Query ID	EPG.NextPush 💌 >> << New ID				
View Linked Queries Test Combined Query View All Queries Rule Filter					
Query Details					
Query Sequence No	ND O Image: Second constraints Second constrats Second constraints <th< th=""></th<>				
Selected Database					
Data/Fields Selected	(distinct TOP [Rows] C_ID as C_ID_Index_H_ID_CID_HID_CID_HID_Key,Current_Timing,Current_WeekDay, Current_Monthy				
From Table/s	IPushCBRSearchView name, keywords, language etc. These are populated from lookup table.				
Where Clause	APP_Id=5 and c_ID not in (select c_id from downloads where u_id=[EPG.User_ID]				
	which are already seen by the user.				

Fig. 18 Predefined query for CBR search

c)Modeling using UDFs, Expert Systems and CBR

Various generic ESs, UDFs and CBR schemas are created to take care of various functionalities in recommendation solution. UDFs are useful when only single rule is required, however if there are set of rules required to build complex logic, rule-base is written. Figure 19 shows some of the UDFs

coded in P&R framework. Figure 20 shows UDF *CreateClusterForContent* coded to create and return cluster of items around given item. Similar to rule-base, UDFs can also be modified depending upon the functionality required. This helps to implement dynamic business rules and logic using functions. Modifications can be done even client system is live e.g. weights of feature *EPG.Content_Language* can be changed from 25% to 30%, the P&R framework reflects such changes immediately.

Application	EPG ? >> <<		
	EPG 💌 >> << Content_Language		
	Multivalued ID Type ID_CaseSchema		
Variables and Values	Possible values of variable:EPG.Content_Language Benojpuri Cantonese Dannish Add Value		
Operator/Function	Expression1 = IS ARE HAS BEEN Expression2:Boolean		
Other Options	Add Expression AND () " Space Nex		
Selected UDF ID	CreateClusterForContent		
New UDF ID	AddContentRating		
Description	CreateClusterForContent CreateClusters GenerateGlobalUserProfile GenerateNextAdPushForUser		
Argument List	GenerateNextPushForUser GenerateNextPushForUser GenerateNextPushForUserForAllL1s GenerateUserProfile GenerateUserProfile		

Fig. 19 Partial list of UDFs

P&R framework has predefined generic CBRs modeled and configured using generic features as listed in figure 21 to address various functionalities given in table II. Word *CF* in feature name represents that feature similarity values are generated using collaborative filtering algorithm. Features named *EPG.Content_L1*, *EPG.Content_L2*... represent taxonomy at first level, second level respectively.



Fig. 20 Implementation of UDF: CreateClustersForContent

Based on modeling requirements various features and their parameters are set, figure 22 shows some of the parameters used. Models using hybrid recommendation approaches can be implemented in various ways. For example, if content-based filtering is to combined with collaborative filtering in *weighted hybrid mode* [24] then feature (e.g. *EPG.Content_CF_CID* in figure 21) whose similarity values are calculated using collaborative filtering algorithm is included in CBR (which is configured and used for content-based filtering) by setting *appropriate weight*. Feature can be removed or its weight is set to 0 if it is not to be combined.

Select Application	EPG ? >> <<
Case IDs	NextPush >><
New Case ID	Add Case Renar
Selected Feature	EPG.Content_CF_CID ? >> <<
New Feature	EPG.Content_CF_CID EPG.Content_CF_Keyword EPG.Content_CF_Tags
	EPG.Content_CIDs EPG.Content_Description EPG.Content_Format EPG.Content_HID
	EPG.Content_HID_Prority EPG.Content_LID EPG.Content_KeywordWithWeights EPG.Content_L1 EPG.Content_L2 EPG.Content_L3 EPG.Content_L4 EPG.Content_L4 EPG.Content_L4
	EPG.Content_Tags EPG.Current_Month EPG.Current_Timing EPG.Current_WeekDay

Fig. 21 List of generic features

EPG.Content_CF_CID ? >> << Remove Feature							
Variable Group EPG Variables Content_CF_CID Variables Content_CF_CID							
Ī	Key/Index Parameters						
	Feature Type	✓ Key ☐ Index ☐ Multi_Index ☐ Solution ☐ Output ☐ Group ☐ ParentNode	Index Level	-1 > < Club Index Values Self Index			
l	Weight(%)	0.00 > < Check Weight 🗹 Total Weight:82.00%	Max Cases at Index	10 > <			
l	Group to Feature	Not Set V >> <<	Max Cases at Level	25 > <			
	Linked Case	Not Set 💌 >> <<	Max Cases From DB	25 > <			
	Upper Hirarchy Feature	EPG.Content_HID ? >>	Cut-Off (%)	10 > <			
	Report URL Params	GoalVar=EPG.Queries&Type=SQL& QueryID=ContentDetailsView&Filter=C_ID=[Value]& Layout=Vertical&ShowOnlyOutput=Yes&Ajax=Yes	Max Indices	10 > <			
l	Similarity Measure						
l	Similarity Measure Symbolic & >> << UseMultiValuedMeasure Multi-Valued Measure Cardinal >> <<						
l							
l	Custom Function	NotSet V >> <<					
	Reverse Case/Problem Values	□Yes					
	Collaborative Filtering Query	Description V >> << Run Collaborative F Do not consider similarities alow cutoff (0-1) 0	iltering Undo				
	Content Filtering Query	DBSimilarities_CID_CF	ontent Filtering Undo	Similarities			
ĺ	Similar Values Function	NotSet V Dynamic query	EPG.Description	is linked to			
	Similarity Precision	≥ ✓ leature EPG.Co be used to fetch	dataset to comput	e items based			
-	Update Setting	on collaborative	e filtering				
T	-						
I	Group	10 V? >> << Remove Below CutOff Apply to All	I Groups 🛄				
I	Existing Values	10000000985870000 ♥ ↑ >> << Remove Add Sim For Possible Values 10000000985870000 <>1000001491020000 [0.50] ♥ >> << 10000000985870000					
l	Ouery Value						
l	Case Value	10000001491020000	_				
l	Similarity	0.50 Symmetric This combo b	ox shows items (a	long			
	Possible Values	1000000985870000 >>> << With similarit Move To C.Value Move To C.Value Content ID: 1	y) which are simila 000000098587000	ar to 00			
I	Selected Similarity	Update Add Remove Copy Pusing Collabo	rative filtering algo	orithm			
	All Similarities Import Similarities (MextPush Format) Check Values While Import Refresh from D& Save To DB Copy To Clipboard Remove Complete Range						

Fig. 22 Parameters of selected feature

Based on business logic, feature parameters such weight, similarity function, range of values are changed. For example, if *language* of item is one of the important features, and business policy is to show the user items in the language that user likes, then weight of language feature can be set to high compared to other features. There are lot of database and CBR functions provided to implement complex business logic using

UDFs and rule-based ESs. For example UDF GenerateNextPushForUser, looks into each of the subcategory-wise user profile and based on relative interests of user in that subcategory it searches the items in that category using combination of filtering techniques. Hybrid framework provides testing and debugging environment along with various development interfaces. Debugging and testing can be done interactively, UDFs can be included in rule-base and inputs can be asked at run time.

d) Tag Mapping

Meta-contents are created from client database or even from RSS feeds. Since hybrid framework converts all database calls into XML, field names are converted as XML tags. Mapping is defined between source field names (which are be used to import data) and meta-contents. Figure 23 shows sample tag mapping from RSS schema to P&R generic schema. Once this mapping is defined, data can be extracted or imported from client database or RSS feeds by calling appropriate web services.



Fig. 23 Partial sample tag mappings

e) Reports and forms

Functionality of *Form Designer* and *Report Designer* of the hybrid framework has been extended to generate forms and reports automatically for interactive knowledge-based recommendation sessions based on features selected in CBR configuration and domain vocabulary. This saves explicit efforts of creating forms and reports. During recommendation session, appropriate forms are invoked to ask and get relevant inputs from the user while formatted reports are used to show recommended products, explanations and related information.

f) Scheduled tasks:

P&R framework has scheduler to carry out various activities especially data transfer from client database to P&R framework on periodic basis. It carries these activities using web services. List of such activities can be entered into scheduled task setup configuration file.

3) Web Services

Once development, analysis, customizations and testing of recommendation solution are done, it can be loosely integrated into operational systems through web services. There are two types of web services P&R framework uses while integrating with client systems. P&R framework web services and hybrid framework web services (shown in figure 6). Figure 24 shows partial list of P&R framework web services. The names of web services are prefixed with broad functionality they provide. Services starting with MetaContent_ are used to manage meta-contents e.g. MetaContent_ImportFromRSS is used to import data from RSS feeds. While PnR_ services are used for P&R. Services starting with Trans_ are used notifying transactions (user interactions) to P&R system. In PnR services word related indicates clustering based on CBR while matching algorithm recommended indicates collaborative filtering. Some of the web services wrap functionality using ESs and UDFs so that business logic can changed web be easily. For example service PnR_GetRelatedContents internally calls UDF CreateClusterForContent which returns cluster of items around given item. If the logic for creating cluster is changed (e.g. giving more weight to feature language), it will be automatically reflected when PnR_GetRelatedContent called next time. This gives greater degree of flexibility in managing business logic based on client's requirements.

Category_AddChild MetaContent_GetCountryList MetaContent_GetFormatList Category_GetAllCategories MetaContent_GetKeyWordsInHierarchy Category GetChildren Category_GetHID $MetaContent_GetLanguageList$ MetaContent_GetTypeList MetaContent_GetUserTypeList Category GetL1 Category_GetL1Categories MetaContent_ImportFromRSS Search CreateAllIndexes MetaContent_RemoveContents Search_CreateCategoryIndexes MetaContent RemoveKeyword Search_CreateDescriptionIndexes MetaContent_ResetPersonalDetails Search_CreateKeywordIndexes Search SearchForContents PnR DiscoverContents Search SearchForKeywords PnR GenericFiltering PnR_GetContentsForBrowse Trans_AddRating PnR_GetPersonalizedContents Trans_AddTag PnR GetPersonalizedContentsUsingFilter Trans_NotifyTransaction ${\tt PnR_GetRecommendedContents}$ PnR_GetRecommendedKeywords User_AddUser PnR GetRelatedContents User CreaterUsersFromMasterUsers User SetUserStatus PnR GetRelatedKeywords

Fig. 24 Partial list of P&R web services

Most of the $PnR_$ and $Search_$ services cache results in database (along with date and time) instead of calculating again and again. These include parameter called $p_Minutes$, to indicate how long results should be cached in database before they are recalculated again. Based on frequency of updates of items, number of users active at a time, available hardware resources, these parameters can be set for different web services. For example, item clustering need not be done again and again unless new items are added or existing removed etc. while web services for collaborative filtering e.g. $PnR_GetRecommendedContents$ and personalization e.g. PnR GetPersonalizedContents can be run every fifteen

minutes or half-an-hour to reflect changing users interests.

st						
To test the oper	ation using the HTTP POST	protocol, click the 'Invoke' but				
Parameter	Value	After every 15 minutes cluster				
p_Key:	1234556	of items (runs UDF:				
p_CID:	1000000939410000 CreateClusterForConter item id=100000093941					
p_Minutes:	15	would be created				
p_CutOff:	0 N	Number of related items to				
p_MaxValues:	100	e returned.				

Fig. 25 Explicit invocation of web service

PnR_GetRelatedContents[1] - Notepad
Eile Edit Format View Help
xml version="1.0" encoding="utf-8"?
<string< td=""></string<>
xmlns="http://ikensolution.com/webservices/">[10000000915990000:19=81.8,100
00001011110000:19=81.8,10000001010270000:19=81.8,1000009 988990000
:19=81.8,10000000987920000:19=81.8,10000000986750000:1/~~\.8,100000
01026400000:19=81.8,10000000985780000:19=81.8,100000:19
=81.8,10000001010580000.19=81.8,100 Clustered tiens returned in sequence 0009
64120000.19=81.8,1000000933360000 with item iD:Category ID=% Matching. =81.
8,10000001008440000:19=81.8,1000000Means item ID:1000000915990000 1868
90000:19=81.8,10000000997280000:19=matches 81.8% in category ID:19
0000000783230000:19=81.8,100000010[1000000939410000]1000
00:19=81.8,10000000996270000:19=81.8,100000009852700000:19=81.8j
ng>

Fig. 26 Source view of web service output of PnR_GetRelatedContents

Related Programs	Blown Away	,				Other Screenings			
Nero 08:30 PM Monday 25th May	- CAR	an and	Genre:	Film Action					
Superman II 09:00 AM Tuesday 12th May			Channet Director:	Star Vijay Stephen Hopkins					
No Retreat No Surrender 01:30 AM Friday 8th May			Language:	English					
Wake Of Death 02:35 AM Tuesday 19th May	(Death Widget for <i>Related Items</i> functionality: items are displayed (after formatting) by that are retuned calling <i>PnR GetRelatedContents</i> which user clicks on <i>Blown Away</i>								
House Of Flying Daggers 10.30 PM Sunday 31st May	SHARE 2	Add to favourite	Renind Me						
		Widget fo	or Peopl	e also Liked Items f	unctionality:				
Viewers also liked	Synopsis	items are displayed (after formatting) that are returned by calling <i>PnR GetRecommendedContents</i>							
Hero 00:30 PM Monday 25th May	when user clicks on Blown Away with item ID of Blown Away								
Born To Fight 11:00 PM Wednesday 27th May	Cast Jeff Bridges , Tommy	Lee Jones , Suzy	Anio						

Fig 27 Screen shot of website invoking web services



Fig 28 Screen shot of website invoking P&R web services

Figure 25 shows invoking of web service *PnR_GetRelatedContents* Figure 26 shows output of web service call. Most of the web services return only item IDs (we call as *Content_ID* and in database field *C_ID*, while

importing item data from client database, IDs are maintained as they are in client database). This makes it easier to implement and manage at front-end and items can be displayed in various widgets based on website design policy. Figures 27 and 28 show how items are displayed in various widgets in EPG website (to respect confidentiality we have removed other details).

We will not discuss web services but one of the important services is *PnR_GetPersonalizedContents*. It takes three major inputs user id, top level category and criteria. It returns items in selected top category or genre (like film, sports, fashion, etc.) that user would like based on user's static as well as dynamic profile. Criteria indicate when user profile and personalized contents should be recomputed for the active user e.g. only after at least one download in last 15 minutes (see figure 29 for major steps involved in web service *PnR_GetPersonalizedContents*).



Fig. 29 Major steps in PnR_GetPersonalizedContents

IV. CASE STUDIES

Various prototype systems have successfully developed to demonstrate and test P&R framework functionality and results. Right now P&R solution is being implemented for one of the big content providers in India for their e-Commerce B2C web site selling video and audio albums/tracks online. The first case study is on P&R for mobile VAS (value-added services) application for SonyBMG and other case study includes recommendation on website for EPG for TV programs (TVPs).

Because of confidentiality issues we would not discuss case studies in details. The screen-shots are included in figures 27 and 28 for EPG application. One of the peculiarities of P&R in TVPs websites, recommendations have to be in real time and forward looking (forthcoming TVPs unless repeats), there is no point in recommending the TVPs which are already telecasted and not going to be repeated again on any TV channel.

Brief Requirement Analysis: Studying the client database schema, understanding where required information like meta-contents, user and transactions is available ir client database. What kind of functionality needs to be implemented, events to be included, study of existing website/portal, widgets available etc. Creating Generic P&R Database and Models: this is done by creating shallow copies of database schema and generic models from master- setups. Defining tag mappings to extract data from client database, etc. Creating Master Database: Create Generic P&R meta-contents, users, initial transactions Models and Database by importing data from client database onfiguration using various web services. Modifying database, extract Yes Are customization additional data and customize required? models and configurations No Testing various functionalities, UDFs, expert system results, etc. manually or through web services. Integrating P&R solution into client system through web services, web services can be wrapped by writing APIs at client system to take care of additional security, calls with fewer parameters etc, testing the results after integration On-going improvement, fine tuning the models to get better user experience and desired results

Fig. 30 Major steps in developing recommender solutions using P&R Framework

Figure 30 shows steps followed while developing P&R solutions using P&R framework. TVPs in eight top level categories: Film, Sports, Children, Documentary, TV Show, News, Business and Finance and Music have been modeled and implemented. The data in client database was already structured with TVP attributes like genre, subgenre, episode title, episode no, brief synopsis, casts, sub-casts, directors, guest-casts, keywords, tags and so on. Other information included schedules, which TVP is scheduled on what television channel, external TVRs (television ratings by third parties) etc. When data is extracted, all casts, sub-casts, directors, channels, etc. were converted into keywords with respective roles. Conversion is automatically done at the time of data extraction using tag mapping configuration, mapping source field names into P&R framework field names (e.g. as shown in figure 23).

The website was revamped to enable P&R. It includes various widgets to display items and keywords based on P&R functionalities. Website offers various options for users to interact with website. The user can add program in favourite list, request to send reminder on mobile for a particular program, add tag to program, etc. In P&R framework, these called as events including clicks and store them as user *transactions along with* other information like *date, time, location* etc. Two character codes are given to all these events which are used for personalization like code *TG* for adding tag, *MD* for adding mood, *KY* for click on keyword etc. Each of these events is given weight to denote relevance in building models.

The client web application calls appropriate web service that returns list of item IDs or keywords. E.g. in related program widget, it displays items (programs) in response to web service *PnR_GetRelatedContents*.

The P&R system was initially modeled using generic configuration. However, expert personnel from client organization asked to change the business logic e.g. the programs displayed in *related programs* widget were restricted in *language* and *genre* of selected program. Similarly different weights of features were adjusted based on requirements.

SonyBMG was looking to enter the market with a differentiated service, were looking for extreme personalization solution on mobile for items like ringtones, music and wallpapers [31]. Mooga.NET (with some administration interfaces, figure 31 shows a screen-shot) is currently administrating SonyBMG's portal in Argentina, Chile and being launched in other Latin America countries. Item and context information (like genre, song title, artist name etc.) were extracted from their database into the P&R framework.

One of the challenges in personalization is to show right information on limited screen size to the right user at right time. The personalization algorithm (figure 29), in P&R framework is configured to show only most relevant items based on users interest and device screen size.

System went live in March 2008, figure 32 shows analysis of data transactional data collected from August 2008 to May 6, 2009 to validate effectiveness of P&R framework in mobile space [31].



Fig. 31 Sample screen-shots of SonyBMG WAP front-end

Vol:3, No:7, 2009

V. CONCLUSIONS

Analytics has become integral part of every business. However, traditional approach of building analytics is more of off-line, ad-hoc or periodic and not integrated into operational systems. In this paper, we represented a framework for BI that uses intelligent systems such as expert system, case-based reasoning in modular and integrated way, and accessed through web-services. One of the advantages of such frameworks, they can be used to build N=1 analytics applications focused on analyzing one customer at a time. Similar to dealing with customer one at a time, N=1 analytics can be integrated into organization's enterprise systems to deal with internal stake-holders like employees on as well as manage relationships with external stake-holders like suppliers on one-to-one basis.

Static top 5 made 7.8% of total sales while dynamic storefront backed by P&R framework made 92.2%.

67.6% users who clicked on recommended items ended up in

downloading them

Almost 12% made multiple downloads from the same artist

83% of the artists got at least one download

27% users made more than one download in same session

Fig. 32 Validations figures based on Aug08 to May09 data

Various approaches and techniques are in use to address P&R problems and develop solutions. We have given a complete different thought to P&R problem by conceptualizing and developing a unique comprehensive framework which includes various components required for P&R. We effectively used combination of rule-based expert system and CBR technologies to P&R. The benefits of using such technologies are automatically available to P&R framework like: models are easier to understand and customize, fine tune proper blend of various approaches and manage business policies and rules.

Various algorithms that are implemented to provide functionalities required for P&R do not need to crunch huge amount of data like required for algorithms based on data mining techniques. They are developed in modular way based on required functionality and focus on only one entity at a time: user, item, keyword, tag or any other feature. Based on availability computational resources and number of active users, computation schedules can be modified. At run-time intelligent systems can be distributed to enhance scalability. Couple of industry deployments show utility and practicability of N=1 analytics approach in P&R space.

REFERENCES

- R. Ling, and D.C. Yen, "Customer relationship management: an analysis framework and implementation strategies", Journal of Computer Information Systems, Vol. 41, No. 3, pp. 82-97, 2001.
- [2] E. W. T. Ngai, Li Xiu, D. C. K. Chau, "Review: Application of data mining techniques in customer relationship management: A literature review and classification", *Expert Systems with Applications: An International Journal*, Vol. 36, No. 2, 2592-2602, 2009.
- [3] E. W. T. Ngai, "Customer relationship management research (1992-2002): An academic literature review and classification", *Marketing Intelligence, Planning*, Vol. 23, 582-605, 2005.

- [4] J. Abbott, M. Stone, F. Buttle, "Customer relationship management in practice – a qualitative study", *Journal of Database Marketing*, Vol. 9 No.1, pp.24-34, 2001.
- [5] S.L. Pan and J.N. Lee, "Using e-CRM for a unified view of the customer", *Communications of the ACM*, 46, (4), 95-99, 2003.
- [6] C.K. Prahalad, M.S. Krishnan, The new age of innovation: Driving Cocreated Value Through Global Networks, Tata McGraw Hill, New Delhi, 2008
- [7] Don Tapscott , Anthony D. Williams, Wikinomics: How Mass Collaboration Changes Everything, Portfolio, 2006
- [8] http://www.trai.gov.in/ accessed on 25 June 2009.
- [9] http://www.rbi.org.in/ accessed on 25 June 2009.
- [10] E. Turban, J. Aronson, Ting-Peng Liang, *Decision Support Systems and Intelligent Systems (7th Edition)*, Prentice-Hall, Inc., Upper Saddle River, NJ, 2004.
- [11] R. Bergmann, K-D Althoff, S. Breem, M. Goker, M. Manago, R. Traphoner, *Developing Industrial Case-Based Reasoning Applications*, 2nd Ed., Springer, Berlin, 2003.
- [12] L. Medsker, *Hybrid intelligent systems*, Kluwer Academic Publishers, Boston, 1995.
- [13] S. Goonatilake and S. Khebbal, ed. *Intelligent Hybrid System*, John Wiley and Sons, 1995.
- [14] E. Corchado, J. Corchado, A. Abraham, *Innovations in Hybrid Intelligent System*, Springer, 2008.
- [15] http://www.w3.org/XML/ accessed on 25 June 2009.
- [16] W. Richardson, "The ABCs of RSS". Technology & Learning, Issue 10, 20-24, May 2005.
- [17] R.M. Sonar, "An Enterprise Intelligent System Development and Solution Framework", *International journal of applied science*, *engineering and technology*, Vol. 4, No. 1, 31-35, 2008, Available at http://www.waset.org/journals/ijaset/v4/v4-1-6.pdf accessed on 25 June 2009.
- [18] http://www.ikenstudio.com accessed on 25 June 2009.
- [19] J. Kolodner, J., Case-Based Reasoning, Morgan Kaufmann, San Mateo, CA, 1993.
- [20] A. Aamodt, E. Plaza, "Case-Based Reasoning: Foundational Issues, Methodological Variations, and System Approaches", AI Communications, Vol. 7:1, 39-52, 1994.
- [21] A. Felfernig, G. Friedrich, L. Schmidt-Thieme, "Introduction to the Recommender Systems", *IEEE Intelligent Systems Special Issue*, 22(3), 18-21, 2007.
- [22] A. Felfernig, R. Burke, "Constraint-based recommender systems: technologies and research issues", *ICEC '08: Proceedings of the 10th international conference on Electronic commerce*, New York, NY, USA, ACM, 1-10, 2008.
- [23] G. Adomavicius, A. Tuzhilin, "Toward the next generation of recommender systems: a survey of the state-of-the-art and possible extensions", *IEEE Transactions on Knowledge and Data Engineering*, 17(6), 734-749, 2005.
- [24] R. Burke, 2007. "Hybrid web recommender systems", *The Adaptive Web: Methods and Strategies of Web Personalization*, 377-408, Heidelberg, Germany, Springer, 2007.
- [25] M. Balabanovic, Y. Shoham, "Fab: Content-Based, Collaborative Recommendation", *Communications of ACM*, Vol. 40, No. 3, 66-72, 1997.
- [26] R. Burke, "Knowledge-Based Recommender Systems", *Encyclopedia of Library and Information Systems*, A. Kent, ed., Vol. 69, Supplement 32, Marcel Dekker, 2000.
- [27] A. Felfernig, "Koba4MS: Selling Complex Products and Services Using Knowledge-Based Recommender Technologies", Proc of the Seventh IEEE International Conference on E-Commerce Technology, July 19-22, 92-100, 2005.
- [28] N. Mirzadeh, F. Ricci, M. Bansal, "Feature Selection Methods for Conversational Recommender Systems", *IEEE International Conference* on e-Technology, e-Commerce, and e-Service (EEE'05), Hongkong, 772-777, 2005.
- [29] M. Godse, R. Sonar, A. Jadhav, "A Hybrid Approach for Knowledgebased Product Recommendation", *Communications in Computer and Information Science*, Springer, Vol. 31, 268-279, 2009.
- [30] A. Jadhav, R. Sonar, "An Integrated Rule-based and Case-based Reasoning Approach for Selection of the Software Packages", *Communications in Computer and Information Science*, Springer-Verlag, Vol. 31, 280-291, 2009.
- [31] http://www.ikensolutions.com/files/en/Mooga_casestudySony.pdf accessed on 25 June 2009.