

Unsteady Free Convection Flow Over a Three-Dimensional Stagnation Point With Internal Heat Generation or Absorption

Mohd Ariff Admon, Abdul Rahman Mohd Kasim, and Sharidan Shafie

Abstract—This paper considers the effect of heat generation proportional to $(T - T_\infty)^p$, where T is the local temperature and T_∞ is the ambient temperature, in unsteady free convection flow near the stagnation point region of a three-dimensional body. The fluid is considered in an ambient fluid under the assumption of a step change in the surface temperature of the body. The non-linear coupled partial differential equations governing the free convection flow are solved numerically using an implicit finite-difference method for different values of the governing parameters entering these equations. The results for the flow and heat characteristics when $p \leq 2$ show that the transition from the initial unsteady-state flow to the final steady-state flow takes place smoothly. The behavior of the flow is seen strongly depend on the exponent p .

Keywords—Free convection, Boundary layer flow, Stagnation point, Heat generation

I. INTRODUCTION

A large number of physical phenomena involve natural convection driven by heat generation. The study of heat generation in moving fluids is important in several physical problems dealing with chemical reactions and those concerned with dissociating fluids. Possible heat generation effects may alter the temperature distribution and therefore, the particle deposition rate. In addition, understanding of the effects of internal heat generation also significant in numerous applications that include reactor safety analysis, metal waste, spent nuclear fuel, fire and combustion studies and strength of radioactive materials (Postelnicu, [1]). Foraboschi and Federico [2] investigated steady state temperature profiles for linear parabolic and piston flow in circular tubes. They determined that the volumetric rate of heat generation, $q''' [W/m^3]$ varies linearly with $Q_0(T - T_\infty)$, where Q_0 is the heat generation constant. The relation explained above is valid as an approximation of the rate of some exothermic process, having T_∞ as the free stream temperature.

Vajravelu and Hadjinicolaou [3] studied the heat transfer characteristics in the laminar boundary layer of a viscous fluid over a linearly stretching continuous surface with viscous dissipation or frictional heating and internal heat generation. Chamkha and Camille [4] solved hydromagnetic flow with heat and mass transfer over a flat plate in the presence of heat generation or absorption and thermophoresis. Mendez and Trevino [5] analyzed the effects of the conjugate conduction-natural convection heat transfer along a thin vertical plate with non-uniform heat generation. Continuing the work of Vajravelu and Hadjinicolaou [3], natural convection with heat generation along a uniformly heat vertical wavy surface have demonstrated by Molla et al. [6]. Besides that, Mohammadein and Gorla [7], Rahman et al. [8] and Magyari and Chamkha [9] take into account the effect of heat generation to investigate the characteristics of heat and mass transfer in a micropolar fluid flow. Natural convection flows in a porous medium also have received much attention in recent time due to its wide application in such fields as geothermal energy utilization and oil reservoir modeling. Many researchers interested with the problem of plate that is embedded in a uniform porous medium with internal heat generation such as Mohamed [10], Jawdat and Hashim [11], and Ferdousi and Alim [12]. Mohamed [10] studied the effects of first-order homogeneous chemical reaction on the unsteady magnetohydrodynamic (MHD) double-diffusive free convection fluid flow past a vertical porous plate in the presence of heat generation and soot effects. The effects of uniform internal heat generation on chaotic behavior in thermal convection in a fluid-saturated porous layer subject to gravity and heated from below for low Prandtl number was investigated by Jawdat and Hashim [11]. Then, Ferdousi and Alim [12] considered the effect of heat generation on natural convection flow from a porous vertical plate. In 2006, Veena et al. [13] have worked on heat transfer characteristics in the laminar boundary layer flow of a viscoelastic fluid over a linearly stretching continuous surface with variable wall temperature subjected to suction or blowing. Molla et al. [14] examined the natural convection flow of a viscous incompressible fluid past an isothermal horizontal circular cylinder considering the temperature dependent internal heat generation. Mahdy [15] considered the effects of chemical reaction and heat generation on double-diffusive natural convection heat and mass transfer near a vertical truncated cone in porous media. Afterward, Siddiqua et al. [16] studied natural convection flow of a viscous incompressible fluid over a semi-infinite flat plate with the effects of exponentially varying temperature dependent viscosity and the internal heat

Mohd Ariff Admon, Abdul Rahman Mohd Kasim, and Sharidan Shafie are with the Department of Mathematics, Faculty of Science, Universiti Teknologi Malaysia, 81310 UTM Johor Bahru, Johor, MALAYSIA (e-mail: abdulrahmanmohdkasim@yahoo.com, ariffadmon@yahoo.com, ridafie@yahoo.com).

generation. The flow in the neighborhood two-dimensional flow and axisymmetric stagnation point is a classical problem in fluid dynamics and has been investigated by many researchers. It was first examined by Hiemenz [17] who displayed a technique to reduce Navier-Stokes equations governing the flow to an ordinary differential equation of third order using similarity transformation (Schlichting, [18]). However, these two cases of two-dimensional and axisymmetric flows can be regarded as special cases of a general three-dimensional stagnation point flow. Several authors, such as Poots [20], Banks [21] and Sharidan et al. [22] have studied the steady free convection boundary layer flow in the region of the stagnation point of a three-dimensional body. The work of Poots [20] is particularly interesting because he was the first to derive the boundary layer equations governing the free convection flow at the lower stagnation point of a general three-dimensional body and has shown that the two-dimensional and axisymmetric flows are just two special cases from a more general point of view. Then, Banks [21] showed that other solutions exist over the whole range of stagnation points and Prandtl numbers. To our best knowledge, however, the unsteady free convection near the stagnation point on a heated regular three-dimensional body has been studied only by Ingham et al. [23] and Slaouti et al. [24]. Ingham et al. [23] considered an isothermal body surface, while Slaouti et al. [24] considered the case when there is an initial steady state that is perturbed by a step-change in the wall temperature. Besides that, Kumari and Nath [25] presented the results of electrically conducting fluid on unsteady three-dimensional laminar incompressible free convection boundary layer flow with the effect of magnetic field near the stagnation point. Following Kumari and Nath [25], Sharidan et al. [22] showed other results for the effect of a small fluctuating gravitational field characteristic of g-jitter on three-dimensional flow. Recently, by applying homotopy analytical solution (HAM), Hayat et al. [26] studied MHD flow in porous space induced by a stretching surface. Most recently, Ariff et al. [27] has presented their results for unsteady free convection flow over a three-dimensional stagnation point. They show that the transition from the initial unsteady-state flow to the final steady-state flow takes place smoothly.

Motivated by the works above, objective of the present work is to study the behavior of unsteady free convection of a viscous and incompressible fluid in the stagnation point region of a heated three-dimensional body considering the temperature dependent internal heat generation of the general form recently proposed by Mealey and Merkin [28] and Merkin [29,30]

$$q''' = \begin{cases} Q_0 (T - T_\infty)^p, & T \geq T_\infty \\ 0, & T < T_\infty \end{cases}$$

where, p is a constant. The transformed non-linear coupled partial differential equations governing the flow are solved numerically using a very efficient finite difference scheme together with Keller-box method. Attention is given to the influence of the heat generation parameter, Q Prandtl number,

Pr and the orientation on the heat transfer and flow characteristics near the stagnation point. The results for the steady-state flow are compared with those of Banks [21] and Sharidan et al. [22], and found to agree very favorably.

II. GOVERNING EQUATIONS




Fig. 1 Physical model and coordinate system.

Consider the unsteady free convection flow near the stagnation point of a heated three-dimensional body placed in a viscous and incompressible fluid of uniform temperature T_∞ . It is assumed that the uniform temperature of the body is suddenly changed from T_w to T_∞ , where $T_w > T_\infty$. A locally Cartesian orthogonal system (x, y, z) is chosen with the origin N at the nodal stagnation point as shown in Figure 1, where the x - and y -coordinates are measured along the body surface, while the z -coordinate is measured normal to the body surface. Under these assumptions, the boundary layer equations governing unsteady free convection flow are,

$$\frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} + \frac{\partial w}{\partial z} = 0 \quad (1)$$

$$\frac{\partial u}{\partial t} + u \frac{\partial u}{\partial x} + v \frac{\partial u}{\partial y} + w \frac{\partial u}{\partial z} = \nu \frac{\partial^2 u}{\partial z^2} + g \beta a x (T - T_\infty) \quad (2)$$

$$\frac{\partial v}{\partial t} + u \frac{\partial v}{\partial x} + v \frac{\partial v}{\partial y} + w \frac{\partial v}{\partial z} = \nu \frac{\partial^2 v}{\partial z^2} + g \beta b y (T - T_\infty) \quad (3)$$

$$\frac{\partial T}{\partial t} + u \frac{\partial T}{\partial x} + v \frac{\partial T}{\partial y} + w \frac{\partial T}{\partial z} = \alpha \frac{\partial^2 T}{\partial z^2} + \frac{Q_0}{\rho C_p} (T - T_\infty)^p \quad (4)$$

subject to the initial and boundary conditions

$$\begin{aligned} t < 0: & \quad u = v = w = 0, \quad T = T_\infty \quad \text{for any } x, y, z \\ t \geq 0: & \quad u = v = 0, \quad T = T_w \quad \text{on } z = 0, x \geq 0, y \geq 0 \\ & \quad u = v = 0, \quad T = T_\infty \quad \text{on } x = 0, y \geq 0, z > 0 \\ & \quad u = v = 0, \quad T = T_\infty \quad \text{on } y = 0, x \geq 0, z > 0 \\ & \quad u = v = 0, \quad T = T_\infty \quad \text{as } z \rightarrow \infty, x \geq 0, y \geq 0 \end{aligned} \quad (5)$$

Here u, v, w are the velocity components along x, y, z axes, t is the time, T is the fluid temperature, g is the magnitude of the gravity acceleration, α is the coefficient of thermal diffusivity, ν is the kinematic viscosity, β is the volumetric coefficient of thermal expansion, ρ is the fluid density, c_p is the specific heat at constant pressure and a and b are the parameters of the principal curvatures at N , of the body measured in the planes y and x , respectively.

The term $Q_0(T - T_\infty)^p$ is assumed to be amount of heat generated or absorbed per unit volume, which Q_0 may take on either positive or negative values. Further, if $Q_0 > 0$ then it represents heat generation and on the other hand when $Q_0 < 0$ it represents heat absorption.

There is no loss of generality in requiring that $|a| \geq |b|$ with $a > 0$. Clearly $b = 0$ corresponds to the plane stagnation flow case, while $b = a$ is the axisymmetric case. We assume here that a and b are positive so that solutions of the resulting equations lead to stagnation points which are nodal points of attachment, i.e. $0 \leq c \leq 1$, where $c = b/a$. However, a or b could also be negative which leads to saddle points of attachment, i.e. $-1 \leq c \leq 0$. Since most shapes of practical interest lie between cylinder ($c = 0$) and sphere ($c = 1$) we shall confine our analysis to nodal points of attachment only ($0 \leq c \leq 1$).

A little inspection shows that equations (1) to (4) along with the boundary conditions (5) admit a semi-similar solution of the form, see Shesadri *et al.* [31],

$$\begin{aligned} \eta &= Gr^{1/4} a \xi^{-1/2} z, & u &= \nu a^2 x Gr^{1/2} f'(\xi, \eta) \\ v &= \nu a^2 c y Gr^{1/2} h'(\xi, \eta), & w &= -\nu a Gr^{1/4} \xi^{1/2} (f + ch) \\ \theta(\xi, \eta) &= \frac{(T - T_\infty)}{(T_w - T_\infty)}, & \xi &= 1 - e^{-\tau}, \\ \tau &= \nu a^2 Gr^{1/2} t \end{aligned} \quad (6)$$

where $Gr = g_0 \beta (T_w - T_\infty) / (a^3 \nu^2)$ is the Grashof number and primes denote partial differentiation with respect to η . Substitution of (6) in (2) to (4) gives

$$\begin{aligned} f''' + (1 - \xi) \frac{\eta}{2} f'' + \xi [(f + ch) f'' - f'^2] \\ + \xi \theta = \xi (1 - \xi) \frac{\partial f'}{\partial \xi} \end{aligned} \quad (7)$$

$$\begin{aligned} h''' + (1 - \xi) \frac{\eta}{2} h'' + \xi [(f + ch) h'' - ch'^2] \\ + \xi \theta = \xi (1 - \xi) \frac{\partial h'}{\partial \xi} \end{aligned} \quad (8)$$

$$\begin{aligned} \frac{1}{Pr} \theta'' + (1 - \xi) \frac{\eta}{2} \theta' + \xi (f + ch) \theta' \\ + \xi Q \theta^p = \xi (1 - \xi) \frac{\partial \theta}{\partial \xi} \end{aligned} \quad (9)$$

while the boundary conditions (5) become

$$\begin{aligned} f(\xi, 0) = f'(\xi, 0) = 0, \quad h(\xi, 0) = h'(\xi, 0) = 0, \quad \theta(\xi, 0) = 1 \\ f' \rightarrow 0, \quad h' \rightarrow 0, \quad \theta \rightarrow 0 \quad \text{as } \eta \rightarrow \infty \end{aligned} \quad (10)$$

for $0 \leq \xi \leq 1$ where $Q = (T_w - T_\infty)^{p-1} Q_0 / (c_p a^2 \mu Gr^{1/2})$ is the dimensionless heat generation or absorption coefficient. Here Pr is the Prandtl number and primes denote partial differentiation with respect to η .

The physical quantities of practical interest in this problem are the skin friction coefficients in the x and y directions, C_{fx} and C_{fy} and the Nusselt number, Nu , that are defined as

$$\begin{aligned} C_{fx} &= \mu \left(\frac{\partial u}{\partial z} \right)_{z=0} / (\rho \nu^2 a^3 x), \\ C_{fy} &= \mu \left(\frac{\partial v}{\partial z} \right)_{z=0} / (\rho \nu^2 a^3 y), \\ Nu &= a^{-1} \left(\frac{\partial T}{\partial z} \right)_{z=0} / (T_w - T_\infty) \end{aligned} \quad (11)$$

where ρ and μ is the density and dynamic viscosity, respectively. In terms of the non-dimensional variables (6), we have

$$\begin{aligned} C_{fx} \xi^{1/2} / Gr^{3/4} &= f''(\xi, 0), \\ C_{fy} \xi^{1/2} / Gr^{3/4} &= h''(\tau, 0), \\ Nu \xi^{1/2} / Gr^{3/4} &= -\theta'(\tau, 0) \end{aligned} \quad (12)$$

For the unsteady-initial flow case, where $\xi = 0$, equations (7) to (9) reduce to the following form

$$f''' + \frac{\eta}{2} f'' = 0, \quad h''' + \frac{\eta}{2} h'' = 0, \quad \theta'' + Pr \frac{\eta}{2} \theta' = 0 \quad (13)$$

subject to the boundary conditions

$$\begin{aligned} f(0) = f'(0) = 0, \quad h(0) = h'(0) = 0, \quad \theta(0) = 1 \\ f'(\infty) = 0, \quad h'(\infty) = 0, \quad \theta(\infty) = 0 \end{aligned} \quad (14)$$

The solution of Eqs. (14) subject to (15) is given by

$$f = h = 0, \quad \theta(\eta) = \text{erfc}(\sqrt{Pr} \eta / 2) \quad (15)$$

where $\text{erfc}(\eta \sqrt{Pr} / 2)$ is the complementary error function. For the final steady-state flow case, where $\xi = 1$, equations (7) to (9) reduce to the following similar form

$$f''' + (f + ch) f'' - f'^2 + \theta = 0 \quad (16)$$

$$h''' + (f + ch) h'' - ch'^2 + \theta = 0 \quad (17)$$

$$\theta'' + Pr (f + ch) \theta' + Pr Q \theta^p = 0 \quad (18)$$

subject to the boundary conditions

$$f(0) = f'(0) = 0, \quad h(0) = h'(0) = 0, \quad \theta(0) = 1 \quad (19)$$

$$f'(\infty) = 0, \quad h'(\infty) = 0, \quad \theta(\infty) = 0$$

These equations are identical with those first found by Poots [20], Banks [21] and Sharidan *et al.* [22].

III. RESULT AND DISCUSSION

Equations (8) to (10) subject to boundary conditions (11) has been solved numerically using an implicit finite difference scheme, known as the Keller-box method developed by Keller [32]. This method has been found to be very suitable in dealing with nonlinear parabolic problems. Details of the method may be found in many recent publications, examples Hussain and Hossain [33], Sharidan *et al.* [34] and Cebeci and

Bradshaw [35]. Results are obtained for $p = 1$ and 2 , $Pr = 0.015$ (mercury), 0.7 and 0.72 (air), 4 (R-12 refrigerant), 7 (water at 20°C) and 100 (engine oil) and $c = 0$ (plane stagnation point), 0.25 , 0.5 , 0.75 and 1.0 (axi-symmetric stagnation point). To access the accuracy of the solutions, the present results for the reduced skin friction coefficients $f''(0)$ and $h''(0)$, and heat transfer from the surface of the body, $-\theta'(0)$ are compared with those calculated by Banks [21] and Sharidan *et al.* [22] for natural convection heat transfer from a three-dimensional body with constant wall temperature in Newtonian fluids with $\zeta = 1$, $Pr = 0.72$, $Q = 0$ and values of c between 0 and 1 , as shown in Table 1. The present results agree well with the solutions presented by Banks [21] and Sharidan *et al.* [22]

TABLE I
COMPARISON OF REDUCED SKIN FRICTIONS $f''(0)$, $h''(0)$ AND HEAT FLUX RATE $-\theta'(0)$ FOR $\varepsilon = 1$ (FINAL STEADY-STATE), $Pr = 0.72$, $Q = 0$ AND DIFFERENT VALUES OF c

c	Banks [21]		Sharidan et al. [22]		Present	
	0	1	0	1	0	1
$f''(0)$	0.856372	0.761132	0.855909	0.764685	0.856544	0.765796
$h''(0)$	0	0.760640	0	0.764685	0	0.760209
$-\theta'(0)$	0.372749	0.461187	0.374102	0.462223	0.373535	0.461082

A comparison of the present results for these quantities with those obtained by Sharidan *et al.* [22] is shown also in Figure 2. It is seen that all these results are in excellent agreement. Therefore, this favorable comparison lends confidence in the numerical results obtained in this paper







Fig. 2 Comparison of the skin friction coefficients $f''(0)$ and $h''(0)$, and heat flux from the surface of the body $\theta'(0)$ for steady flow case ($\zeta = 1$) when $Pr = 0.72$ and $Q = 0$.

The variation of the velocity $f(\zeta, \eta)$, $h(\zeta, \eta)$ and temperature $\theta(\zeta, \eta)$ profiles with η for some values of ζ are shown in Figures 4 and 5 for $Pr = 0.72$, $c = 0, 1$, and $p = 1$ and 2 . It has been seen from Figures 3 and 4 that as ζ increases, the velocity $f(\zeta, \eta)$, $h(\zeta, \eta)$ and temperature $\theta(\zeta, \eta)$ profiles increase. The changes of velocity profiles, $f(\zeta, \eta)$ and $h(\zeta, \eta)$ in the η direction reveals the typical velocity profiles for natural convection boundary layer flow, i.e., the velocity is zero at the boundary wall then the velocity increases to the peak values as η increases and finally the



velocity approaches to zero (the asymptotic value). The changes of temperature profiles, $\theta(\zeta, \eta)$ in the η direction also shows the typical temperature profile for natural convection boundary layer flow that is the value of temperature profile is one at the boundary wall then the temperature profile decreases gradually along η direction for the values of ζ from 0 to 1 to the asymptotic value. Regarding to the changes in values of p , the heat generation term θ'' can be dominant, leading to a breakdown in the solution with a thermal runaway. This happens for moderate values of p . For even larger values of p , the temperature profiles remain bounded throughout, θ'' remains small for p large and eventually the initial heat input decays away.






(a) (b)

Fig. 3 Velocity profiles $f''(\zeta, \eta)$, $h''(\zeta, \eta)$ and $\theta(\zeta, \eta)$ for various ζ with $c = 0, Q = 1, Pr = 0.72$ and (a) $p = 1$, and (b) $p = 2$.



(a) (b)

Fig. 4 Velocity profiles $f''(\zeta, \eta)$, $h''(\zeta, \eta)$ and $\theta(\zeta, \eta)$ for various ζ with $c = 1, Q = 1, Pr = 0.72$ and (a) $p = 1$, and (b) $p = 2$.



(a) (b)

IV. CONCLUSION

Unsteady natural convection flow on a three-dimensional body in the presence of heat generation near the stagnation point has been investigated in this paper for different values of relevant physical parameters including Prandtl number, Pr and heat generation parameter, Q . From the present investigation, the following conclusions may be drawn:

- The steady-state flow for the reduced skin friction and heat transfer coefficients has a similar structure to what was studied by Banks [21] and Sharidan *et al.* [22].
- There is a smooth transition from unsteady-state flow ($\zeta = 0$) to the steady-state flow ($\zeta = 1$) for all velocity and temperature profiles.

ACKNOWLEDGMENT

This work is supported by a research grant (Vot FRGS No. 78338 & 4F019) from Universiti Teknologi Malaysia, UTM.

REFERENCES

[1] Postelnicu, A., and Pop, I. Similarity solutions of free convection boundary layers over vertical and horizontal surface in porous media

- with internal heat generation, *Int. Comm. Heat Mass Transf.* 26, (1999) 1183-1191.
- [2] Foraboschi, F. P., and Federico, I. D. Heat transfer in a laminar flow of non-Newtonian heat generating fluids. *Int. J. Heat Mass Transfer* 7, (1964), 315.
- [3] Vajravelu, K., and Hadjinicolaou, A. Heat transfer in a viscous fluid over a stretching sheet with viscous dissipation and internal heat generation. *Int. Comm. Heat Mass Transfer* 20, (1993) 417-430.
- [4] Chamkha, A. J., and Camille, I. Effects of heat generation/absorption and the thermophoresis on hydromagnetic flow with heat and mass transfer over a flat plate. *Int. J. Numer. Meth. Heat Fluid Flow* 10(4), (2000) 432-438.
- [5] Mendez, F., and Trevino, C. The conjugate conduction-natural convection heat transfer along a thin vertical plate with non-uniform internal heat generation. *Int. J. Heat Mass Transfer* 43, (2000) 2739-2748.
- [6] Molla, M. M., Hossain, M. A., and Yao, L. S. Natural convection flow along a vertical wavy surface with heat generation/absorption. *Int. J. Therm. Sci.* 43, (2004) 157-163.
- [7] Mohammadein, A. A., and Gorla, R. S. R. (2001). Heat transfer in a micropolar fluid over a stretching sheet with viscous dissipation and internal heat generation. *Int. J. Numer. Meth. Heat Fluid Flow.* 11(1), 50-58.
- [8] Rahman, M. M., Eltayeb, I. A., and Rahman, S. M. M. (2009). Thermo-micropolar fluid flow along a vertical permeable plate with uniform surface heat flux in the presence of heat generation. *Therm. Sci.* 13(1), 23-36.
- [9] Magyari, E., and Chamkha, A. J. (2010). Combined effect of heat generation or absorption and first-order chemical reaction on micropolar fluid flows over a uniformly stretched permeable surface: The full analytical solution. *Int. J. Therm. Sci.* 1-8.
- [10] Mohamed, R. A. (2009). Double-diffusive convection-radiation interaction on unsteady MHD flow over a vertical moving porous plate with heat generation and sores effects. *Appl. Math. Sci.* 3(13), 629-651.
- [11] Jawdat, J. M., and Hashim, I. (2010). Low Prandtl number chaotic convection in porous media with uniform internal heat generation. *Int. Comm. Heat Mass Transfer.* 37, 629-636.
- [12] Ferdousi, A., and Alim, M. A. (2010). Natural convection flow from a porous vertical plate in the presence of heat generation. *D. Int. Uni. J. Sci. Tech.* 5(1), 73-80.
- [13] Veena, P. H., Abel, S., rajagopal, K., and Pravin, V. K. (2006). Heat transfer in a visco-elastic fluid past a stretching sheet with viscous dissipation and internal heat generation. *Z. Angew. Math. Phys.* 57, 447-463.
- [14] Molla, M. M., Paul, S. C., and Hossain, M. A. (2009). Natural convection flow from a horizontal circular cylinder with uniform heat flux in presence of heat generation. *Appl. Math. Modelling.* 33, 3226-3236.
- [15] Mahdy, A. (2010). Effect of chemical reaction and heat generation or absorption on double-diffusive convection from a vertical truncated cone in porous media with variable viscosity. *Int. Comm. Heat Mass Transfer.* 37, 548-554.
- [16] Siddiq, S., Asghar, S., and Hossain, M. A. (2010). Natural convection flow over an inclined flat plate with internal heat generation and variable viscosity. *Math. Comp. Modelling.* 52, 1739-1751.
- [17] Hiemenz, K. (1911), Die Grenzschicht an einem in den gleichformigen Flussigkeitsstrom eingetauchten geraden Kreiszyylinder. *Dinglers Polym. J.*, Vol. 326, pp. 321-410.
- [18] Schlichting, H. *Boundary layer theory.* McGraw-Hill Book Co. (1986).
- [19] Bhattacharyya, S., Gupta, A.S. (1998). MHD flow and heat transfer at a general three-dimensional stagnation point. *Int. J. Non-Linear Mech.* 33, 125.
- [20] Poots, G. (1964). Laminar free convection on the lower stagnation point on an isothermal curved surface. *Int. J. Heat Mass Transfer* 7, 863.
- [21] Banks, W.H.H. (1974). Laminar free convection flow at a stagnation point of attachment on an isothermal surfaces. *J. Engng. Math.* 8, 45.
- [22] Sharidan, S., Amin, N., and Pop, I. (2007). G-Jitter free convection flow in the stagnation point of a three-dimensional body. *Mech. Res. Comm.* 34, 115-122.
- [23] Ingham, D.B., Merkin, J.H., Pop, I. (1984). Unsteady free convection of a stagnation point of attachment on an isothermal surface. *Int. J. Math. Math. Phys.* 7, 599.
- [24] Slaouti A, Takhar HS and Nath G. (1998). Unsteady free convection flow in the stagnation-point region of a three-dimensional body. *International Journal Heat and Mass Transfer* 41, 3397.
- [25] Kumari, M., and Nath, G. (1986). Unsteady free convection MHD boundary layer flow near a three-dimensional stagnation point. *Indian. J. Pure Appl. Math.* 17(7), 957-968.
- [26] Hayat, T., Qasim, M., and Abbas, Z. (2010). Homotopy solution for the unsteady three-dimensional MHD flow and mass transfer in a porous space. *Comm. Nonlinear Sci. Numer. Simulat.* 15, 2375-2387.
- [27] M.A. Admon, S. Shafie and I. Pop (2011). Unsteady Free Convection Flow near the Stagnation Point of a Three-dimensional Body, *Journal of Applied Sciences* (Accepted)
- [28] Mealey, L., and Merkin, J.H. (2008). Free convection boundary layers on a vertical surface in a heat generating porous medium. *IMA J. Appl. Math.* 73, 231.
- [29] Merkin, J.H. (2009). Natural convective boundary-layer flow in a heat generating porous medium with a prescribed wall heat flux. *J. Appl. Math. Phys. (ZAMP)* 60, 543.
- [30] Merkin, J.H. (2010). Free convection boundary layers on a vertical surface in a heat generating porous medium: Similarity solutions. *Quart. J. Mech. Applied Math.* (online).
- [31] Seshadri, R., Sreeshylan, N., Nath, G., 2002. Unsteady mixed convection flow in the stagnation region of a heated vertical plate due to impulsively motion. *Int. J. Heat Mass Transfer.* 45, 1345.
- [32] Keller H. B. A new difference scheme for parabolic problems, in numerical solutions of partial differential equations (B.Hubbard, ed). New York, Academic Press. 2: 327-350, 1971.
- [33] Hussain, S. and Hossain, M.A. Natural convection flow from a vertical permeable flat plate with variable surface temperature and species concentration. *Engineering Computations* 2000; 17, 7: 789 – 812.
- [34] Sharidan, S, Amin, N and Pop, I. g-jitter induced free convection near a two-dimensional stagnation point in micropolar fluids. *International Journal of Applied Mechanics and Engineering.* Vol. 10, No. 3, 311-328, 2005.
- [35] Cebeci, T., Bradshaw, P., 1984. *Physical and Computational Aspects of Convective Heat Transfer.* Springer, New York.