

# Alphanumeric Hand-Prints Classification: Similarity Analysis between Local Decisions

G. Dimauro, S. Impedovo, M.G. Lucchese, R. Modugno, G. Pirlo

**Abstract**-This paper presents the analysis of similarity between local decisions, in the process of alphanumeric hand-prints classification. From the analysis of local characteristics of hand-printed numerals and characters, extracted by a zoning method, the set of classification decisions is obtained and the similarity among them is investigated. For this purpose the Similarity Index is used, which is an estimator of similarity between classifiers, based on the analysis of agreements between their decisions. The experimental tests, carried out using numerals and characters from the CEDAR and ETL database, respectively, show to what extent different parts of the patterns provide similar classification decisions.

**Keywords** - Handwriting Recognition, Optical Character Recognition, Similarity Index, Zoning.

## I. INTRODUCTION

Classification by parts has rightly been considered as one of the most effective strategies for alphanumeric hand-prints classification [1]. In fact, local information is decisive to overcome difficulties due to different writing styles and changeable writing conditions [2].


So far, many systems have been proposed which perform hand-printed digit classification by combining local decisions obtained from the analysis of different parts of the pattern. In this case, the degree of similarity among the local decisions is very important since it is well known that the higher the similarity degree of local decisions the more effective the process of decision combination can be [3,4].

This paper presents the analysis of similarity between local classification decisions, in a process of isolated hand-printed digit recognition. Local classification decisions are obtained from the information extracted by a zoning method: the pattern image is split into sub-images, named zones, each one providing information about a specific part of the pattern [3]. The degree of similarity between local decisions is measured by the *Similarity Index*, which is an estimator of similarity between classifiers, based on the analysis of their agreements [5]. This paper is organized as follows: Section 2 presents the zoning technique for local classification. Section 3 describes the *Similarity Index*, used to estimate the degree of similarity between classifiers. Section 4 shows the experimental results, which have been carried out on hand-printed numerals and characters, extracted from the CEDAR and ETL database, respectively.

*Manuscript received Novembre 18, 2004. This paper has been supported by the Italian Ministry "Ministero dell'Istruzione, dell'Università e della Ricerca", MIUR. G.Dimauro, S.Impedovo, M.G.Lucchese and G. Pirlo are with the Università degli Studi di Bari - Dipartimento di Informatica, Via Orabona 4 - 70126 Bari - Italy R.Modugno is with the Università degli Studi di Bari- Centro Rete Puglia, Via G.Petroni 15/F.1 - 70100 Bari - Italy.*

## II. LOCAL CLASSIFICATION DECISIONS BY ZONING

Zoning is a diffuse strategy for local analysis of patterns. So far, several zoning methods have been designed by superimposing a  $r \times s$  regular grid on the pattern image, creating the zones  $z_1, z_2, \dots, z_1, \dots, z_M, M = r \cdot s$  [6,7,8]. Figure 1 shows the zoning  $Z^{3 \times 3}$  and  $Z^{5 \times 5}$ , which have been successfully used for the classification of handwritten numerals and characters, respectively.



(a)  $Z^{3 \times 3}$  (b)  $Z^{5 \times 5}$   
Figure 1. Standard Zonings

Let  $C = \{C_1, C_2, \dots, C_k, \dots, C_K\}$  be the set of pattern classes and  $F = \{f_1, f_2, \dots, f_i, \dots, f_L\}$  the feature set. When zoning  $Z = \{z_1, z_2, \dots, z_j, \dots, z_M\}$  is used, for each zone  $z_j, j=1, 2, \dots, M$ , the function  $\Omega^{C_k}(f_i, z_j)$  can be defined, which denotes the probability that  $f_i$  is detected in  $z_j$ , for patterns belonging to the class  $C_k$ .  $\Omega^{C_k}(f_i, z_j)$  can be estimated by using the set of training patterns  $P = \{p_1, p_2, \dots, p_N\}$ :

$$\Omega^{C_k}(f_i, z_j) = \frac{\Gamma^{C_k}(f_i, z_j)}{\sum_{k=1}^K \Gamma^{C_k}(f_i, z_j)} \quad \text{if } \sum_{k=1}^K \Gamma^{C_k}(f_i, z_j) > 0; \quad (1a)$$

$$\Omega^{C_k}(f_i, z_j) = 0, \quad \text{otherwise.} \quad (1b)$$

where

$$\Gamma^{C_k}(f_i, z_j) = \frac{N_{C_k}(f_i, z_j)}{N_{C_k}} \quad (2)$$

and

- $N_{C_k}(f_i, z_j) = \text{card} \{p_t \in P \mid p_t \in C_k \text{ and } p_t \text{ contains } f_i \text{ in zone } z_j\}$
- $N_{C_k} = \text{card} \{p_t \in P \mid p_t \in C_k\}$ .

Now, let  $p'_t$  be a test pattern described by the set

$$S(p'_t) = \{(f_{i_q}, z_{t_q}) \mid q=1, 2, \dots, Q\} \quad (3)$$

where  $(f_{i_q}, z_{t_q})$  means that  $f_{i_q}$  has been detected in the zone  $z_{t_q}$  of  $p'_t$ . A local classification decision is obtained for each zone  $z_j, j=1, 2, \dots, M$ . Let

$$D_{z_j}^{C_k}(p'_t) = \sum_{(f_i, z_j) \in S(p'_t)} \Omega^{C_k}(f_i, z_j) \quad k=1, 2, \dots, K, \quad (4)$$

the pattern  $p'_t$  is assigned to the class  $C_m$  for which it results:

$$\diamond z_j(p'_t) = C_m \text{ iff } D_{z_j}^{C_m}(p'_t) = \max_k D_{z_j}^{C_k}(p'_t) \quad (5)$$

$$\text{and } D_{z_j}^{C_m}(p'_t) - D_{z_j}^{C_m}(p'_t) > 0$$

$$(where D_{z_j}^{C_m}(p_t) = \max_k \{D_{z_j}^{C_k}(p_t) \mid k=1, \dots, K, k \neq m\});$$

❖  $z_j(p_t) = \text{Reject}$  otherwise.

III. THE SIMILARITY INDEX

The *Similarity Index*, which is an estimator of similarity among *abstract-level* classifiers [5], is here used to measure the degree of similarity between local decisions obtained from specific pattern zones.

Let  $Z = \{z_1, z_2, \dots, z_j, \dots, z_M\}$  a zoning method and  $P = \{p_t \mid t=1, 2, \dots, N\}$  a set of patterns. Let  $z_i(p_t)$  be the classification decision (class label) for the input pattern  $p_t$ , obtained from  $z_i$  by eq.(5) (we also assume that  $z_i(p_t) = \text{Rej}$  means that  $z_i$  rejects  $p_t$ ). The *Similarity Index*  $\rho_{\{z_i, z_j\}}$  between  $z_1$  and  $z_2$  can be defined as:

$$\rho_{\{z_i, z_j\}} = \frac{1}{C(P_{ij})} \sum_{P_t \in P_{ij}} Q(z_i(p_t), z_j(p_t)) \quad (6)$$

where  $P_{ij} = \{p_t \in P \mid z_i(p_t) \neq \text{Rej}, z_j(p_t) \neq \text{Rej}\}, C(P_{ij}) = \text{Card}(P_{ij})$  and

$$Q(z_i(p_t), z_j(p_t)) = \begin{cases} 1 & \text{if } z_i(p_t) = z_j(p_t) \\ 0 & \text{otherwise} \end{cases} \quad (7)$$

	$p_1 \in '3'$	$p_2 \in '6'$	$p_3 \in '7'$	$p_4 \in '2'$	$p_5 \in '0'$	$p_6 \in '1'$	$p_7 \in '9'$	$p_8 \in '8'$	$p_9 \in '5'$	$p_{10} \in '0'$
$z_i$	3	6	7	2	0	1	9	9	5	0
$z_j$	3	6	1	2	0	1	0	9	5	8

Figure 2. Local decisions from the zones  $z_1, z_2$

In the example of Figure 2, the local decisions obtained from the zones  $z_i$  and  $z_j$  are reported, when ten patterns  $p_1, p_2, \dots, p_{10}$  are considered. Correct decisions are reported in white cells, wrong decisions in grey cells. In this case  $z_i$  provides correct decisions 9 times out of 10, whereas  $z_j$  provides correct decisions 6 times out of 10. Decisions from  $z_i$  and  $z_j$  are the same 7 times out of 10, thus the *Similarity Index* is equal to  $\rho_{\{z_i, z_j\}} = 0.7$ .

In general, for the zoning  $Z = \{z_1, z_2, \dots, z_j, \dots, z_M\}$ , the *Similarity Index*  $\rho_Z$  is defined as [5]:

$$\rho_Z = \frac{\sum_{\substack{i, j=1, \dots, M \\ i < j}} \rho_{\{z_i, z_j\}}}{\binom{M}{2}} \quad (8)$$

In the example of Figure 3, the local decisions obtained from the four zones of  $Z = \{z_1, z_2, z_3, z_4\}$  are reported, when ten patterns  $p_1, p_2, \dots, p_{10}$  are considered. Figure 4 reports the

matrix of *Similarity Index* values for each pair of zones. Of course, since  $\rho_{\{z_i, z_j\}} = \rho_{\{z_j, z_i\}} \forall i, j$ , only the values  $\rho_{\{z_i, z_j\}}, i \leq j$ , are reported. The *Similarity Index* for  $Z = \{z_1, z_2, z_3, z_4\}$  is equal to  $\rho_Z = 0.783$ .

	$p_1 \in '2'$	$p_2 \in '5'$	$p_3 \in '5'$	$p_4 \in '8'$	$p_5 \in '1'$	$p_6 \in '0'$	$p_7 \in '4'$	$p_8 \in '9'$	$p_9 \in '0'$	$p_{10} \in '3'$
$z_1$	2	5	7	8	1	0	4	8	0	3
$z_2$	2	5	7	9	1	0	4	8	0	3
$z_3$	3	5	5	8	1	0	4	8	0	3
$z_4$	2	5	5	8	1	8	4	8	0	3

Figure 3. Local decisions from the zones  $z_1, z_2, z_3, z_4$

	$z_1$	$z_2$	$z_3$	$z_4$
$z_1$	100%	90%	80%	80%
$z_2$		100%	70%	70%
$z_3$			100%	80%
$z_4$				100%

Figure 4. Degree of Similarity between local decisions

Of course, the *Similarity Index* ranges in the interval from 0 to 1 (i.e.  $\rho_Z \in [0, 1]$ ):

- $\rho_Z$  close to 0 means that local decisions are weakly similar;
- $\rho_Z$  close to 1 means that local decisions are strongly similar.

IV. EXPERIMENTALS RESULTS

The experimental tests have been carried out on numerals ( $C^N = \{0, 1, 2, \dots, 9\}$ ) of the CEDAR database (18467 learning patterns, 2189 test patterns) [9] and characters ( $C^C = \{A, B, C, \dots, Z\}$ ) of the ETL database (29570 learning patterns, 7800 test patterns) [10]. For the analysis of the numerals the zoning  $Z^{3 \times 3}$  of Figure 1a has been considered, whereas the zoning  $Z^{5 \times 5}$  of Figure 1b has been used for the analysis of characters. Furthermore, two feature sets,  $F_1$  and  $F_2$ , have been extracted from the normalized pattern images (72x54 pixel image). The set  $F_1 = \{f_1, \dots, f_9\}$  consists of hole, cavity and endpoint features [3,11]. The feature set  $F_2 = \{f_1, \dots, f_{37}\}$  consists of features extracted from contour profiles, intersections, extrema-points, cross points [3,11]

**4.1 Experiments by  $C^N$  and  $F_1$ .** Figure 5 shows the degree of similarity between the local decisions from the different zones of the patterns images, when the set of numeral digits  $C^N$  is recognized by the features of the set  $F_1$ . Four levels of similarity are considered: *Strongly Similar* ( $\rho_Z \in ]0.75, 1]$ ), *Similar* ( $\rho_Z \in ]0.50, 0.75]$ ), *Weakly Similar* ( $\rho_Z \in ]0.25, 0.50]$ ) and *Not Similar* ( $\rho_Z \in [0, 0.25]$ ). In general, the local decisions provided by the different zones are similar. Strongly similar decisions are only provided by the zones  $z_1$  and  $z_4$ .

	Z1	Z2	Z3	Z4	Z5	Z6	Z7	Z8	Z9
Z1	100%	63.2%	41.4%	77.5%	50.2%	69.2%	44.4%	59.4%	64.4%
Z2		100%	29.2%	68.3%	44.9%	64.0%	40.6%	54.4%	57.1%
Z3			100%	45.1%	20.4%	43.5%	33.9%	37.0%	40.1%
Z4				100%	55.6%	71.9%	46.2%	61.8%	63.4%
Z5					100%	47.7%	25.1%	38.9%	40.2%
Z6						100%	41.0%	58.7%	63.1%
Z7							100%	35.2%	35.2%
Z8								100%	61.8%
Z9									100%

Strongly Similar
  Similar
  Weakly Similar
  Not Similar

Figure 5. Class Set  $C^N$  – Feature Set  $F_1$  : Analysis of Similarity between local decisions

	Z1	Z2	Z3	Z4	Z5	Z6	Z7	Z8	Z9
Z1	100%	11.8%	29.5%	6.4%	13.0%	12.7%	0.3%	8.2%	14.2%
Z2		100%	12.8%	13.2%	19.7%	24.2%	6.4%	21.7%	7.5%
Z3			100%	5.2%	24.6%	11.1%	24.1%	2.7%	1.5%
Z4				100%	13.1%	27.0%	14.4%	24.1%	17.2%
Z5					100%	11.8%	18.6%	12.2%	5.0%
Z6						100%	12.6%	40.6%	32.7%
Z7							100%	19.5%	21.0%
Z8								100%	37.8%
Z9									100%

Strongly Similar
  Similar
  Weakly Similar
  Not Similar

Figure 6. Class Set  $C^N$  – Feature Set  $F_2$  : Analysis of Similarity between local decisions

Conversely, several zones provide weakly similar decisions. For instance, decisions from zone  $z_7$  are weakly similar to decisions from any other zone. Decisions from  $z_3$  are weakly similar to decisions from  $z_1, z_2, z_5, z_6, z_7, z_8, z_9$ , whereas no significant similarity is measured between decisions from  $z_3$  and  $z_4$ . The overall similarity between decision from the different zones is (eq. (8)) 49.83%.

**4.2 Experiments by  $C^N$  and  $F_2$ .** Figure 6 shows the degree of similarity between the local decisions from the different zones of the patterns images, when the set of numeral digits  $C^N$  is recognized by the features of the set  $F_2$ . In this case the local decisions are generally not similar. Weakly similar decisions are provided by  $z_1$  and  $z_3, z_4$  and  $z_6, z_6$  and  $z_8, z_6$  and  $z_9, z_8$  and  $z_9$ . The overall similarity between decisions from the different zones is equal to (see eq. (8)) 16.07%.

**4.3 Experiments by  $C^C$  and  $F_1$ .** Figure 7 the degree of similarity between the local decisions from the different zones of the patterns images, when the set of characters  $C^C$  is recognized by the features of the set  $F_1$ . In this case the local decisions are generally strongly similar. Similar decisions are generally provided by decisions from zones  $z_{13}, z_{21}$  and  $z_{25}$ , with respect to decisions from other zones. The overall similarity between decision from the different zones is equal to (eq. (8)) 80.40%.

**4.4 Experiments by  $C^C$  and  $F_2$ .** Figure 8 shows the degree of similarity between the local decisions from the different

zones of the patterns, when the set of characters  $C^C$  is recognized by the features of  $F_2$ . The local decisions are generally not similar. Weakly similar decisions are provided by the zones in the central part of the character ( $z_7, z_8, z_9, z_{12}, z_{13}, z_{14}, z_{17}, z_{18}, z_{19}$ ). The overall similarity between decision from the different zones is equal to (eq.(8)) 18,81%.

V. CONCLUSION

This paper presents the analysis of similarity between local decisions obtained from different regions of hand-written numerals and characters. Two different zoning methods and feature sets have been considered for the experimental tests. The result show the effectiveness of the proposed analysis in estimating to what extent different pattern regions convey similar information.

REFERENCES

- [1] C.Y. Suen, J. Guo, Z.C. Li , " Analysis and Recognition of Alphanumeric Handprints by parts", IEEE T-SMC, 1994, Vol. 24(4), pp. 614-630.
- [2] S. Mori, C.Y. Suen, K. Yamamoto, "Historical Review of OCR research and development", Proc. IEEE, 1992, Vol. 80, pp. 1029-1058.
- [3] O.D. Trier, A.K. Jain, T.Taxt, "Feature Extraction Methods For Character Recognition – A survey", *Pattern Recognition* , 1996, Vol 29(4), pp. 641-662.
- [4] C.Y. Suen, C. Nadal, R. Legault, T.A.Mai, L. Lam, "Computer Recognition of unconstrained handwritten numerals", Proc. IEEE, 1992, Vol 80, pp. 1162-1180.
- [5] G.Dimauro, S.Impedovo, G.Pirlo, "Multiple Experts:A New Methodology for the Evaluation of the Combination Processes", IWFHR-5, Colchester,Uk,1996,pp.131-136.
- [6] G. Baptista, K.M. Kulkarni, "A high accuracy algorithm for recognition of hand-written numerals", *Pattern Recognition* , 1988, Vol. 4, pp. 287-291.

[7] M. Bokser, Omnidocument Technologies, Proc. IEEE, 1992, Vol. 80, pp. 1066-1078.  
 [8] F. Kimura, M. Shridar, "Handwritten Numerical Recognition Based on Multiple Algorithms", *Pattern Recognition*, 1991, Vol. 24 (10), pp. 969-983.  
 [9] <http://www.cedar.buffalo.edu/Databases/>

[10] <http://axiongw.ee.ucc.ac.jp/japanese/link/resources/database/ETLCDB.html>  
 [11] Heutte L., Paquet T., Moreau J. V., Lecourtier Y., Olivier C. A structural / Statistical Features Based Vector for Handwritten Character Recognition. *Pattern Recognition Letters* 1998, 9:629-641.

	Z1	Z2	Z3	Z4	Z5	Z6	Z7	Z8	Z9	Z10	Z11	Z12	Z13	Z14	Z15	Z16	Z17	Z18	Z19	Z20	Z21	Z22	Z23	Z24	Z25
Z1	100%	94.2%	91.7%	94.1%	89.9%	91.3%	85.3%	85.0%	89.3%	95.5%	91.1%	87.9%	69.3%	80.7%	96.0%	92.1%	92.7%	84.9%	89.1%	93.3%	70.1%	83.1%	6.6%	85.8%	73.7%
Z2		100%	90.0%	92.3%	88.0%	89.5%	83.5%	83.2%	87.5%	93.6%	89.6%	86.0%	67.4%	88.7%	94.1%	90.4%	90.7%	83.1%	87.2%	92.2%	68.7%	81.2%	85.2%	84.3%	72.1%
Z3			100%	89.5%	85.0%	87.7%	81.4%	80.4%	84.7%	90.8%	89.3%	83.3%	64.6%	86.0%	91.4%	90.0%	88.1%	80.4%	84.7%	90.1%	65.2%	79.8%	83.8%	82.0%	69.4%
Z4				100%	87.4%	89.2%	83.6%	82.9%	87.6%	93.3%	88.8%	85.7%	67.2%	88.6%	93.8%	90.1%	90.5%	82.9%	87.4%	92.0%	68.5%	80.8%	85.3%	84.2%	71.8%
Z5					100%	85.5%	80.2%	78.7%	83.0%	92.1%	84.6%	82.0%	63.3%	84.6%	91.7%	85.7%	86.2%	78.5%	82.7%	86.6%	67.8%	77.5%	80.3%	79.6%	67.7%
Z6						100%	80.6%	80.2%	84.8%	90.8%	86.8%	83.4%	64.9%	85.9%	91.4%	87.4%	89.4%	80.9%	84.5%	89.2%	67.4%	78.1%	82.3%	81.6%	69.9%
Z7							100%	75.9%	80.0%	85.5%	80.3%	78.2%	60.2%	80.1%	85.5%	81.5%	82.1%	74.9%	79.0%	83.1%	71.2%	72.2%	76.2%	76.0%	65.6%
Z8								100%	78.7%	84.4%	80.1%	79.0%	62.0%	80.3%	84.8%	80.9%	81.9%	76.6%	79.4%	83.0%	62.1%	71.9%	76.1%	75.8%	66.1%
Z9									100%	88.7%	84.1%	81.6%	65.7%	84.5%	89.2%	85.2%	86.0%	79.6%	83.6%	86.4%	64.7%	75.6%	79.7%	79.4%	72.6%
Z10										100%	90.1%	87.4%	68.7%	89.9%	95.2%	91.2%	91.9%	84.2%	88.6%	92.4%	70.4%	81.5%	85.6%	85.0%	73.0%
Z11											100%	83.1%	65.2%	85.5%	90.6%	87.3%	88.2%	81.0%	84.0%	87.8%	65.9%	78.2%	82.2%	81.6%	69.9%
Z12												100%	64.1%	82.8%	87.9%	84.0%	85.0%	79.3%	82.0%	84.9%	65.0%	74.7%	78.7%	79.3%	68.9%
Z13													100%	65.6%	69.4%	65.5%	66.8%	61.4%	65.1%	67.1%	47.5%	56.9%	61.2%	62.9%	58.6%
Z14														100%	90.5%	86.6%	87.3%	80.3%	84.3%	87.7%	64.6%	77.2%	81.1%	81.0%	69.5%
Z15															100%	91.8%	92.4%	84.7%	88.9%	92.8%	70.3%	82.0%	86.1%	85.7%	73.5%
Z16																100%	89.0%	81.4%	85.5%	89.0%	66.2%	79.5%	82.9%	82.7%	70.8%
Z17																	100%	82.4%	86.9%	89.8%	67.0%	79.6%	83.5%	84.1%	70.7%
Z18																		100%	80.7%	82.9%	60.2%	71.9%	76.3%	77.6%	66.0%
Z19																			100%	86.5%	64.1%	76.3%	80.8%	81.6%	68.6%
Z20																				100%	66.9%	80.2%	85.2%	84.4%	71.4%
Z21																					100%	56.3%	60.4%	60.6%	53.2%
Z22																						100%	72.7%	73.3%	60.2%
Z23																							100%	77.0%	65.1%
Z24																								100%	64.2%
Z25																									100%

Strongly Similar   Similar   Weakly Similar   Not Similar

Figure 7. Class Set C<sup>C</sup> – Feature Set F<sub>1</sub> : Analysis of Similarity between local decisions

	Z1	Z2	Z3	Z4	Z5	Z6	Z7	Z8	Z9	Z10	Z11	Z12	Z13	Z14	Z15	Z16	Z17	Z18	Z19	Z20	Z21	Z22	Z23	Z24	Z25
Z1	100%	15.5%	17.8%	12.7%	12.0%	10.7%	20.9%	29.6%	21.4%	7.0%	7.3%	17.3%	17.2%	13.1%	11.8%	4.1%	20.7%	24.1%	17.8%	12.1%	0.3%	12.7%	15.6%	12.8%	13.1%
Z2		100%	26.7%	23.0%	7.4%	12.2%	21.1%	17.0%	17.7%	11.1%	9.1%	13.5%	17.2%	14.4%	15.6%	8.4%	16.0%	15.7%	17.8%	12.6%	2.0%	19.5%	18.5%	16.5%	11.4%
Z3			100%	34.6%	5.1%	9.3%	22.4%	23.7%	15.8%	9.1%	10.9%	20.4%	17.1%	16.9%	19.5%	9.1%	21.6%	21.1%	21.0%	17.6%	0.7%	16.7%	23.5%	24.0%	12.1%
Z4				100%	12.9%	7.2%	20.9%	20.6%	20.7%	6.6%	8.8%	21.8%	20.2%	23.6%	17.9%	11.1%	21.8%	21.0%	23.6%	16.7%	4.6%	13.5%	20.2%	19.3%	15.1%
Z5					100%	3.7%	6.4%	10.1%	9.4%	3.8%	1.2%	3.2%	6.3%	6.0%	4.1%	7.0%	5.2%	7.9%	8.9%	2.6%	4.5%	7.2%	6.3%	6.8%	3.7%
Z6						100%	20.1%	9.0%	10.0%	19.9%	29.3%	17.9%	11.0%	15.1%	23.1%	20.6%	17.7%	13.8%	20.6%	18.4%	2.8%	13.8%	13.5%	19.0%	13.3%
Z7							100%	43.6%	38.4%	21.5%	18.3%	35.6%	35.0%	30.1%	31.5%	15.2%	40.6%	39.4%	38.3%	34.1%	1.0%	14.8%	23.8%	27.2%	25.1%
Z8								100%	41.7%	16.2%	10.8%	35.5%	31.6%	24.5%	23.2%	8.5%	36.6%	40.0%	33.1%	25.3%	5.4%	11.6%	16.2%	20.3%	23.7%
Z9									100%	18.0%	9.3%	30.1%	34.1%	29.0%	19.4%	10.8%	40.6%	39.8%	37.8%	24.9%	1.2%	13.0%	17.8%	20.5%	25.3%
Z10										100%	19.3%	22.0%	18.8%	20.1%	35.9%	16.2%	20.3%	18.1%	24.5%	27.9%	2.7%	12.2%	10.0%	14.4%	12.4%
Z11											100%	20.9%	10.9%	16.1%	25.9%	25.6%	14.7%	10.8%	19.3%	19.9%	2.2%	9.1%	10.6%	17.3%	15.3%
Z12												100%	40.1%	36.3%	32.5%	18.1%	37.5%	32.8%	34.8%	26.7%	7.8%	11.1%	12.1%	20.9%	26.6%
Z13													100%	34.4%	25.8%	10.4%	37.0%	34.8%	31.2%	22.3%	0.6%	9.0%	10.9%	16.1%	21.4%
Z14														100%	30.2%	14.2%	33.1%	30.3%	35.9%	22.3%	7.7%	9.2%	14.8%	18.5%	18.5%
Z15															100%	20.6%	29.1%	23.3%	33.2%	46.1%	8.1%	18.2%	20.1%	27.4%	24.0%
Z16																100%	14.3%	10.4%	18.6%	21.0%	10.1%	8.8%	12.0%	15.9%	19.7%
Z17																	100%	52.5%	45.2%	30.3%	2.6%	19.0%	26.3%	28.3%	26.1%
Z18																		100%	47.2%	24.0%	2.5%	14.5%	24.6%	24.5%	22.4%
Z19																			100%	32.4%	2.5%	17.8%	25.3%	29.5%	23.5%
Z20																				100%	5.3%	19.2%	26.5%	30.6%	33.1%
Z21																					100%	2.5%	3.6%	2.7%	13.8%
Z22																						100%	33.3%	23.4%	14.0%
Z23																							100%	40.5%	19.9%
Z24																								100%	29.8%
Z25																									100%

Strongly Similar   Similar   Weakly Similar   Not Similar

Figure 8. Class Set C<sup>C</sup> – Feature Set F<sub>2</sub> : Analysis of Similarity between local decisions