Application of Stochastic Models to Annual Extreme Streamflow Data

Karim Hamidi Machekposhti, Hossein Sedghi

Abstract-This study was designed to find the best stochastic model (using of time series analysis) for annual extreme streamflow (peak and maximum streamflow) of Karkheh River at Iran. The Auto-regressive Integrated Moving Average (ARIMA) model used to simulate these series and forecast those in future. For the analysis, annual extreme streamflow data of Jelogir Majin station (above of Karkheh dam reservoir) for the years 1958-2005 were used. A visual inspection of the time plot gives a little increasing trend; therefore, series is not stationary. The stationarity observed in Auto-Correlation Function (ACF) and Partial Auto-Correlation Function (PACF) plots of annual extreme streamflow was removed using first order differencing (d=1) in order to the development of the ARIMA model. Interestingly, the ARIMA(4,1,1) model developed was found to be most suitable for simulating annual extreme streamflow for Karkheh River. The model was found to be appropriate to forecast ten years of annual extreme streamflow and assist decision makers to establish priorities for water demand. The Statistical Analysis System (SAS) and Statistical Package for the Social Sciences (SPSS) codes were used to determinate of the best model for this series.

Keywords—Stochastic models, ARIMA, extreme streamflow, Karkheh River.

I. INTRODUCTION

CCURATE simulation and forecasting of water $A_{availability}$ is a key step in efficient planning, operation, and management of water resources. Developing reliable surface water flow forecasting methods for real time operational becomes water resources management important. Various approaches, increasingly including physical and mathematical models, have been used for this purpose. The problems water resources in a region can check by stochastic hydrologic methods, thus this method is very important for hydrologists. The most important model of this method are time series models (ARMA or ARIMA models) that these models were developed extensively since the 1960s and were used by many researchers in the world. Time series analysis [1] has been widely used in the field of hydrology and water resources for simulation and forecasting [3].

Time series analysis is effective instrumentations for selecting a model that demonstrates the past behavior of historical data. With this analysis and select the best model, we are able to predict future events such as rainfall. Many studies in this subject have specified that stochastic time series models are very useful and effective to predict. References [1], [15], [17] have developed around ARIMA models and their extensions. Shakeel et al. applied time series to modelling of annual maximum flow in River Indus at Sukkur India. They found that ARIMA (2,1,1) model was appropriate for this series [11]. Srikanthan et al. used time series models to analyse annual flow of Australian streams. ACF and PACF were applied to determine the appropriate form of Box-Jenkins time series models [12].

Stojković et al. studied stochastic structure of annual discharges of large European rivers. They suggested that the stochastic flows simulated by the model can be used for hydrological simulations in river basins [13]. Huang et al. analyzed annual maximum stage readings of three rivers in Langat River basin in Malaysia for forecasting of flood using stochastic model (ARIMA). They found that ARIMA(1,1,0), ARIMA(1,1,0) and ARIMA(1,1,1) are the best models for the Dengkil, Kg. Lui and Kg. Rinching series respectively [4]. Tian et al. studied extreme value analysis of stream flow time series in Poyang Lake Basin, China [14]. During the last decades, several studies have developed methods of analyzing stochastic characteristics of streamflow time series [2], [5]-[10], [16], [18].

In this study, linear stochastic models known as nonseasonal ARIMA models were used to model annual extreme streamflow for Karkheh River at Iran. The study area is located on latitudes 31^0 48' and 34^0 58' N and longitudes 46^0 57' and 49^0 10' E with its elevation ranging 1216 meter. The Kakheh River is formed of two main branches of Saymareh and Kashkan rivers and is one of the rivers the in southwestern of Iran, which flows in the southern of Khuzestan provinces. With 900 kilometres in length, it is known as the third long river in Iran. In this study, extreme streamflow data for the Karkheh River at Jelogir Majin gauging station (upstream of Karkheh dam) were obtained from the Iran Water Resources Management Organization (IWRMO), covering the period 1958–2015. It includes a length of 58 years observations. Fig. 1 showed Karkheh River basin.

II. METHODS

A stationary time series data which have constant mean and variance, can be modelled in different ways and process: Auto Regressive (AR), Moving Average (MA), or Auto Regressive and Moving Average (ARMA). When the data are stationary, we can use ARMA model but if data are not stationary, we need to use differencing on data series. These models are called ARIMA models.

Karim Hamidi Machekposhti is the Ph.D in Water Sciences and Engineering Department, Science and Research Branch, Islamic Azad University, Tehran, Iran (phone: 00989197704935- fax: 00982144865179-82; e-mail: karim.hamidi@srbiau.ac.ir).

Hossein Sedghi is with Water Sciences and Engineering Department, Science and Research Branch, Islamic Azad University, Tehran, Iran (e-mail: h.sedghi1320@gmail.com).



Fig. 1 The Karkheh River Basin

The general model of the non-seasonal ARIMA family is classified by three parameters p,d,q where p and q are degree (order) of AR and MA in model. The letter "d" is on dth difference of the time series. The amounts of p,d,q can be zero or positive in a general non-seasonal ARIMA model.

$$(B)\nabla^d X_t = (B)_t \tag{1}$$

where (B) and $\theta(B)$ = Polynomials of order p and q, respectively.

$$\boldsymbol{\phi} (B) = 1 - \boldsymbol{\phi}_1 B - \boldsymbol{\phi}_2 B^2 - \cdots \boldsymbol{\phi}_P B^p \tag{2}$$

and

$$(B) = 1 - \theta_1 B - \theta_2 B^2 - \cdots + \theta_q B^q \tag{3}$$

Four basic stages of ARIMA in identifying patterns in time series data and forecasting are model identification, parameter estimation, diagnostic checking and forecasting.

A. Model Identification Stage

In this stage, the number of auto-regressive (p) and moving average (q) parameters necessary to yield an effective model of the process is decided. The data are examined to check for the most appropriate class of ARIMA processes through selecting the order of the regular and nonseasonal differencing required to make the series stationary, as well as through specifying the number of regular and auto-regressive and moving average parameters necessary to adequately represent the time series model. The plots of the series with correlograms of ACF and PACF are the major tools for the identification phase. Correlograms are plot of auto correlation and partial auto correlation verses lag. In a time series, amount of linear dependence between data can be expressed by plotting of ACF and determinate of auto regressive term for manifest of trend, either in the average level or in the variance level of the series, by plotting of PACF.

B. Parameter Estimation Stage

At the parameter estimation stage, the parameters are estimated using by the Maximum Likelihood (ML), Conditional Least Square (CLS) and ULS methods. Among these methods, ML seems to be the best [1]. The parameters should be statistically significant at α =p% and should satisfy two conditions, namely stationary and invertibility for autoregressive and moving average models, respectively. In this stage, several models are tentatively chosen and then compute the values of Akaike Information Criterion (AIC). The model structure which has the minimum AIC value, among others model structures, will be chosen as the best model. Equation (4) describes the formula to compute AIC. In this equation, Tp is the number of AR, I and MA parameters.

$$AIC = -2Ln (Max . Likelihood) + \frac{2T_p}{n - T_p - 1}$$
(4)

C. Diagnostic Check Stage

After different models have been fitted to the data, it is important to perform diagnostic checks to test the adequacy of each model. First test is to check the residuals by using ACF and PACF graph. If the selected model is appropriate, the residuals graphs of both correlation functions should be white noise, indicating no remaining correlation.

The second test is Port Manteau lack of fit test (5). If the values of p-value in this test exceed 5%, it indicates that residuals have significant departure from white noise. If the selected model fails to pass Port Manteau lack of fit test, the modeler returns to select alternative model and follows the same procedure until satisfactory model results are obtained.

$$Q = (N - d - DS) \sum_{k=1}^{M} r_k^2 a_k$$
(5)

In (5), r_k (a_t) is the auto-correlation coefficient of the residual (a_t) at lag k, and M is the maximum lag considered (about N/4), ARIMA model is considered adequate if p>chi square is greater than 0.05 where 0.05 is the level of significant.

D. Forecasting Stage

At the forecasting stage, the estimated parameters are used to calculate new values of the time series and assurance periods for forecasted values. The estimation process is applied on transformed (differenced) data, hence before prediction and production of data series the series needs to be integrated to thwart the effect of differencing so that the predicts are expressed in values suitable with the input data. The letter "I" in ARIMA model represents this automatic integration feature. To evaluate the performance of the best ARIMA model at each station, coefficient of determination (R^2) is used to select the best model. R^2 gives impartial result as it takes mean values of both the observed and predicted data.

In the present study, to identify the best fitted model, the predicted values using the several different ARIMA models are compared to the observed data of the validation period (2006-2015). The SAS and SPSS codes were used for all the analytical work. The basic methodology of ARIMA modelling is shown in Fig. 2:



Fig. 2 ARIMA model development

III. RESULT AND DISCUSSION

A. Fitting Box-Jenkins



Fig. 3 Time series of annual peak streamflow of Karkheh River (1958-2005) in (m^3/s)

The time series model development consists of three stages: identification, estimation and diagnostic, see [9]. In the identification stage, data transformation is often needed to make the time series stationary. During the estimation stage, the model parameters are calculated by different method. Finally, diagnostic check test of the model is performed to reveal possible model inadequacies to assist in the best model selection.

B. Identification of Representative Models

Model computation was made with extreme streamflow annual data from between 1958 to 2015. The dataset from 2006 to 2015 was considered in forecasting estimations of the model. The time series plot was conducted using the annual extreme streamflow data for Karkheh River at Jelogir Majin gauge station to assess the stability of the data, and Figs. 3 and 4 were obtained. The plots show that there is a little increasing of the series, and the series are nonstationary. Also, from the plot of the ACF and PACF of the annual data, Figs. 5 and 6, it has been found that the data must be differenced by one nonseasonal degree of differencing to achieve stationary (d=0). Differencing for nonseasonal ARIMA was not done due to absence of trends in the datasets. Figs. 7 and 8 confirm that the ACF and PACF plots for the differenced data (d=1) were stable, and the ARIMA model (p,1,q) could be identified for further analysis.



Fig. 4 Time series of annual maximum streamflow of Karkheh River (1958–2005) in (m³/s)



Fig. 5 ACF and PACF Plots of natural annual peak streamflow of Karkheh River (d=0)



Fig. 6 ACF and PACF Plots of natural annual maximum streamflow of Karkheh River (d=0)



Fig. 7 ACF and PACF Plots of annual peak streamflow after one nonseasonal difference (d=1)



Fig. 8 ACF and PACF Plots of annual maximum streamflow after one nonseasonal difference (d=1)

C. Parameters Estimation

After the identification of model using the parameter estimation methods such as ML, CLS and ULS are done. The values of parameters estimation are shown in Tables I and II. The values of these tables showed that all the selected models are suitable for entrance to next stage because these selected models have two conditional stationary and invertibility. The AIC values are shown in Table V. The model that gives the minimum AIC is selected as best fit model. Obviously, model ARIMA(4,1,1) has the smallest values of AIC, then one would temporarily have a model ARIMA (4,1,1). The values of AIC for different ARIMA models are shown in Table V (AIC=88.87 in CLS estimation method for annual peak streamflow and AIC=77.75 in ML estimation method for annual maximum streamflow). In this case, the initial suggested model structure has the minimum AIC value and has been chosen as best model structure for annual extreme

streamflow time series.

D. Diagnostic Check

In the Box Jenkins methodology, after selecting suitable model and estimated of parameters, the residuals of the model must requires examining to verify that selected model is an appropriate one for the series. An appropriate model should have uncorrelated residuals. This is the minimal condition for select of the best model. For a good predicting model, the residuals of the model must satisfy the requirements of a white noise process. Two common tests for this purpose are summarized briefly in the following paragraphs.

E. Port Manteau Lack of Fit Test

The goodness of fit of the selected model was tested using the Ljung-Box statistic test. The test is employed for checking independence of residual. From Tables III and IV, the goodness of fit values for the auto-correlations of residuals

from the model up to lag 24 was ≥ 0.05 . The result of Port Manteau test demonstrates the acceptation of the null hypothesis of model sufficiency at the 5% significance level and the set of autocorrelation of residuals was considered white noise. Since the model diagnostic tests show that all the parameter estimates are significant, and the residual series is white noise, the estimation and diagnostic checking stages of the modelling process are complete.

F. ACF and PACF of Residuals

The ACF and PACF of residuals of the model ARIMA (4,1,1) are shown in Figs. 9 and 10. Most of the values of the RACF and RPACF of residuals of the model lies within confidence, and figures do not indicate significant correlation between the residuals of model. The results of the ACF and PACF plots of the residuals and Port Manteau lack of fit test suggested that the residuals are white noise, therefore the ARIMA (4,1,1) model is the best model for forecasting of study series

G. Forecasting

ARIMA model can also be used for forecasting future values based on the historical data. The ARIMA (4,1,1) model was tested for its validity to forecast ten observations obtained for the years 2006-2015 for Karkheh River. The result of comparison between forecasted and observation data is shown Figs. 11 and 12. The observed streamflow was found to be closely aligned to the forecasted values. In order to evaluate the performance of the models, ten years ahead forecasts were generated for the testing period from 2006 to 2015 in Table VI. The hydrograph between observation and forecasted streamflow data using ARIMA models is shown in Figs. 11 and 12. These corresponding observed values are also shown in Figs. 13 and 14. The agreement between the observed and forecasted values is very good (R²=0.84 for annual peak streamflow and R²=0.87 for annual maximum streamflow), it is confirmed that the ARIMA (4,1,1) model is adequate. Also, this model is better than other models because ARIMA model gives low value of error and in good fit with the observed data.

TABLE I Values of Nonsfasonal Arima Model Parameters for Annual Peak Streamflow						
Estimation Method	Type (Order) and Values of parameters ARIMA(p,1,q)	Absolute Value of t	Probability of t	Stationary Condition	Invertibility Condition	
ML	P(1) = -0.48656	-3.81	0.0001	Satisfy		
CLS	P(1) = -0.48713 Q(0)	-3.78	0.0005	Satisfy		
ULS	P(1) = -0.49708 Q(0)	-3.88	0.0003	Satisfy		
ML	P(1) = 0.10744 Q(1) = 0.93539	0.66 10.87	0.5104 0.0001<	Satisfy	Satisfy	
CLS	P(1) = 0.11274 Q(1) = 0.96723	0.69 15.99	0.4926 0.0001<	Satisfy	Satisfy	
ULS	P(1) = 0.12820 O(1) = 0.99998	0.84 3.35	0.4072 0.0001<	Satisfy	Not Satisfy	
ML	P(4) = -0.3317 O(1) = 0.86679	-2.25 9.89	0.0243 0.0001<	Satisfy	Satisfy	
CLS	P(4) = -0.33489 O(1) = 0.86679	-2.19 13.48	0.0339 0.0001<	Satisfy	Satisfy	
ULS	P(4) = -0.36065 Q(1) = 0.89524	-2.4 11.84	0.0208	Satisfy	Satisfy	

TABLE II

VALUES OF NONSEASONAL ARIMA MODEL PARAMETERS FOR ANNUAL MAXIMUM STREAMFLOW					
Estimation	Type (Order) and Values of	Absolute	Probability	Stationary	Invertibility
Method	parameters ARIMA(p,1,q)	Value of t	of t	Condition	Condition
ML	P(1) = -0.51759	-4.14	0.0001<	Satisfy	
	Q(0)				
	P(1) = -0.49304	-3.84	0.0004	Satisfy	
0L0	Q(0)				
ULS	P(1) = -0.52951	-4.23	0.0001	Satisfy	
	Q(0)				
ML	P(1) = 0.14873	0.86	0.3922	Satisfy	
	Q(1) = 0.92809	8.16	0.0001<		Satisfy
CLS	P(1) = 0.230274	1.46	0.1501	Satisfy	
	Q(1) = 0.97512	28.55	0.0001<		Satisfy
ULS	P(1) = 0.17543	1.13	0.2631	Satisfy	
	Q(1) = 0.999999	3.35	0.0016		Not Satisfy
ML	P(4) = -0.26820	-1.71	0.087	Satisfy	
	Q(1) = 0.74897	6.36	0.0001<		Satisfy
CLS	P(4) = -0.26824	-1.7	0.0964	Satisfy	
	Q(1) = 0.69253	5.76	0.0001<		Satisfy
ULS	P(4) = -0.27556	-1.66	0.1031	Satisfy	
	Q(1) = 0.85681	8.77	0.0001<		Satisfy







Fig. 10 ACF and PACF Plots for ARIMA (4,1,1) Residuals for annual maximum streamflow

ADIMA Madal	Estimation	Talas	Df	Chi-	Pr>Chi	Adequacy for
ARIMA Model	Method	To Lag	DI	Square	Square	Modelling
		6	5	9.99	0.0754	
	MI	12	11	11.25	0.4228	Satisfy
	ML	18	17	14.32	0.6447	Satisty
		24	23	17.26	0.7962	
		6	5	9.68	0.0850	
ADD(A(1,1,0))	CIS	12	11	10.94	0.4484	C-4:-6-
AKINIA(1,1,0)	CLS	18	17	14.02	0.6659	Satisty
		24	23	16.93	0.8128	
		6	5	10.02	0.0748	Satisfy
	IIIC	12	11	11.29	0.4190	
	ULS	18	17	14.38	0.6400	
		24	23	17.33	0.7928	
		6	4	5.32	0.2562	Satisfy
	М	12	10	5.93	0.8212	
	ML	18	16	9.21	0.9046	
		24	22	12.45	0.9473	
ARIMA(1,1,1)		6	4	4.63	0.3269	
	CT C	12	10	5.20	0.8775	Satisfy Satisfy
	CLS	18	16	8.26	0.9409	
		24	22	10.89	0.9763	
		6	4	1.30	0.8608	
	ML	12	10	2.77	0.9863	
		18	16	7.46	0.9653	
		24	22	10.70	0.9787	
	1) CLS ULS	6	4	1.36	0.8504	Satisfy
		12	10	2.98	0.9818	
ARIMA(4,1,1)		18	16	7.56	0.9610	
		24	22	10.41	0.9822	
		6	4	1.25	0.8702	
		12	10	2.53	0.9904	Satisfy
		18	16	7.61	0.9596	
		24	22	11 47	0 9674	







Fig. 12 Comparison of observed data and ARIMA (4,1,1) model annual maximum streamflow (2006-2015)



Fig. 13 Correlation between observation and forecasted values of annual peak streamflow





TABLE IV						
RESULT OF AUTOCORRELATION CHECK OF RESIDUALS ANNUAL MAXIMUM STREAMFLOW						
	Estimation Method	TE T	Df	Chi-	Pr>Chi	Adequacy for
ARIMA Model		To Lag	Di	Square	Square	Modelling
		6	5	9.63	0.0866	U
	М	12	11	10.85	0.4559	G
	ML	18	17	14.10	0.6602	Satisfy
		24	23	21.24	0.5665	
		6	5	8.87	0.1145	
ADIMA(1,1,0)	CLC	12	11	10.14	0.5177	C-4:-C-
ARIMA(1,1,0)	CLS	18	17	13.26	0.7185	Sausty
		24	23	20.50	0.6118	
		6	5	9.65	0.0856	
	IIIC	12	11	10.89	0.4525	C-4:-C-
	ULS	18	17	14.21	0.6519	Sausty
		24	23	21.26	0.5653	
		6	4	3.85	0.4262	
	М	12	10	5.64	0.8445	C-4:-C-
	ML	18	16	10.50	0.8391	Sausty
ADIMA(1 1 1)		24	22	17.76	0.7201	
ARIMA(1,1,1)		6	4	4.15	0.3856	
	CIS	12	10	5.74	0.8365	Satisfy
	CLS	18	16	10.06	0.8637	Sausty
		24	22	16.58	0.7861	
		6	4	1.22	0.8752	
	МІ	12	10	5.29	0.8712 Satia	Satisfy
	IVIL	18	16	10.91	0.8152	Sausty
		24	22	15.22	0.8527	
		6	4	0.97	0.9139	
ADIMA(4 1 1)	(4,1,1) CLS	12	10	6.01	0.8144	Satisfy
AKIMA(4,1,1)		18	16	11.58	0.7726	Sausty
		24	22	15.57	0.8364	
		6	4	2.15	0.7077	
	IIIS	12	10	6.91	0.7338	Satisfy
	ULS	18	16	13.12	0.6638	Sausty
		24	22	17.33	0.7449	

IV. CONCLUSION

In this paper, stochastic model known as nonseasonal ARIMA was used to simulate and forecast annual extreme streamflow for Karkheh River at Iran. ARIMA model has the best fits of the criteria and the requirement. By analyzing of the predicted values in future, it was found that use of ARIMA model for predicting annual extreme streamflow is very good. The stochastic ARIMA models to annual streamflow time series could result in a better tool which can be used for water resource planning in studied region. ARIMA model has the ability to predict accurately the future annual extreme streamflow, especially short-term period, for all streamflow gauge stations in Karkhe River in Karkheh basin at Iran. The choice of model type itself has an important role in stochastic hydrology for forecasting and data generation, and each case

deserves an investigation to determine the most appropriate model.

The significant ACF and PACF plots with high order in ARIMA (4,1,1) model (four order) can be caused by factors such as the good vegetation of the region and snowmelt. The good vegetation of the region and the forest causes water retention in the soil surface layer and delay in the rise in surface runoff. As well as vegetation reduces the power and erodibility destroyed by a severe storm (intense rain events happening across the region). Also, runoff from the storm drainage system seems to cause significant delays. The ARIMA model is suitable for short term forecasting because the ARMA family models can model short term persistence very well. The auto regressive model is a finite memory model, thus it does not fare well in long term forecasting. GOODNESS OF FIT STATISTIC FOR ANNUAL PEAK AND MAXIMUM STREAMFLOW ARIMA Estimation Akaikc's Parameter Model Method Statistic ML. 103.4247 (1,1,0)CLS 103.4469 ULS 103.4316 Annual ML 95.2824 Peak (1,1,1)CLS 93.1350 Streamflow ML 90.8381 (4,1,1) CLS 88.8680 ULS 91.0387 ML 84.185 84.9952 (1,1,0)CLS ULS 84.1939 Annual ML 79.7781 Maximum (1,1,1)CLS 79.6182 Streamflow ML 77.7478 78.8943 (4,1,1) CLS ULS 78.1438

TABLE V

TABLE VI

FORECASTS AND OBSERVATIONS OF ANNUAL STREAMFLOW FROM PERIOD 2006-7 TO 2015-16

Period	Annual Pea	ak Streamflow	Annual Maximum Streamflow		
	Forecast	Observation	Forecast	Observation	
2006-7	1451	1300	1235	1161	
2007-8	1385	1323	1177	1163	
2008-9	1092	1175	962	941	
2009-10	984	1004	920	960	
2010-11	1257	1253	1092	1070	
2011-12	1276	1187	1106	1090	
2012-13	1382	1346	1167	1202	
2013-14	1431	1401	1182	1210	
2014-15	1319	1330	1129	1150	
2015-16	1312	1290	1099	1080	

References

- [1] Box, G. E. P.; Jenkins, G. M. "Time Series Analysis: Forecasting and Control", Holden Day, San Francisco, California, 1976.
- [2] Can, I., Selim, S. "Stochastic modelling of mean monthly flows of Karasu River, in Turkey", Water and Environment Journal, 2009.
- [3] Hipel, K. W., McLeod, A. I. "Time series modeling of water resources and environmental systems", Amsterdam, Elsevier, 1994.
- [4] Huang, Y. F., Mirzaei M., Yap W. K. "Flood Analysis in Langat River Basin using Stochastic Model", *International Journal of GEOMATE*, 2016, 11(27): 2796-2803.
- [5] Modarres, R. "Streamflow Drought Time Series Forecasting", Stoch Environ Res Risk Assess, 2007, 21: 223–233.
- [6] Mohamed, T. M., Etuk, E. H. "Application of Linear Stochastic Models to Monthly Streamflow Data", *Journal of Scientific and Engineering Research*, 2017, 4(4):322-326.
- [7] Musa, J. J. "Stochastic Modelling of Shiroro River Stream flow Process", American Journal of Engineering Research (AJER), 2013, 2(6): 49-54.
- [8] Nigam, R., Nigam, S., Mittal, S.K. "The river runoff forecast based on the modeling of time series," *Russian Meteorology and Hydrology*, 2014, 39(11), 750-761.
- [9] O'Connel, P. E. "ARIMA model in synthetic hydrology: Mathematical model for surface hydrology", John Wiley, NY, USA, 1977.
- [10] Pisarenko, V. F., Lyubushin, A. A., Bolgov, M. V., Rukavishnikova, T. A., Kanyu, S., Kanevskii, M. F., Savel'eva, E. A., Dem'yanov, V. V., & Zalyapin, I. V. "Statistical methods for river runoff Prediction", *Water Resources*, 2005, 32(2): 115–126.

- [11] Shakeel, A.M.; Idrees, A.M.; Naeem, H.M.; Sarwar, B.M. "Time Series Modelling of Annual Maximum Flow of River Indus at Sukkur," *Pakistan. Journal of Agricultural Sciences*, 1993, 30(1), 36-38.
- [12] Srikanthan, R.; McMohan, T.A., Irish, J.L. "Time series analysis of annual flows of Australian streams", J. Hydrology, 1983.
- [13] Stojković, M.; Prohaska, S.; Plavšić, J. "Stochastic structure of annual discharges of large European rivers", J. Hydrology and Hydromechanics, 2015, 63(1), 63–70.
- [14] Tian, P., Zhao, G. J, Li, J., Tian, K. "Extreme Value Analysis of Stream flow Time Series in Poyang Lake Basin, China", *Water Science and Engineering*, 2011, 4(2): 121-132.
- [15] Thomas, H. A., Fiering, M. B. "Mathematic synthesis of streamflow sequences for analysis of river basins by simulation, in Design of Water Resources Systems", edited by A. Mass, pp. 459 – 493, Harvard Univ. Press, Cambridge, Mass. 1962.
- [16] Vijayakumar, N., Vennila, S. A. "comparative analysis of forecasting reservoir inflow using ARMA model and Holt winters exponential smoothening technique", *International Jour. of Innovation in Science* and Mathematics, 2016, 4(2): 85-90.
- [17] Yevjevich, V. "Stochastic Processes in Hydrology", Water Resour. Publ., Highlands Ranch, Colo. 1972.
- [18] Yurekli, K., Kurunc, K., Ozturk, F. "Application of linear Stochastic models to monthly flow data of Kelkit Stream", *Ecological Modeling*, 2005, 183: 67–75.