# Rayleigh-Bénard-Taylor Convection of Newtonian Nanoliquid

P. G. Siddheshwar, T. N. Sakshath

Abstract—In the paper we make linear and non-linear stability analyses of Rayleigh-Bénard convection of a Newtonian nanoliquid in a rotating medium (called as Rayleigh-Bénard-Taylor convection). Rigid-rigid isothermal boundaries are considered for investigation. Khanafer-Vafai-Lightstone single phase model is used for studying instabilities in nanoliquids. Various thermophysical properties of nanoliquid are obtained using phenomenological laws and mixture theory. The eigen boundary value problem is solved for the Rayleigh number using an analytical method by considering trigonometric eigen functions. We observe that the critical nanoliquid Rayleigh number is less than that of the base liquid. Thus the onset of convection is advanced due to the addition of nanoparticles. So, increase in volume fraction leads to advanced onset and thereby increase in heat transport. The amplitudes of convective modes required for estimating the heat transport are determined analytically. The tri-modal standard Lorenz model is derived for the steady state assuming small scale convective motions. The effect of rotation on the onset of convection and on heat transport is investigated and depicted graphically. It is observed that the onset of convection is delayed due to rotation and hence leads to decrease in heat transport. Hence, rotation has a stabilizing effect on the system. This is due to the fact that the energy of the system is used to create the component V. We observe that the amount of heat transport is less in the case of rigid-rigid isothermal boundaries compared to free-free isothermal boundaries.

Keywords—Nanoliquid, rigid-rigid, rotation, single-phase.

## NOMENCLATURE

# Latin symbols

specific heat at constant pressure

acceleration due to gravity (0,0,-g)

distance between the plates

thermal conductivity

pressure

velocity vector (u, 0, w)

dimensional temperature

temperature of the upper plate(reference temperature)

dimensional horizontal velocity component

dimensional vertical velocity component

non-dimensional horizontal velocity component

non-dimensional vertical velocity component

dimensional horizontal coordinate dimensional vertical coordinate

non-dimensional horizontal coordinate non-dimensional vertical coordinate

P. G. Siddheshwar and T. N. Sakshath are with the Department of Mathematics, Bangalore University, Bangalore 560056, Karnataka, India (e-mail: mathdrpgs@gmail.com, sakshath.tn@gmail.com).

#### Greek symbols

thermal diffusivity

thermal expansion coefficient β

volume fraction

temperature difference

dynamic viscosity

Laplacian operator  $(\frac{\partial^2}{\partial x^2} + \frac{\partial^2}{\partial z^2})$  $\nabla^2$ 

stream function

non-dimensional stream function

density

non-dimensional temperature

#### Subscripts

basic state

base liquid

nanoliquid

nanoparticle

critical

## I. Introduction

THE effect of rotation is shown to have a significant impact on the flow in porous media. The effect of Coriolis force on the onset of convection and extent to which it delays the onset of convection was examined by Chandrasekhar [8]. Experimental study that includes the stability of Rayleigh-Bénard convection over a wide range of Taylor numbers was conducted by Rossby [17]. Liu and Ecke [13] presented the experimental studies of turbulent thermal convection in water confined in a cell with a square cross section with and without rotation Some of the recent developments in bifurcation theory and their relevance to the study of rotating convection was summarized by Knobloch [12]. Thermal instablities of a fluid contained in rotating system are investigated by Busse [6]. Agarwal et al. [1] studied the thermal instability in a rotating anisotropic porous layer saturated by a nanofluid while the thermal instability in a rotating horizontal porous layer considering the effect of Brownian motion and thermophoresis was discussed by Bhadauria and Agarwal [3]. Galdi and Straughan [10] applied the nonlinear energy stability theory to study the stabilizing effect of rotation. Vadasz [20] carried out an analytical investigation of the Coriolis effect on three dimensional gravity-driven convection in a rotating porous layer using linear and weakly non linear stability theories. Beaume et al. [2] computed the non-linear solutions of the equations describing two-dimensional convection in a rotating horizontal layer with constant angular velocity. The stability of a rotating doubly diffusive fluid was studied by Pearlstein [15]. The influence of various parameters on convection in the presence of rotation, for both high and low rotation rates was discussed

by Vanishree and Siddheshwar [21]. The effect of modulation of the rotation speed on the Rayleigh-Bénard instability was investigated by Bhattacharjee [4]. Cox and Matthews [9] described new instabilities arising in three related convection problems namely rotating convection, magnetoconvection and rotating magnetoconvection. Riahi [16] discussed the nonlinear convection in a porous medium and rotation about vertical axis. The preferred cellular pattern depending upon the rotation rate was reported by Veronis [22]. Tagare et al. [19], Yadav et al. [23] studied the effect of Coriolis force on gravity-driven convection for idealised stress-free boundary conditions. The influence of centrifugal force on a rotating convection system was examined by Lopez and Marques [14].

#### A. Mathematical Formulation

The schematic of the flow configuration is as shown in Fig. 1. The coordinate system is taken at the lower boundary with the z-axis taken vertically upwards and the x-axis along the plates. The system is rotated about the z-axis with uniform angular velocity  $\hat{\Omega}$ .




Fig. 1 Schematic representation of Rayleigh-Bénard-Taylor convection of Newtonian nanoliquid

The governing describing Rayleigh-Bénard-Taylor convection are:

$$\nabla . \overrightarrow{q} = 0, \tag{1}$$

$$\rho_{nl}(\overrightarrow{q}.\nabla)\overrightarrow{q} = -\nabla p + \mu_{nl}\nabla^2 \overrightarrow{q} + \rho_{nl}\overrightarrow{g} + 2\rho_{nl}(\overrightarrow{q}\times\overrightarrow{\Omega}), (2)$$

$$\alpha_{nl}\nabla^2 T = (\overrightarrow{q}.\nabla)T,\tag{3}$$

$$\rho_{nl}(T) = \rho_{nl}(T_0) - (\rho\beta)_{nl}(T - T_0), \tag{4}$$

where the nanoliquid properties are obtained from either phenomenological laws or mixture theory as given below: a) Phenomenological laws

$$\frac{\mu_{nl}}{\mu_l} = \frac{1}{(1-\gamma)^{2.5}} (Brinkman model [5]), \tag{5}$$

$$\frac{k_{nl}}{k_l} = \frac{\left(\frac{k_{np}}{k_l} + 2\right) - 2\chi \left(1 - \frac{k_{np}}{k_l}\right)}{\left(\frac{k_{np}}{k_l} + 2\right) + \chi \left(1 - \frac{k_{np}}{k_l}\right)}$$
(Hamilton-Crosser model [11]).

b) Mixture theory

$$\alpha_{nl} = \frac{k_{nl}}{(\rho C_p)_{nl}},$$

$$\frac{\rho_{nl}}{\rho_l} = (1 - \chi) + \chi \frac{\rho_{np}}{\rho_l},$$

$$\frac{(\rho C_p)_{nl}}{(\rho C_p)_l} = (1 - \chi) + \chi \frac{(\rho C_p)_{np}}{(\rho C_p)_l},$$

$$\frac{(\rho \beta)_{nl}}{(\rho \beta)_l} = (1 - \chi) + \chi \frac{(\rho \beta)_{np}}{(\rho \beta)_l},$$

$$(7)$$

1) Basic State Solution: We assume boundary conditions on  $\overrightarrow{q}$  and T to be:

$$\overrightarrow{q} = 0$$
,  $T = T_0 + \Delta T$  at  $z = -\frac{h}{2}$ .  
 $\overrightarrow{q} = 0$ ,  $T = T_0$  at  $z = \frac{h}{2}$ .

Taking the velocity, temperature, density and pressure in the quiescent basic state as follows:

$$\overrightarrow{q} = \overrightarrow{q}_b = (0,0) 
p(z) = p_b(z) 
\rho(z) = \rho_b(z) 
T(z) = T_b(z)$$
(8)

we obtain the quiescent state solution for the temperature in

$$T_b(z) = T_0 + \Delta T \left(\frac{1}{2} - \frac{z}{h}\right). \tag{9}$$

We now superimpose perturbations on the quiescent basic state and so we write:

$$\overrightarrow{q} = \overrightarrow{q}_{b} + \overrightarrow{q}'$$

$$p = p_{b} + p'$$

$$\rho = \rho_{b} + \rho'$$

$$T = T_{b} + T'$$
(10)

where the primes indicate a perturbed quantity. Now eliminating the pressure p between the x- and y-components of (2), introducing the stream function  $\psi(x,z)$  in the form

$$u = \frac{\partial \psi}{\partial z}$$
 and  $w = -\frac{\partial \psi}{\partial x}$ 

and incorporating the quiescent state solution and non dimensionalizing the resulting equations as well as (3) using the following definition

$$(X,Z) = \left(\frac{z}{h}, \frac{z}{h}\right), \ \Psi = \frac{\psi}{\alpha_l}, \ \Theta = \frac{T}{\Delta T}, \ V = \frac{vh}{\alpha_l},$$

$$U = \frac{uh}{c}, W = \frac{wh}{c}$$

 $U=\frac{uh}{\alpha_l}, W=\frac{wh}{\alpha_l},$  we obtain the dimensionless form of governing equations as:

$$a_1 \nabla^4 \Psi - a_1^2 R a_{nl} \frac{\partial \Theta}{\partial X} + a_1 \sqrt{T a} \frac{\partial V}{\partial Z} + \frac{1}{P r_{nl}} \frac{\partial (\Psi, \nabla^2 \Psi)}{\partial (X, Z)} = 0,$$
(11)

$$-\frac{\partial \Psi}{\partial X} + a_1 \nabla^2 \Theta + \frac{\partial (\Psi, \Theta)}{\partial (X, Z)} = 0, \tag{12}$$

$$\nabla^2 V - \sqrt{Ta} \frac{\partial \Psi}{\partial Z} + \frac{1}{Pr_{nl}} \frac{\partial (\Psi, V)}{\partial (X, Z)} = 0, \tag{13}$$

where V is the velocity in the y direction which vary along x and z directions,

$$a_1 = \frac{\alpha}{\alpha_1} \text{(thermal diffusivity ratio)},$$

$$Ra_{nl} = \frac{(\rho\beta)_{nl}h^3g\Delta T}{\mu_{nl} \alpha_{nl}} \text{(nanoliquid Rayleigh number)},$$

$$Ta = \left(\frac{2\rho_{nl}\Omega h^2}{\phi\mu_{nl}}\right)^2 \text{(modified Taylor number)},$$

$$Pr_{nl} = \frac{\mu_{nl}}{\rho_{nl}\alpha_{nl}} \text{(nanoliquid Prandtl number)}.$$

In the next section, we make a linear stability analysis and study the onset of convection.

#### B. Linear Stability Analysis

The boundary conditions suitable for rigid-rigid isothermal boundaries are:

$$\Psi = \frac{\partial \Psi}{\partial Z} = \Theta = V = 0 \text{ at } Z = \pm \frac{1}{2}.$$
 (14)

The normal mode solution for solving eigen boundary value problem is:

$$\Psi = A \sin(\nu X) (C_f)_e(Z),$$

$$\Theta = B \cos(\nu X) \sin[\pi(Z + \frac{1}{2})],$$

$$V = C \sin(\nu X) z \sin[\pi(Z + \frac{1}{2})],$$
(15)

where A, B and C are the amplitudes,  $\nu$  is the wave number and  $(C_f)_e(Z)$  is the Chandrasekhar function (even solution) [7] and  $\mu_1$ =4.73004074 is the eigen value satisfying the following equation,

$$tanh\left(\frac{\mu_1}{2}\right) + tan\left(\frac{\mu_1}{2}\right) = 0. \tag{16}$$

Substituting (15) in the dimensionless form of the governing equations (11)-(13) and following the standard orthogonalization procedure, we obtain the expression of the critical value of nanoliquid Rayleigh number for stationary onset as:

$$Ra_{nlc} = \frac{\delta_c^2 \left( F_1 \left( \nu_c^4 + \mu_1^4 \right) + 2F_2 \nu_c^2 \mu_1^2 \right)}{2F_3^2 \nu_c^2} + \frac{12\pi^4 F_4^2 \ \delta_c^2 \ Ta}{F_3^2 \nu_c^2 \left( -6\nu_c^2 + \pi^2 \left( \nu_c^2 + 6 \right) + \pi^4 \right)}$$
(17)

where

$$\delta_c^2 = \nu_c^2 + \pi^2$$

$$F_{1} = \frac{1}{1 + \cos(\mu_{1})} - \frac{\tan\left(\frac{\mu_{1}}{2}\right)}{\mu_{1}} + \frac{1}{1 + \cosh(\mu_{1})} - \frac{\tanh\left(\frac{\mu_{1}}{2}\right)}{\mu_{1}},$$
(18)

$$F_{2} = \frac{1}{1 + \cos(\mu_{1})} + \frac{\tan\left(\frac{\mu_{1}}{2}\right)}{\mu_{1}} - \frac{1}{1 + \cosh(\mu_{1})} - \frac{\tanh\left(\frac{\mu_{1}}{2}\right)}{\mu_{1}}, \tag{19}$$

$$F_3 = \frac{4\pi\mu_1^2}{\pi^4 - \mu_1^4},\tag{20}$$

$$F_{4} = \frac{8(\mu_{1}^{4} + \pi^{4})\mu_{1}^{2}}{(\pi^{4} - \mu_{1}^{4})^{2}} + \mu_{1}^{3} \left(\frac{\tan\left(\frac{\mu_{1}}{2}\right)}{(\pi^{2} - \mu_{1}^{2})^{2}} - \frac{\tanh\left(\frac{\mu_{1}}{2}\right)}{(\mu_{1}^{2} + \pi^{2})^{2}}\right)$$
$$- \pi^{2}\mu_{1} \left(\frac{\tan\left(\frac{\mu_{1}}{2}\right)}{(\pi^{2} - \mu_{1}^{2})^{2}} + \frac{\tanh\left(\frac{\mu_{1}}{2}\right)}{(\mu_{1}^{2} + \pi^{2})^{2}}\right). \tag{21}$$

The non-linear analysis will now be used to study the enhancement of heat transport.

## C. Weakly Non-Linear Stability Analysis

The truncated representation for making a weakly non-linear analysis for rigid-rigid, isothermal boundaries is

$$\Psi = A \sin(\nu_c X) (C_f)_e(Z),$$

$$\Theta = B \cos(\nu_c X) \sin[\pi(Z + \frac{1}{2})] + C \sin[2\pi(Z + \frac{1}{2})],$$

$$V = D \sin(\nu_c X) z \sin[\pi(Z + \frac{1}{2})]$$
(22)

Substituting (22) into (11)-(13) and using the orthogonality condition with the eigen functions on the resulting equations, we get the following algebraic equations:

$$2a_{1}\nu_{c}\left[F_{1}\left(\nu_{c}^{3} + \frac{\mu_{1}^{4}}{\nu_{c}}\right) + 2F_{2}\nu_{c}\mu_{1}^{2}\right]A - 2a_{1}^{2}F_{3}\nu_{c}Ra_{nl}B + 2\pi a_{1}F_{4}\sqrt{Ta}D = 0,$$
(23)

$$A\frac{(F_5C + 2F_3)\nu_c}{a_1\delta_c^2} - B = 0, (24)$$

$$AB + \frac{8a_1\pi^2}{F_5\nu_c}C = 0, (25)$$

$$2\pi F_4 \sqrt{Ta} A - \frac{\left[-6\nu_c^2 + \pi^2 (6 + \delta_c^2)\right]}{12\pi^2} D = 0.$$
 (26)

where  $F_1, F_2, F_3, F_4$  are given by (18)-(21) and

$$F_5 = \frac{16\pi^2 \mu_1^2 \left(\mu_1^4 + 39\pi^4\right)}{\mu_1^8 - 82\pi^4 \mu_1^4 + 81\pi^8}.$$
 (27)

Solving (23)-(26), we get

$$A^{2} = \frac{8\pi^{2}\delta_{c}^{2}a_{1}^{2}r}{\nu_{c}^{2}F_{5}^{2}}\left[1 - \frac{1}{r}\right], \tag{28}$$

$$B = \frac{2\nu_c F_3}{a_1 \delta_c^2 r} A, \tag{29}$$

$$C = -\frac{F_3 F_5 \nu_c^2}{4\pi^2 a_1^2 \delta_c^2 r} A^2 = -\frac{2F_3}{F_5} \left[ 1 - \frac{1}{r} \right], \quad (30)$$

$$D = \frac{24\pi^3 F_4 \sqrt{Ta}}{-6\nu_c^2 + \pi^2 (6 + \delta_c^2)} A, \tag{31}$$

where

$$r = \frac{Ra_{nl}}{Ra_{nlc}} \tag{32}$$

is the scaled Rayleigh number.

We next study the heat transport in terms of Nusselt number.

#### D. Nusselt Number

The amount of heat transport by Rayleigh-Bénard-Taylor convection for rigid-rigid, isothermal boundaries can be quantified in terms of the Nusselt number,  $Nu_{nl}$ , as follows:

$$Nu_{nl} = \frac{\text{Heat transport by(conduction + convection)}}{\text{Heat transport by conduction}}.$$

Using Fourier first law and further simplyfying, we get:

$$Nu_{nl} = 1 + \frac{k_{nl}}{k_l} \left[ \frac{-\int_0^{\frac{2\pi}{\nu}} \left(\frac{\partial\Theta}{\partial Z}\right) dX}{-\int_0^{\frac{2\pi}{\nu}} \left(\frac{d\Theta_b}{dZ}\right) dX} \right]_{Z=-\frac{1}{2}}, \quad (33)$$

where  $k_{nl}$  and  $k_l$  are the thermal conductivities of the nanoliquid and base liquid respectively.

Substituting dimensionless form of (9) and (22) in (33) and completing the integration, we get

$$Nu_{nl} = 1 - 2\pi \frac{k_{nl}}{k_l} C.$$
 (34)

Using (30), (33) takes the form

$$Nu_{nl} = 1 + 2\frac{2\pi F_3}{F_5} \frac{k_{nl}}{k_l} \left[1 - \frac{1}{r}\right],$$

where  $F_3$ ,  $F_5$  are given by (20) and (27) and r is given by (32).

## II. CONCLUSION

From Tables I and II it is found that the thermophysical properties of the base liquid, nanoliquid and nanoparticles vary as shown below:

$$a) k_l < k_{nl} << k_{np},$$

b) 
$$(C_p)_{np} > (C_p)_l > (C_p)_{nl}$$
,

c) 
$$\rho_{np} > \rho_{nl} > \rho_l$$
,

TABLE I
THERMO-PHYSICAL PROPERTIES OF ETHYLENE GLYCOL AND COPPER
NANOPARTICLES AT 300K [18]

NANOFARTICLES AT 500K [16]		
Quantity	Ethylene Glycol	Copper nanoparticles
Donaity	01,001	nanoparates
Density	$\rho_l = 1114.4$	$\rho_{np} = 8933$
$[kg.m^{-3}]$	7 6	T NP
Specific heat	$(C_p)_l$ =2415	$(C_p)_{np}$ =385
[J/kg - K]		
Thermal conductvity	$k_l = 0.252$	$k_{np}$ =401
[W/m-K]		
Thermal expansion		
coefficient	$\beta_1$ =65	$\beta_{np} = 1.67$
$[K^{-1} \times 10^5]$	ρ[-03	$\rho_{np}$ -1.07
Dynamic coefficient		
of viscosity	$\mu_l$ =0.0157	-
[kg/m-s]		
Thermal diffusivity	0.02/2/	1165.0
$[m^2.s^{-1} \times 10^7]$	$\alpha_l$ =0.93636	$\alpha_{np}$ =1165.9
$[m^2.s^{-1} \times 10^7]$	$\alpha_l$ =0.93636	$\alpha_{np}$ =1165.9

TABLE II
THERMO-PHYSICAL PROPERTIES OF ETHYLENE GLYCOL-COPPER
NANOLIOUID AT 300K FOR VOLUME FRACTION, x = 0.1 [18]

Ethylene glycol-Copper
1896.26
1458.70
0.335824
35.1662
0.020431
1.21408
2.76607
0.666842

d) 
$$\beta_l > \beta_{nl} > \beta_{np}$$
,

$$e) \alpha_{np} >> \alpha_{nl} > \alpha_l.$$

To study the implications of linear stablity results, we may write Ra as:

$$Ra_{nl} = FRa_l,$$

where 
$$F = \begin{bmatrix} (\rho \beta)_{nl} & \mu_l & \alpha_l \\ \rho_l \beta_l & \mu_{nl} & \alpha_{nl} \end{bmatrix}$$
 and  $Ra_l = \frac{\rho_l \beta_l g h^3 \Delta T}{\mu_l \alpha_l}$ .

On further computation it is seen that the factor, F, multiplying  $Ra_l$  decreases with increase in  $\chi$ . This leads to the conclusion that the critical value of nanoliquid Rayleigh number is less than that of the base liquid without nanoparticles.

Rotation delays the onset of convection and thereby decreases heat transport. This result is shown in Fig. 2. This is because the energy of the system is used to create the component V.

The amount of heat transport increases with increase in  $\chi$  and this is depicted in Fig. 3. Increase in the value of  $\chi$  implies increase in volume fraction of nanoparticles.




Fig. 2 Variation of Nu with Ra for different values of Ta, for  $\chi$ =0.1




Fig. 3 Variation of Nu with Ra for different values of  $\chi$ , for Ta=100

#### ACKNOWLEDGMENT

One of the authors (TNS) would like to thank the Department of Backward Classes Welfare, Government of Karnataka for providing fellowship to carry out his research work. The authors would like to thank the Bangalore University for their support.

#### REFERENCES

- S. Agarwal, B. S. Bhadauria and P. G. Siddheshwar, Thermal instability of a nanofluid saturating a rotating anisotropic porous medium, Special Topics and Reviews in Porous Media: An International Journal, 2(1), 53-64, 2011.
- [2] C. Beaume, A. Bergeon, H. C. Kao and E. Knobloch, Convectons in a rotating fluid layer, Journal of Fluid Mechanics, 717, 417-448, 2013.
- [3] B. S. Bhadauria and S. Agarwal, Natural convection in a nanofluid saturated rotating porous layer: A nonlinear study, Transport in Porous Media, 87, 585-602, 2011.
- [4] J. K. Bhattacharjee, Rotating Rayleigh-Bénard convection with modulation, Journal of Physics A: Mathematical and General, 22(24), L1135, 1989.
- [5] H. C. Brinkman, The viscosity of concentrated suspensions and solutions, The Journal of Chemical Physics, 20, 571, 1952.
- [6] F. H. Busse, Thermal Convection in Rotating Systems, Proceedings of US National Congress of Applied Mechanics, American Society of Mechanical Engineers, 299-305, 1982.
- [7] S. Chandrasekhar, Hydrodynamic and Hydromagnetic Stability, Clarendon Press, London, 1961.
- [8] S. Chandrasekhar, The instability of a layer of fluid heated below and subject to Coriolis forces, Proceedings of the Royal Society of London A: Mathematical, Physical and Engineering Sciences, 217, 306-327, 1953.
- [9] S. M. Cox and P. C. Matthews, New instabilities in two-dimensional rotating convection and magnetoconvection, Physica D: Nonlinear Phenomena, 149(3), 210-229, 2001.

- [10] G. P. Galdi and B. Straughan, A nonlinear analysis of the stabilizing effect of rotation in the Bénard problem, In Proceedings of the Royal Society of London A: Mathematical, Physical and Engineering Sciences, 402(1823), 257-283, 1985.
- [11] R. L. Hamilton and O. K. Crosser, Thermal conductivity of heterogeneous two-component systems, Industrial and Engineering Chemistry Fundamentals, 1, 187-191, 1962.
- [12] E. S. Knobloch, Rotating Convection: Recent Developments, International Journal of Engineering Science, 36, 1421-1450, 1998
- [13] Y. Liu and R. E. Ecke, Heat transport measurements in turbulent rotating Rayleigh-Bénard convection, Physical Review E, 80(3), 036314, 2009.
- [14] J. M. Lopez and F. Marques, Centrifugal effects in rotating convection: nonlinear dynamics, Journal of Fluid Mechanics, 628, 269-297, 2009.
- [15] A. J. Pearlstein, Effect of rotation on the stability of a doubly diffusive fluid layer, Journal of Fluid Mechanics, 103, 389-412, 1981.
- [16] D. H. Riahi, The effect of Coriolis force on nonlinear convection in a porous medium, International Journal of Mathematics and Mathematical Sciences, 17(3), 515-536, 1994.
- [17] H. T. Rossby, A Study of Bénard Convection with and without Rotation, Journal of Fluid Mechanics, 36, 309-335, 1969.
- [18] P. G. Siddheshwar and N. Meenakshi, Amplitude equation and heat transport for RayleighBénard convection in Newtonian liquids with nanoparticles, International Journal of Applied and Computational Mathematics, 2, 1-22, 2016.
- [19] S. G. Tagare, A. B. Babu and Y. Rameshwar, Rayleigh-Bénard convection in rotating fluids, International Journal of Heat and Mass Transfer, 51, 1168-1178, 2008.
- [20] P. Vadasz, Coriolis effect on gravity-driven convection in a rotating porous layer heated from below, Journal of Fluid Mechanics, 376, 351-375, 1998.
- [21] R. K. Vanishree and P. G. Siddheshwar, Effect of rotation on thermal convection in an anisotropic porous medium with temperature-dependent viscosity, Transport in porous media, 81(1), 73, 2010.
- [22] G. Veronis, Cellular convection with finite amplitude in a rotating fluid, Journal of Fluid Mechanics, 5(03), 401-435, 1959.
- [23] D. Yadav, G. S. Agrawal and R. Bhargava, Thermal instability of rotating nanofluid layer, International Journal of Engineering Science, 49(11), 1171-1184, 2011.



P. G. Siddheshwar is a Professor of Mathematics at Bangalore University. He has more than 100 research papers at his credit on the topic of linear and non-linear stability of natural convection in Newtonian and non Newtonian clear fluids and nanoliquids in saturated porous medium with local thermal equilibrium and local thermal non-equilibrium.

**T. N. Sakshath** is a Doctoral student of Mathematics at Bangalore University. He is in the third year of his research period. His research topic is Rayleigh Bénard convection of nanoliquids in porous media.